## Final

## Phase I RFI/RI Technical Memorandum Number 1

Rocky Flats Plant Inside Building Closures (Operable Unit 15)

U S Department of Energy Rocky Flats Plant Golden, Colorado

**Environmental Restoration Program** 

May 1994

## **Final**

# Phase I RFI/RI Technical Memorandum Number 1

Rocky Flats Plant Inside Building Closures (Operable Unit 15)

U.S. Department of Energy Rocky Flats Plant Golden, Colorado

**Environmental Restoration Program** 

May 1994

700
N/UCNI 873

Technical Memorandum Number 1 for Operable Unit 15 Phase I RFI/RI Inside Building Closures

Manual Section Page RFP/ER-OU15 01-TM 01-93 TOC, Final

#### TABLE OF CONTENTS

T TO:	. O.T. m		Page
		ABLES	1V
		GURES	VI
		CRONYMS	V11
		ATA TABLE FIELD DESCRIPTIONS U15 QC CODE DESCRIPTIONS	1X
		U15 TEST GROUP DESCRIPTIONS	X
		U15 RESULT TYPE DESCRIPTIONS	X X
		EFERENCES .	XI
1.0	INTI	RODUCTION	1
	1.1	Objectives	1
		Requirements of the Interagency Agreement (IAG)	
	1.3		3 5
	1.4	Report Organization	6
2.0	HIST	TORICAL INFORMATION AND VISUAL INSPECTIONS	1
	2.1	IHSS 178	1
		2.1.1 Historical Use of IHSS 178	. 2 2 3 3 3
		2.1 2 Additional Historical Information for IHSS 178	2
		2.1.3 Visual Inspection of IHSS 178	3
	2.2		3
		2.2.1 Historical Use of IHSS 179	
		2.2.2 Additional Historical Information for IHSS 179	4
		2 2 3 Visual Inspection of IHSS 179	5
	2.3	IHSS 180	6
		2.3.1 Historical Use of IHSS 180	6
		2.3.2 Additional Historical Information for IHSS 180	7
		2.3.3 Visual Inspection of IHSS 180	7
	2.4	IHSS 204 .	7
		2.4.1 Historical Use of IHSS 204	8
		2.4.2 Additional Historical Information for IHSS 204	9
	2.5	2 4 3 Visual Inspection of IHSS 204	9
	2.5	IHSS 211	10
		2.5 1 Historical Use of IHSS 211	10
		2 5.2 Additional Historical Information for IHSS 211	11

RFP/ER-OU15 01-TM 01-93 Technical Memorandum Number 1 Manual for Operable Unit 15 Phase I RFI/RI Section TOC, Final 11 of x1 Inside Building Closures Page TABLE OF CONTENTS (continued) 12 2.5.3 Visual Inspection of IHSS 211 13 2.6 **IHSS 217** 13 2.6.1 Historical Use of IHSS 217 14 2.6.2 Additional Historical Information for IHSS 217 14 2.6 3 Visual Inspection of IHSS 217 3.0 1 **METHODS** 1 3.1 Sampling Activities 2 3.1.1 IHSS 178 - Building 881 Drum Storage Area 2 3.1.2 IHSS 179 - Building 865 Drum Storage Area 3 3.1.3 IHSS 180 - Building 883 Drum Storage Area 3 3.1.4 IHSS 204 - Unit 45, Original Uranium Chip Roaster 4 3.1.5 IHSS 211 - Unit 26, Building 881 Drum Storage Area 3.1.6 IHSS 217 - Unit 32, Cyanide Bench Scale Treatment 4 5 3.2 Sample Collection and Field Analysis Procedures 5 3.2.1 Smear Sample Collection 5 3.2.2 Hot Water Rinsate Sample Collection 3.2.3 Final Radiological Surveys 7 7 Chemical and Radionuclide Laboratory Analysis Methods 3.3 3.4 8 Data Quality Assurance/Quality Control 9 3.5 Data Processing and Storage 1 4.0 DATA QUALITY EVALUATION Phase I RFI/RI Data Quality Objectives 1 4.1 4.1.1 Characterize Site Physical Features 1 4.1.2 Define Contaminant Sources 2 2 4 1.3 Determine Nature and Extent of Contamination 3 4 1.4 Describe Contaminant Fate and Transport 3 4.1.5 Support a Baseline Risk Assessment 4 4.2 Data Useability 4 4.2.1 Quality Control 4.2 2 PARCC **EVALUATION OF RCRA-REGULATED CONSTITUENTS** 1 5.0

Approach

IHSS 178

5 2

5.1.1 Data Evaluation

5 1.2 RCRA Closure Performance Standards

1

2

3

4

Techr	nıcal M	emorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI		Section	TOC, Final	
Inside	Inside Building Closures		Page	111 of x1
<del></del>		TABLE OF CO	NTENTS (contin	nued)
	5.3	IHSS 179		5
	5.4	IHSS 180		6
	5.5	IHSS 204		7
	5.6	IHSS 211		8
	5.7	IHSS 217		9
	5.8	Summary of RCRA Evaluation	on	10
6.0	CER	CLA EVALUATION		1
	6.1 Approach			1
		6.1.1 Radionuclide Data Ev	aluation	1
		6.1.2 Radionuclide Standard	ds	4
	6.2	IHSS 178		8
	6.3	IHSS 179		9
	6.4	IHSS 180		10
	6.5	IHSS 204		12
	6.6	IHSS 211		13
	6.7	IHSS 217		14
	6.8	Summary of CERCLA Evalu		14
		6.8.1 Radionuclide Evaluati	on	15
		6.8.2 Beryllium Contaminat	ron	15
7.0	7.0 SUMMARY AND CONCLUSIONS			1
	7.1	Summary of Findings		1
	7.2	Recommendations		2
8.0	SCH	EDULE		1

Technical Memorandum Number 1			
for Operable Unit 15 Phase I RFI/RI			
Inside Building Closures			

Manual Section Page RFP/ER-OU15 01-TM 01-93 TOC, Final IV of XI

## TABLE OF CONTENTS (continued)

### List of Tables

Table 3-1	OU15 Field Investigation Activities
Table 3-2	Summary of Hot Water Rinsate Real & QA/QC Samples
Table 4-1	Comparison of Proposed to Actual Hot Water Rinsate QC Sampling
	Frequency
Table 4-2	Laboratory Qualifiers and Validation Codes
Table 4-3	Duplicate Sample Results and Relative Percent Differences
Table 4-4	Equipment Rinsate Blank Sample Results
Table 4-5	Trip Blank Sample Results
Table 4-6	Field Blank (Source Water) Sample Results
Table 4-7	Hot Water Rinsate Blank Sample Results
Table 5-1	Organic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 178
Table 5-2	Organic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 179
Table 5-3	Organic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 180
Table 5-4	Organic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 204
Table 5-5	Organic and Inorganic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 211
Table 5-6	Organic and Inorganic Compounds Detected in IHSS Hot Water Rinsate Samples - IHSS 217
Table 6-1	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 178
Table 6-2	Smear Sample Results - IHSS 178
Table 6-3	Beta and Gamma Dose-Rate Survey Data - IHSS 178
Table 6-4	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 179
Table 6-5	Smear Sample Results - IHSS 179
Table 6-6	Beta and Gamma Dose-Rate Survey Data - IHSS 179
Table 6-7	Beryllium Smear Data - IHSS 179
Table 6-8	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 180
Table 6-9	Smear Sample Results - IHSS 180
Table 6-10	Beta and Gamma Dose-Rate Survey Data - IHSS 180
Table 6-11	Beryllium Smear Data - IHSS 180
Table 6-12	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 204
Table 6-13	Smear Sample Results - IHSS 204
Table 6-14	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 211
Table 6-15	Smear Sample Results - IHSS 211
· · · · · · · · · · · · · · · · · · ·	1

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	TOC, Final
Inside Building Closures	Page	v of xı

## TABLE OF CONTENTS (continued)

Table 6-16	Beta and Gamma Dose-Rate Survey Data - IHSS 211
Table 6-17	Radionuclides Detected in Hot Water Rinsate Samples - IHSS 217
Table 6-18	Smear Sample Results - IHSS 217
Table 6-19	Beta and Gamma Dose-Rate Survey Data - IHSS 217
Table 7-1	Decision Summary Matrix

Technical Memorandum Number 1				
for Operable Unit 15 Phase I RFI/RI				
Inside Building Closures				

Manual Section Page RFP/ER-OU15 01-TM 01-93 TOC, Final vi of xi

## TABLE OF CONTENTS (continued)

## List of Figures

Figure TOC-1	Drawing Legend and Abbreviations
Figure 2-1	IHSS 178 Location
Figure 2-2	IHSS 179 Location
Figure 2-3	IHSS 180 Location
Figure 2-4	IHSS 204 Location
Figure 2-5	IHSS 204 Location
Figure 2-6	IHSS 204 Location
Figure 2-7	IHSS 211 Location
Figure 2-8	IHSS 217 Location
Figure 3-1	IHSS 178 RAD Sample Locations
Figure 3-2	IHSS 178 Rinsate Sample Locations
Figure 3-3	IHSS 179 Rad Sample Locations
Figure 3-4	IHSS 179 Rinsate Sample Locations
Figure 3-5	IHSS 180 Rad Sample Locations
Figure 3-6	IHSS 180 Rinsate Sample Locations
Figure 3-7	IHSS 204 Rad Sample Locations
Figure 3-8	IHSS 204 Rad Sample Locations
Figure 3-9	IHSS 204 Rad Sample Locations
Figure 3-10	IHSS 204 Rinsate Sample Locations
Figure 3-11	IHSS 204 Rinsate Sample Locations
Figure 3-12	IHSS 204 Rinsate Sample Locations
Figure 3-13	IHSS 211 Rad Sample Locations
Figure 3-14	IHSS 211 Rinsate Sample Locations
Figure 3-15	IHSS 217 Rad Sample Locations
Figure 3-16	IHSS 217 Rad Sample Locations
Figure 3-17	IHSS 217 Rinsate Sample Locations
Figure 3-18	IHSS 217 Rinsate Sample Locations
Figure 3-19	Hot Water Rinsate Sampling System

Technical Memorandum Number 1 for Operable Unit 15 Phase I RFI/RI Inside Building Closures Manual Section RFP/ER-OU15 01-TM 01-93 TOC, Final

Page

vii of xi

#### LIST OF ACRONYMS

BRA Baseline Risk Assessment

BU building sample

CDH Colorado Department of Health

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CFR Code of Federal Regulations
CLP Contract Laboratory Program

CRQL Contract Required Quantitation Limit

D&D Decontamination and Decommissioning

DEHP bis(2-ethylhexyl)phthalate

DOE United States Department of Energy

DQO Data Quality Objective

EB Electron Beam

EG&G Rocky Flats, Inc

EMRG Environmental Management Radiological Guidelines
EPA United States Environmental Protection Agency

FSP Field Sampling Plan

GENII Hanford Environmental Dosimetry System (Generation II)

GRRASP General Radiochemistry and Routine Analytical Services Protocol

IAG Interagency Agreement

ICRP International Commission on Radiological Protection

IHSS Individual Hazardous Substance Site

MDA minimum detectable activity

MS matrix spike

MSD matrix spike duplicate NFA No Further Action

NRC Nuclear Regulatory Commission

OU operable unit

PARCC precision, accuracy, representativeness, completeness and comparibility

QAPJP Quality Assurance Project Plan QA/QC quality assurance/quality control RCA Radiologically Controlled Area

RCRA Resource Conservation and Recovery Act
RFEDS Rocky Flats Environmental Database System

RFI RCRA Facility Investigation

RFP Rocky Flats Plant remedial investigation

ROI Radiological Operating Instruction

RPD relative percent difference

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	TOC, Final
Inside Building Closures	Page	viii of xi

RPT	Radiation Protection Technologist
SOP	Standard Operating Procedure
TAL	Target Analyte List
TC	Toxicity Characteristic
TCL	Target Compound List
TM#1	Technical Memorandum Number 1
TM#2	Technical Memorandum Number 2
VOC	volatile organic compound

| |

Technical Memorandum Number 1 for Operable Unit 15 Phase I RFI/RI Inside Building Closures

Manual Section Page RFP/ER-OU15 01-TM 01-93 TOC, Final

ix of xi

#### LIST OF DATA TABLE FIELD DESCRIPTIONS

IHSS

IHSS that sample was collected at or associated with

Sample Number

The sample identifier

**OC** Code

Quality control sample information provided by the field

QC Partner

The sample number associated with a QC sample's REAL sample is entered here. If the sample is REAL then this column is left

blank

Sample Date

The date the sample was collected

Test Group

Also referred to as the method code This is a RFEDS code for

the method used to analyze a group of samples

Result Type

RFEDS codes that differentiate between target analytical results, laboratory quality assurance samples, and laboratory reanalysis. This field specifically distinguishes the multiple analytical attempts when more than one analysis attempt was necessary or requested.

Compound/Radionuclide

The analyzed compound/radionuclide name

Result

Concentration numeric value

Error

The counting error The error is a measure of the variability of the instrument reading during sample counting. Error data is

provided for radionuclide analyses only

Qualifier

A code which indicates qualifications or limitations to the reported

result

Detection Limit

The detection limit specified for the analysis type as required in the GRASP For diluted samples, the detection limit is corrected

for the dilution factor

Validation Code

Validation code for the result

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	TOC, Final
Inside Building Closures	Page	x of xi

### LIST OF OU15 QC CODE DESCRIPTIONS

OC CODE	DESCRIPTION
DUP FB REAL RNS TB	Duplicate sample taken in the field Field blank (source water sample) Real sample Equipment rinsate blank following decontamination Trip blank

#### LIST OF OU15 TEST GROUP DESCRIPTIONS

TEST GROUP	DESCRIPTION	
BNACLP	Semi-volatile organic compounds	
DMETADD	Dissolved metals (additional list)	
DSMETCLP	Dissolved metals (CLP list)	
DRADS	Dissolved radionuclides	
VOACLP	Volatile organic compounds	
WQPL	Water quality parameters (cyanide)	

#### LIST OF OU15 RESULT TYPE DESCRIPTIONS

RESULT TYPE	DESCRIPTION	<del></del>
DIL DL1 REP TRG	Dilution Dilution Replicate Target	

Technical Memorandum Number 1				
for Operable Unit 15 Phase I RFI/RI				
Inside Building Closures				

Manual Section Page RFP/ER-OU15 01-TM 01-93 TOC, Final xi of xi

#### LIST OF REFERENCES

EG&G, 1991: EG&G Rocky Flats, Inc, "General Radiochemistry and Routine Analytical Services Protocol (GRRASP)," Golden, Colorado, 1991

EPA, 1988: Limiting Values of Radionuclide Intake and Air Concentration and Dose Conversion Factors for Inhalation, Submersion, and Ingestion, Federal Guidance Report No 11, EPA-520/1-88-020

EPA, 1989: United States Environmental Protection Agency, "Risk Assessment Guidance for Superfund Volume I, Human Health Evaluation Manual (Part A)," Interim Final, Washington, D C, EPA, Office of Emergency and Remedial Response, EPA/540/1-89/002, 1989

EPA, 1993: External Exposure to Radionuclides in Air, Water, and Soil Federal Guidance Report No 12, EPA-402-R-93-081

Hawley, 1985: J K Hawley, "Assessment of Health Risk from Exposure to Contaminated Soil," Risk Analysis, Vol 5, No 4, pp 289-302, 1985

Napier, et. al., 1988: B A Napier, R A Peloquin, D L Strenge, and J V Ramsdell, "GENII - The Hanford Environmental Radiation Dosimetry Software System, Volumes 1 through 3," Pacific Northwest Laboratory, PNL-6584, 1988

NRC, 1990: Nuclear Regulatory Commission, "Residual Radioactive Contamination From Decommissioning," Draft, Washington, D C, Division of Regulatory Applications, Office of Nuclear Regulatory Commission, NUREG/CR-5512, PNL-7212, 1990

NRC, 1993: Nuclear Regulatory Commission, "Residual Radioactive Contamination From Decommissioning," Final, Washington, D C, Division of Regulatory Applications, Office of Nuclear Regulatory Commission, NUREG/CR-5512, PNL-7212, 1993

## DRAWING LEGEND

SMEAR SAMPLE/FINAL RADIOLOGICAL SURVEY LOCATION 1

SMEAR SAMPLE/FINAL RADIOLOGICAL SURVEY NUMBER

BU00050ER 4472046

HOT WATER RINSATE SAMPLE LOCATION

BU00050ER

HOT WATER RINSATE SAMPLE NUMBER

4472046

HOT WATER RINSATE SAMPLE LOCATION CODE



IHSS LOCATION

ROOM/EQUIPMENT BOUNDARY


CL

COLUMN



DOOR

OBSTRUCTED SPACE BOUNDARY



EYE WASH



PUMP



HEATING ELEMENT

## **ABBREVIATIONS**

ACT ACTIVATED

BLDG BUILDING

DIA DIAMETER

EΒ ELECTRON BEAM

HEPA HIGH EFFICIENCY PARTICULATE AIR

NO NUMBER

RAD RADIOLOGICAL

VAC VOLTS-ALTERNATING CURRENT

																-
KEYWORDS	Α	ORIGIN	IAL ISSU	JE		XX/X	X/93	RCH	KAS	PRB	OLS		T			-
1 0015	SSUC		DESC	RIPTION		DA	TE		R	FP		DOE	OLAS	9 JOB	NO	-
2 PHASE I 3 RFI/RI	$\Lambda$	/	DESIGNED	HEA	xx/xx/93	-	ROCKY					T OF E		Y OLORADO	,	Dat M
+ TECH MEMO	<u> </u>		DRAWN	SCHACKLIN			F	200	k	, 1	Fla	ts 1	Pla	nt		H
S NUMBER 1	-	$\bigvee$	CHECKED	SCHUBBE	xx/xx/93 xx/xx/93	┧			GC	OLDE	OCOL	ORADO (	50401			1
SITE ROOM/AREA	↓ ,	$/ \setminus$				_				_	HASE			10		Ę.
GEN GRID COOR./COL NO.	1/			<u> </u>		1	ΑN		۷۷۶ A	BE	SR.	LE( EVIA	<b>17</b> /	ZNC ZNC	ì	1
L	V	\		BIERBAUM	XX/XX/93	SIZE		DR/		NUM			SSUE	PIGU		ħ.,
MASTER YES □ NO 🖾	L	ONE	APPROVED APPROVED	1		В							A	TOC	-1	X

## Section 1.0

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	1 0, Final
Inside Building Closures	Page	1 of 6

#### 1.0 INTRODUCTION

This document, Technical Memorandum Number 1 (TM#1), supports the Operable Unit 15 (OU15) Phase I Resource Conservation and Recovery Act (RCRA) Facility Investigation/Remedial Investigation (RFI/RI) activities at the Rocky Flats Plant (RFP) as outlined in the Final Phase I RFI/RI Work Plan for OU15 (the Work Plan) Technical memoranda are required to describe the field sampling activities and the Baseline Risk Assessment (BRA) in accordance with the following documents

- PREP Interagency Agreement (IAG) (January 22, 1991) between the United States Department of Energy (DOE), the United States Environmental Protection Agency (EPA), and the State of Colorado Department of Health (CDH), and
- Final Phase I RFI/RI Work Plan for RFP Operable Unit 15 Inside Building Closures (March 23, 1993)

TM#1 describes the implementation of the Work Plan Field Sampling Plan (FSP) and provides the results of completed sampling activities. If necessary, a Baseline Risk Assessment (BRA) will be performed and documented in Technical Memorandum #2 (TM #2). This document does not address the BRA. The OU15 Phase I RFI/RI Report will be based on TM#1 and, if required, TM#2

#### 1.1 Objectives

Sections 4.1 of the Work Plan provides the overall objectives of the OU15 Phase I RFI/RI. The Work Plan provides a technically adequate basis for characterization of indoor contamination at the Individual Hazardous Substance Sites (IHSSs) which compose OU15. Its general purpose is to

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	1 0, Final
Inside Building Closures	Page	2 of 6

- 1 Characterize the nature and extent of contamination associated with the OU15 IHSSs
- 2 Determine whether releases have occurred from any of the OU15 IHSSs
- 3 Support the BRA and closure activities
- 4 Determine the need for additional investigation (Stage III outdoor)

In complying with the requirements of the IAG as they apply to OU15, both RCRA and Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) concerns must be addressed. In the case of OU15, the two environmental acts have defined objectives in terms of the specific evaluations to be performed in the Phase I RFI/RI. Specifically

- The RCRA regulations apply to the closure of RCRA-regulated units within OU15 and address only RCRA-regulated constituents that have been released or are located within the unit boundaries. The RCRA closure performance standards are addressed in the Work Plan and are defined in the RFP State RCRA Permit.
- CERCLA requirements specify that the remediation of an operable unit be performed in such a manner as to be protective of human health and the environment. In the case of RCRA-regulated units, the CERCLA requirements are satisfied through application of the RCRA closure performance standards to each IHSS for RCRA-regulated constituents, because the RCRA closure performance standards are more stringent than the general protectiveness standards of CERCLA. Therefore, the CERCLA evaluation for OU15 is restricted to determining protectiveness as it relates to the radionuclides present at IHSSs within OU15.

This document presents the methods and results associated with the OU15 Stage I and II field investigations. It provides the decision basis for recommending whether additional outdoor investigation should be performed and for determining whether additional indoor investigation (i.e., verification sampling) is required to show that the IHSSs meet the clean closure performance standards defined in the Work Plan. For each

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	1 0, Final
Inside Building Closures	Page	3 of 6

IHSS, the decision regarding the need for Stage III investigation is based on an evaluation of release potential and mechanisms, and on historical use and release reports which indicate whether any releases are known to have occurred. Clean closure status for each IHSS is determined by comparing organic and inorganic contaminant concentrations to levels established in the RFP State RCRA Permit. The evaluation of radiological constituents is based on comparing the dose associated with those constituents to the standards specified in the Work Plan.

To maintain contact with the various parties involved and ensure concurrence on technical issues as the project proceeds, TM#1 will be prepared and submitted to EPA and CDH prior to the submission of the Draft Phase I RFI/RI Report for OU15 Following approval by EPA and CDH, TM#1 will form the basis for the Draft Phase I RFI/RI Report, therefore, early concurrence on the technical issues addressed here will minimize the report comment and revision cycle

#### 1.2 Requirements of the Interagency Agreement (IAG)

In accordance with the IAG, the OU15 Phase I RFI/RI includes IHSSs 178, 179, 180, 204, 211, and 217 OU15 originally comprised of eight IHSSs, however, IHSSs 212 and 215 are no longer included as part of this investigation. The closure of IHSS 212 is now addressed in Part VIII of the RFP RCRA Mixed Residue Permit Modification. If any corrective action under CERCLA is necessary, the work will be performed pursuant to the IAG, including the issuance of a decision document to close the unit. IHSS 215 was transferred to Operable Unit 9 (OU9) in a Modification to Work of the IAG dated April 21, 1992, and has already been included in the Phase I RFI/RI for OU9

The Final Phase I RFI/RI Work Plan (dated March 23, 1993) was approved for OU15 in accordance with the IAG Following completion of the work, the Draft Phase I RFI/RI Report must be submitted by the IAG milestone date of August 1, 1994 The

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	10, Final
Inside Building Closures	Page	4 of 6

Draft Phase I RFI/RI Report must contain a Preliminary Site Characterization Summary describing the OU, and the nature and extent of contamination with data sufficient to support a BRA for OU15, if one is required. The Draft Report must also contain the BRA and an identification of any releases from OU15 (or IHSSs within OU15) and any areas which may have been impacted by such releases. The Final Phase I RFI/RI Report must be submitted by the IAG milestone date of January 4, 1995. If it is determined that no additional investigation is required at OU15, the Final Phase I RFI/RI Report for OU15 will become the Final RFI/RI Report. Otherwise, a second phase of investigation will be initiated.

In accordance with Section I B II a of the IAG, additional action at an IHSS within OU15 may be required if

- There has been a release of hazardous constituents or hazardous substances to the environment external to the IHSS, or
- There is a threat of post-closure escape of hazardous waste, hazardous constituents, leachates, run-off, hazardous waste decomposition products, or hazardous substances

If there has been no releases and there is no threat of release at an IHSS, then further action will not be required

Prior to submission of the Draft Phase I RFI/RI Report, the IAG requires that DOE submit to EPA and CDH a series of four technical memoranda describing the BRA, including

- 1 Contaminant Identification and Documentation,
- 2 Exposure Assessment and Documentation,
- 3 Toxicity Assessment and Documentation, and
- 4 Risk Characterization

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	1 0, Final
Inside Building Closures	Page	5 of 6

This document (TM#1) fulfills the Work Plan requirement of submittal of an FSP Technical Memorandum describing the field sampling activities and results

#### 1.3 Scope of Work

The scope of work for the Phase I RFI/RI at OU15 was approved in the Final Phase I RFI/RI Work Plan, dated March 23, 1993 This section briefly describes the key work elements contained in the Work Plan

Sampling and inspection activities were conducted from April 23, 1993 to November 9, 1993 for Stage I and II of the OU15 Phase I RFI/RI at the following IHSSs

IHSS 178	Building 881, Drum Storage Area (Room 165)
IHSS 179	Building 865, Drum Storage Area (Room 145)
IHSS 180	Building 883, Drum Storage Area (Room 104)
IHSS 204	Building 447, Unit 45, Original Uranium Chip Roaster (Rooms 32 and 502)
IHSS 211	Building 881, Unit 26, Drum Storage Area (Room 266B)
IHSS 217	Building 881, Unit 32, Cyanide Bench Scale Treatment (Room 131C)

The Phase I RFI/RI investigation included surface sampling for chemical and radiological contamination in each of the above IHSSs, but did not include collection of any samples of environmental media (soil, air, water) Analytical parameters were selected for each IHSS based on its previous uses, and included volatile and semi-volatile organic compounds, metals, cyanide, and radionuclides

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	1 0, Final
Inside Building Closures	Page	6 of 6

Samples were collected from surfaces (1 e , floors and structures) within each IHSS as well as from areas defined as "perimeter" and "pathway" areas. Perimeter and pathway areas were selected to determine whether contamination from within an IHSS has migrated out of the IHSS. The data collected at each sampling location included hot water rinsate samples, beryllium and radiological smear samples, and fixed radiation surveys.

The details of the scope of work for the OU15 Phase I RFI/RI are presented in the Work Plan and are summarized in Section 3 0 of this document

#### 14 Report Organization

Section 2 0 of this document summarizes the historical information available for each IHSS and presents the results of the visual inspections for each IHSS. Section 3 0 describes the methods used to collect the Stage I and II samples. Section 4 0 discusses the OU15 Phase I RFI/RI data quality objectives and compares the Stage I and II sampling results to these objectives. Section 5 0 presents the Stage I and II organic and inorganic analytical data and compares them to the RCRA closure performance standards. Section 6 0 presents the Stage I and II radiological data and evaluates them with respect to CERCLA requirements. Section 7 0 summarizes the results of the RCRA and CERCLA evaluations for each IHSS. Finally, Section 8 0 contains the schedule for performing additional OU15 activities.

In addition to this Technical Memorandum, the analytical database for the project is being transmitted under the same cover on diskette

Section 2.0

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	1 of 15

#### 2.0 HISTORICAL INFORMATION AND VISUAL INSPECTIONS

This section summarizes the historical use and presents the visual inspection findings for each of the six IHSSs which compose OU15. Visual inspections of each IHSS were completed before sampling activities began. Drawings of each IHSS were developed from measurements taken during the visual inspections. A legend describing the symbols and abbreviations used on the IHSS drawings is provided in the Table of Contents.

Visual inspections were performed to assess the configuration of the units, to identify the presence and condition of berms or other secondary containment systems, and to document the conditions of the floors. The floors were inspected for slopes, cracks, and/or worn areas that might represent contaminant migration pathways and the presence of any sumps or drains. Visual inspections were performed at each IHSS prior to sampling activities.

Additional research on the historical uses of and releases from each IHSS was completed as part of the Stage I and II field investigations. The research consisted of document and database reviews and interviews with RFP building personnel. The documents and database reviewed included the Draft and Final "Historical Release Reports" for the Rocky Flats Plant, the "Task 3/4 Draft Report. Rocky Flats History," and the EG&G Spill/Release Database.

#### 2.1 IHSS 178

IHSS 178 is a drum storage area located in Room 165 of Building 881 (Figure 2-1) The following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 178

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	2 of 15

#### 2.1.1 Historical Use of IHSS 178

IHSS 178 is a drum storage area located within Room 165 on the first floor of Building 881. There is no basement beneath Room 165. The drum storage area was first used in 1953 when Building 881 operations began. Currently IHSS 178 is used as a RCRA 90-day accumulation area.

The drums stored at this IHSS contained wastes generated within Building 881 Analytical results for wastes from Building 881 typical of those stored in IHSS 178 are presented in the Work Plan These drums contained volatile organic compounds (VOCs) (Freon TF and 1,1,1-trichloroethane), carbon dioxide and possibly low-level radioactive wastes

Routine visual monitoring for spills and/or releases was conducted during the period of operation of this storage unit. However, the visual monitoring frequency is not presently known. As part of the development of the closure plan for this unit, a site visit was performed during November 1986. At that time, there was no visual evidence or documentation of any spills or releases in the storage unit. Five 55-gallon drums were stored at this IHSS in November 1986.

#### 2.1.2 Additional Historical Information for IHSS 178

According to the Final Historical Release Report, "no documentation was found that indicates a release to the environment" During a site visit on April 28, 1994, no hazardous waste was being accumulated in the area RFP building personnel indicated that no hazardous waste had been accumulated in the room for some time (timeframe not specified) A review of inspection logs which dated from March 1, 1989 through April 27, 1993 revealed no information documenting or alluding to any spills or releases of hazardous wastes or constituents

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	3 of 15

#### 2.1.3 Visual Inspection of IHSS 178

As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 178 At the time of the visit, no drums were stored in the IHSS. The IHSS is located in Room 165 of Building 881, on the floor adjacent to the access door for the building plenum in Room 164. The IHSS was demarcated by two painted circles, each approximately four feet in diameter, that straddle a building column At the time of the inspection, there were no access restrictions to the IHSS itself.

A maximum of five 55-gallon drums could be stored in the IHSS at one time. There were no secondary containment berms present around the IHSS or at the doors, and no discernable slope was noted for the floor. With the exception of the IHSS circles, the majority of the concrete floor in Room 165 was not painted. The unpainted concrete did have a finishing coat and was in good condition.

#### 2.2 IHSS 179

IHSS 179 is a drum storage area located in Room 145 of Building 865 (Figure 2-2) The following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 179

#### 2.2.1 Historical Use of IHSS 179

IHSS 179 is a drum storage area located in the north end of Room 145, which is situated on the ground floor in the center of Building 865. Drum storage in IHSS 179 began in 1970. By November 1986, IHSS 179 was being used as a RCRA 90-day accumulation area. The maximum inventory stored in the IHSS at any one time was ten 55-gallon.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	4 of 15

drums The drums stored in IHSS 179 were placed directly on the concrete floor No containment berms were present immediately adjacent to the IHSS

Samples were obtained from drums stored in IHSS 179 during May and July 1986, and analyzed for total alpha, beryllium, and select organic compounds. Total alpha, beryllium, and certain organic compounds were detected in one or both of the drums sampled. The results of the analyses are presented in the Work Plan.

During a site visit in November 1986, two drums were being stored in the IHSS. The drums contained oils, chlorinated solvents, radioactive waste, and possibly beryllium. Shortly thereafter, the use of chlorinated solvents was eliminated in the area where the wastes stored in IHSS 179 were being generated. Consequently, after 1986, it is likely that the waste drums stored in IHSS 179 contained only oil possibly contaminated with beryllium and radioactive waste.

The drums stored in IHSS 179 were visually monitored daily for spills and releases. There have been no documented releases and based on prior visual inspections, and there was no evidence of spills. If any spills from the drums did occur, the spilled material may have collected in the concrete pit underneath the Electron Beam (EB) welder, located north of the IHSS. The pit has a sump with an automatic pump operated by a float switch. Accumulated liquids would have been transferred via overhead piping and the valve vault system to Building 374 for treatment.

#### 2.2.2 Additional Historical Information for IHSS 179

The Final Historical Release Report states, "There have been no documented releases and based on a visual inspection on November of 1986, there was no visual evidence of spills"

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	5 of 15

The Task 3/4 Draft Report indicates that the following chemicals of concern have been used in Room 145 chromium boride, chromium carbide, chromium silicide, lead powder, nickel, and nitric acid. It should be noted that Room 145 is a large process area, and involves many operations not associated with the drum storage area.

A report generated from the EG&G Spill/Release Database indicates that approximately 50 gallons of process water was released in Room 145 on April 6, 1990. According to the report, "50 gallons of Process Waste was released to the Mezzanine and floor of Room 145 after a pipe union broke. Samples were taken for analysis, and the spill was vacuumed up and returned to the Process Waste system by 0930."

#### 2.2.3 Visual Inspection of IHSS 179

As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 179 At the time of the visit, no drums were stored in the IHSS The IHSS was located, in Building 865, on the floor of Room 145 in front of a large electrical panel, and was painted to mark its location. Its dimensions were approximately 8 feet by 12 feet. Markings were also present to identify the access requirements for the electrical panel. At the time of the inspection, there were no access restrictions to the IHSS itself, other than those associated with the Radiologically Controlled Area (RCA) in which it is located

There were no secondary containment berms present around the IHSS The floor sloped north towards a concrete pit in the floor under the EB welder. The concrete floor in the IHSS and surrounding area was painted and was in good condition.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	6 of 15

#### 2.3 IHSS 180

IHSS 180 is a drum storage area located in Room 104 of Building 883 (Figure 2-3) The following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 180

#### 2.3.1 Historical Use of IHSS 180

IHSS 180 is a drum storage area located within Room 104 of Building 883 Room 104 was added on to the east side of the original building and was built on a grade. The area was first used as a container storage area in 1981 and has been used as a 90-day accumulation area for RCRA-regulated wastes for part of its operational history

The storage area within Room 104 measures 10 feet by 16 feet. The unit stored a maximum of thirty 55-gallon drums, which were placed directly on the floor. There are no containment berms around the drums and no drains in the floor.

Samples from drums stored in the area were obtained on five separate dates and analyzed for total alpha, beryllium, and "general components" The results of the analyses are presented in the Work Plan As indicated by the analytical results, VOCs, beryllium, and radioactivity were present in the drums sampled. The wastes included oils contaminated with organic compounds and uranium. Visual monitoring of the storage area was conducted periodically, but the frequency is not presently known. No documentation indicating a release from drums stored at this IHSS was found.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	7 of 15

#### 2.3.2 Additional Historical Information for IHSS 180

According to the Final Historical Release Report, "There have been no documented releases and, based on a visual inspection on November of 1986, there was no visual evidence of spills or leakage" No additional information on the wastes stored in the IHSS was found

#### 2.3.3 Visual Inspection of IHSS 180

As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 180 At the time of the visit, no drums were stored in the IHSS, but the unit was designated for storage of low-level radioactive waste (non-hazardous) The IHSS was located on the floor of Room 104 in Building 883, and was painted to mark its location. At the time of the inspection there were no access restrictions to the IHSS itself, other than those associated with the RCA in which it is located.

There were no secondary containment berms present around the IHSS or at the dock door leading from Room 104 to the outside of the building. The floor sloped from the IHSS toward the weigh scale, which was housed in a concrete pit recessed in the floor, and not toward the dock door. The concrete floor in the IHSS and surrounding area was painted, but was scuffed and in poor condition.

#### 2.4 IHSS 204

IHSS 204 (also known as RCRA Unit 45) is the Original Uranium Chip Roaster located in Rooms 32 and 502 in Building 447 (Figures 2-4 and 2-5). Access to the unit is provided by Rooms 31 and 501. An equipment wash rack/drum washing basin associated with the Original Uranium Chip Roaster is located in Room 501 (Figure 2-6). The

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	8 of 15

following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 204

#### 2.4.1 Historical Use of IHSS 204

The Original Uranium Chip Roaster is located in Rooms 32 and 502 of Building 447, and is constructed of mild steel casing lined with alumina refractory brick. It is cylindrical with a diameter of 5 feet 6 inches and a height of 7 feet 4 inches. The unit was identified as Unit 45 in the 1986 RCRA Part B permit application.

The unit oxidizes elemental uranium to uranium oxide. Depleted uranium chips originated from the Building 444 production area and were historically coated with small amounts of oils and coolants (Freon TF and 1,1,1-trichloroethane). Chips were stored in 55-gallon drums and transferred to Building 447 for roasting. Currently, the Original Uranium Chip Roaster is still operational, however, the uranium chips are no longer coated with oils or coolants that are RCRA-regulated hazardous wastes.

Before roasting, the chips were rinsed with hot water to remove excess coatings. The rinsate was disposed of in the building process drain. The chips were fed into the top of the roaster at a rate of approximately three 55-gallon drums per day. The chips ignited upon entry and sustained self-combustion throughout the roasting cycle. When the roasting cycle was complete, the uranium oxide was removed through a hole in the bottom of the unit and was collected in 30-gallon drums.

An incident involving the roaster occurred in Room 32 of Building 447 on June 28, 1985. The ignition of some cardboard in the room set off the sprinklers and fire alarm, and flooded the basement of the building. A second incident, indirectly related to this IHSS occurred on July 20, 1986. During a major rain event, a main 36-inch storm.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	9 of 15

sewer/drainage system collapsed and flooded portions of Buildings 444 and 447 In Building 447, several inches of water accumulated throughout the process areas The basement, including Room 32, was flooded with several feet of water

#### 2.4.2 Additional Historical Information for IHSS 204

The Final Historical Release Report states, "Because of the operating temperatures of the roaster and the chemical and physical properties of freon TF and 1,1,1-trichloroethane, it is not expected that any residual material remains in this unit "RFP building personnel indicated that there have been no spills or releases associated with this unit during their tenure with the building over the last 15 years. They added that no hazardous constituents (e.g., solvents) have been used in association with the unit since January of 1988.

#### 2.4.3 Visual Inspection of IHSS 204

As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 204 At the time of the visit, approximately twelve drums were stored in Room 32, and six drums were stored in Room 502 Miscellaneous equipment including ladders and drum dollies were also present in both rooms. No drums or equipment were present in the Wash Rack/Drum Washing Basin, which is located in Room 501. The Original Uranium Chip Roaster spans two floors. The chip inlet is located upstairs in Room 502, and the main body of the roaster, including the oxide outlet ports, is located in Room 32, directly beneath Room 502. At the time of the inspection there were no access restrictions in Rooms 31 and 501, other than those associated with the RCA in which they are located. However, entry into Room 32 required use of Anti-C clothing, and entry into Room 502 required use of a full-face respirator.

Technical Memorandum Number 1	Manual	RFP/ER-OU15.01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	10 of 15

There were no secondary containment berms present around Rooms 32 or 502 No discernable slope was noted for the floors in either room. The concrete floor in both rooms was painted and generally in good condition, although black dust was visible on the floors and exterior surfaces of the chip roaster in both rooms. The concrete pad and berm of the Wash Rack/Drum Washing Basin was in good condition with no apparent gaps or cracks. The floor in the basin sloped to a process drain located in the center of the pad.

#### 2.5 IHSS 211

IHSS 211 (also known as RCRA Unit 26) is a drum storage area located in Room 266B of Building 881 (Figure 2-7) The following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 211

#### 2.5.1 Historical Use of IHSS 211

IHSS 211 is a drum storage area located in Room 266B on the second floor annex of Building 881 Since May 16, 1989, IHSS 211 has been operating as a RCRA 90-day accumulation area Prior to this time, the unit was a drum storage area for mixed waste and was included in the hazardous and low-level mixed waste RCRA Part B permit application as Unit 26 The unit was first used as a drum storage area in 1981

The wastes stored in the unit have historically included both liquids and solids generated from the general laboratories in the building. The waste streams currently approved for storage in Unit 26 include low-level combustible waste possibly contaminated with

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	11 of 15

hazardous solvents and/or metals, and metal and glass waste or materials contaminated with hazardous solvents. There was no recorded documentation of a spill or release in the unit

#### 2.5.2 Additional Historical Information for IHSS 211

According to the Final Historical Release Report, there is no indication that hazardous waste or constituents have been released in association with this area. A review of inspection logs which dated from March 1, 1989 through April 27, 1993 revealed no information documenting or alluding to any spills or releases of hazardous wastes or constituents

The Task 3/4 Draft Report indicates that the following chemicals of concern have been used in Room 266 carbon tetrachloride, chloroform, and nickel catalyst. It should be noted that Room 266 is separated from Room 266B by a wall and a sealed doorway. The same report indicates that the following chemicals have been used in Building 881 laboratories benzene, beryllium, cadmium and cadmium compounds, carbon tetrachloride, chloroform, chromium and chromium compounds, lead and lead compounds, mercury, methylene chloride, nickel and nickel compounds, nitric acid, tetrachloroethylene, 1,1,1-trichloroethane, and trichloroethylene

A report generated from the EG&G Spill/Release Database indicates that 2 5 gallons of nitrate solution was released in Room 266 on January 21, 1991. According to the report, the "scrubber hose came loose from the pump and sprayed a lab hood and into the ceiling tile. The pump was shut off and the leak was stopped." The waste was collected in the waste vacuum cleaner and managed in the waste process drain.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	12 of 15

#### 2.5.3 Visual Inspection of IHSS 211

As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 211 At the time of the visit, there were seven 55-gallon drums located in the IHSS Six of the drums contained solid waste, and one of the drums contained liquid waste and was in a catch pan. Access to the IHSS was restricted by a locked cage door

The drum storage area was 10 feet by 20 feet and could store a maximum of twenty-nine 55-gallon drums at one time. The floor was constructed of concrete, which was sealed with epoxy paint. Drums were stored directly on the floor or in catch pans. Weekly container inspections were conducted to visually assess the structural integrity of the drums and to check for leaks and spills.

There were no secondary containment berms around the storage area, at the entrance to the IHSS, or under the sealed door at the back of the IHSS. The concrete floor, painted with an epoxy coating, was in good condition, however, a sealed crack in the floor approximately one to two inches wide ran the length of the room. RFP building personnel were unfamiliar with when the crack had first appeared and how often it had been repaired, but indicated that the crack had most recently been repaired approximately one month prior to the site visit. RFP building personnel added that the crack may have originally been narrower, and may have been ground out at the surface to facilitate its repair.

Since the building is partially below grade, ground water may leak into Building 881 in the vicinity of Room 266B. Room 266B had two catch pans positioned approximately 6 inches under the ceiling to collect potential seepage into the room. The catch pans drained to collection bottles on the floor. Additional catch pans and collection bottles were located in the hallway outside of the IHSS.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	13 of 15

#### 2.6 IHSS 217

IHSS 217 is the cyanide bench scale treatment unit (RCRA Unit 32) located in Room 131C of Building 881 (Figure 2-8) The following subsections summarize the historical use of the IHSS as documented in the Work Plan, present additional historical information, and describe the findings from the visual inspection of IHSS 217

#### 2.6.1 Historical Use of IHSS 217

IHSS 217 is a cyanide bench scale treatment process (RCRA Unit 32) located in Room 131C, on the first floor of Building 881. The unit consisted of a 4 feet by 5 feet painted metal fume hood and laboratory table, three 4-liter polyethylene bottles, a glass beaker, and a chlorine-specific ion electrode. The laboratory table and metal fume hood were originally installed in 1952. No information was available regarding the operational history of this unit prior to its use for treatment of cyanide. The hood appeared to be made of metal covered with a coat of paint. The hood had an integral lip across the front which provided containment of any wastes spilled within the hood.

The bench scale treatment process converted cyanide to cyanate. Aqueous cyanide solutions were transferred to Unit 32 for analysis of cyanide content using a cyanide still. Very low concentrations of other listed hazardous wastes may have been in these solutions. Wastes generated from this analysis were collected in the three 4-liter polyethylene bottles stored in the steel fume hood of the unit. The bottom of the fume hood acted as a secondary containment system in the event of a spill. There was no automated monitoring system for detecting releases. No more than five liters of the cyanide waste were stored in the unit at any given time. The cyanide solution was treated in a 4-liter bottle with sodium or calcium hypochlorite to oxidize the cyanide to cyanate. A residual chlorine-specific ion electrode was used to determine when the

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	2 0, Final
Inside Building Closures	Page	14 of 15

conversion was complete. There have been no documented releases from the polyethylene bottles or spills during transfer or neutralization.

The neutralized solution was poured down a process waste drain located in Room 131C and transferred via the process waste line system to Building 374 for further treatment Since the drain is also used for disposal of other wastes generated in the laboratory, the drain and the associated piping will be investigated separately from IHSS 217

#### 2.6.2 Additional Historical Information for IHSS 217

According to the Final Historical Release Report, the cyanide bench scale treatment unit was used from 1986 until September of 1988. The report states, "No documentation was found which indicated a release to the environment." A review of inspection logs which dated from March 1, 1989 through April 27, 1993 revealed no information documenting or alluding to any spills or releases of hazardous wastes or constituents. The Task 3/4 Draft Report indicates that the following chemicals of concern have been used in Room 131C. nitric acid, potassium chromate, and lead standard.


#### 2.6.3 Visual Inspection of IHSS 217


As part of the OU15 Phase I RFI/RI, the site was visited on April 23, 1993 to visually observe the condition of IHSS 217 At the time of the visit, the unit was not operational Two permanently attached crucibles and a removable tray were present on top of the laboratory table surface. Some staining was evident on both the laboratory table and fume hood surfaces. At the time of the inspection there was an Operational Safety Approval requirement for access into the fume hood.


Secondary containment for the laboratory table was provided by the fume hood itself and a lip on the front side of the table. The floor in Room 131C was covered with linoleum


Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	20, Final
Inside Building Closures	Page	15 of 15


tiles which appeared to be in good condition but had some staining. There were no secondary containment berms present around Room 131C
















WASH RACK/DRUM WASHING BASIN

KEYWORDS	A	ORIGIN	IAL ISSU	JΕ		xx/xx	/93 A	КСН	SPL	DAW	DLS		Т	Τ	
1 0015	SSVE	DESCRIPTION			DAT	Ē		R	P		DOE	مم	19	JOB NO	
2 PHASE I 3 RFI/RI		/	DESIGNED	HEA	xx/xx/93	N	OCKY F						ENERO KOLDEN (		RADO
TECH MEMO	$ \cdot $	. /	DRAWN	SCHACKLIN	12/20/93		R	00	ky	, 1	·la	ts	Pla	nt	
S NUMBER 1	1	\	CHECKED	WEAVER	XX/XX/93	COLOFU COLOGO 60401									
BLDG. /FACILITY	1	χ	APPROVED	SCHUBBE	XX/XX/93										
447		/\	ļ					_0	U1	5 PI	IASE	I R	FI/RI		
RÓOM/AREA 501	] /					1	HS	S	2	0	4	LO	CA	TIC	NC
GRED COOR./COL NO	V	\	SUBMETTED	BIERBAUM	XX/XX/93	SIZE		DRAY	MNG	NUM	BER		ISSUE	r	PIGURE
MASTER	1 '	CALE.	APPROVED		,	Б	II.	10	C	7	04	1	۸	7	2 6
YES [] NO [X]	12	SNE	APPROVED DOE			101	١r	10	J		٠U٤	+	14	4	0





Section 3.0

4

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	1 of 10

#### 3.0 METHODS

This section summarizes the sampling and analysis performed during the combined Stage I and II field investigation. It also describes the FSP sampling, analytical, and quality assurance/quality control (QA/QC) procedures that were followed. Additional detail on the FSP is provided in Section 7.0 of the Work Plan.

# 3.1 Sampling Activities

Sampling activities were conducted from April 23, 1993 to November 9, 1993 to characterize contamination inside and around the perimeter of each IHSS Samples were also collected along pathways outside the perimeter and leading away from the IHSS that might have been impacted by spilled material migrating out of the IHSS

Activities performed as part of the investigation included

- a review of new and/or additional information (documented in Section 2 0),
- a visual inspection and documentation of current conditions (documented in Section 2 0), and
- the sampling and analysis of surfaces within each IHSS area

Sampling was conducted to characterize contamination within the IHSS, perimeter, and pathway areas. Smear sampling for removable radiological (alpha and beta) and, if appropriate, beryllium contamination was performed first. This was followed by hot water sampling and rinsate analysis for Target Compound List (TCL) VOCs, TCL semi-volatile organic compounds, Target Analyte List (TAL) dissolved metals, dissolved radionuclides, and cyanide, as appropriate for each IHSS. Finally, a second set of removable alpha, beta, and (if applicable) beryllium analyses, along with fixed alpha and

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	2 of 10

beta analyses, and beta and gamma dose-rate surveys were performed, as appropriate for each IHSS

The combined Stage I and II investigation programs for each IHSS are summarized in Table 3-1 which details the field sampling and analysis completed. Additional information regarding the number and location of radiological and hot water rinsate samples collected for each IHSS is included in the following subsections.

# 3.1.1 IHSS 178 - Building 881 Drum Storage Area

Following the review of new data and information, and after the visual inspection of IHSS 178, 30 radiological smear samples were collected at the locations shown in Figure 3-1. Three hot water rinsate samples were then obtained from the IHSS, perimeter, and pathway areas as shown in Figure 3-2. Final radiological surveys at each of the 30 initial smear sample locations shown in Figure 3-1 completed the Stage I and II field investigation of IHSS 178.

#### 3.1.2 IHSS 179 - Building 865 Drum Storage Area

Following the review of new data and information, and after the visual inspection of IHSS 179, 23 radiological and beryllium smear samples were collected at the locations shown in Figure 3-3. Three hot water rinsate samples were then obtained from the IHSS, perimeter, and pathway areas as shown in Figure 3-4. Final radiological surveys at each of the 23 initial smear sample locations shown in Figure 3-3 completed the Stage I and II field investigation of IHSS 179.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	3 of 10

# 3.1.3 IHSS 180 - Building 883 Drum Storage Area

Following the review of new data and information, and after the visual inspection of IHSS 180, 49 radiological and beryllium smear samples were collected at the locations shown in Figure 3-5. Four hot water rinsate samples were then obtained from the IHSS, perimeter, and pathway areas as shown in Figure 3-6. The weigh scale located adjacent to the IHSS was not disassembled to perform either hot water rinsate or radiological sampling beneath the scale plate. Final radiological surveys at each of the 49 initial smear sample locations shown in Figure 3-5 completed the Stage I and II field investigation of IHSS 180.

# 3.1.4 IHSS 204 - Unit 45, Original Uranium Chip Roaster

Following the review of new data and information, and after the visual inspection of IHSS 204, radiological smear samples were collected from the areas that compose IHSS 204. Thirty-three smear samples were collected from the floor in Rooms 31 and 32, and one sample was collected from the exterior surface of the oxide outlet of the Original Uranium Chip Roaster. Figure 3-7 shows the locations for these samples Thirty-one smear samples were collected from the floor in Rooms 501 and 502, and two samples were collected from the exterior surface of the chip inlet of the Original Uranium Chip Roaster. Figure 3-8 shows these sample locations. Ten smear samples were also collected from the Wash Rack/Drum Washing Basin in Room 501 as shown in Figure 3-9.

Seven hot water rinsate samples were obtained from the areas that compose IHSS 204

One rinsate sample was collected from the floor of Room 31, Room 32, Room 501, and

Room 502 One sample was also collected from the exterior surface of the oxide outlet
and from the exterior surface of the chip inlet of the Original Uranium Chip Roaster

One rinsate sample was collected from the floor in Room 501, and one rinsate sample

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	4 of 10

was also collected from the Wash Rack/Drum Washing Basin in Room 501 One sample was collected from the floor in Room 502 Sampling locations are shown in Figures 3-10, 3-11, and 3-12 In accordance with the requirements of the Work Plan, no final radiological surveys were performed for IHSS 204

#### 3.1.5 IHSS 211 - Unit 26, Building 881 Drum Storage Area

Following the review of new data and information, and after the visual inspection of IHSS 211, 32 radiological smear samples were collected at the locations shown in Figure 3-13. Three hot water rinsate samples were then obtained from the IHSS, perimeter, and pathway areas as shown in Figure 3-14. Final radiological surveys at each of the 32 initial smear sample locations shown in Figure 3-13 completed the Stage I and II field investigation of IHSS 211.

## 3.1.6 IHSS 217 - Unit 32, Cyanide Bench Scale Treatment

Following the review of new data and information, and after the visual inspection of IHSS 217, five radiological smear samples were collected from the floor adjacent to the laboratory table (perimeter) and eight samples were collected from the laboratory table and fume hood (IHSS) at the locations shown in Figures 3-15 and 3-16, respectively One hot water rinsate sample was then obtained from each of these areas as shown in Figures 3-17 and 3-18. Final radiological surveys at each of the 13 initial smear sample locations shown in Figures 3-15 and 3-16 completed the Stage I and II field investigation of IHSS 217.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	5 of 10

#### 3.2 Sample Collection and Field Analysis Procedures

This section describes the procedures used to collect radiological and beryllium smear samples, and hot water rinsate samples, and to perform the final radiological surveys during the Stage I and II field investigations

# 3.2.1 Smear Sample Collection

All smear samples were obtained according to procedures outlined in Radiological Operating Instruction (ROI) 3.1. This procedure is equivalent to Environmental Management Radiological Guidelines (EMRG) Section 3.1 (Performance of Surface Contamination Surveys). Each IHSS, along with its associated perimeter and pathway areas, was divided into sampling areas measuring one square meter each. To collect the samples, smear paper was rubbed over an area of approximately 100 square centimeters within each square meter.

The smear samples were analyzed with an Eberline SAC-4 Alpha-Scintillation Smear Counting Instrument for alpha counting and an Eberline BC-4 Beta Smear Counting Instrument for beta counting. All smear samples from IHSS 179 and IHSS 180 were also analyzed for beryllium using the on-site beryllium counter (the Beryllium Activated Swipe Test). Radiological results were recorded on data sheets by EG&G Radiation Protection Technologists (RPTs), beryllium results were recorded by EG&G Industrial Hygiene technicians.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	6 of 10

### 3.2.2 Hot Water Rinsate Sample Collection

Hot water rinsate samples were collected in accordance with EG&G SOP (Standard Operating Procedure) FO 27 (Collection of Floor/Equipment Hot Water Rinsate Samples) The hot water rinsate sample collection system designed for use during the OU15 field investigation consisted of a series of modular components divided into two major groups. The first group included a spray applicator and vacuum head, an interceptor can/receiver, and associated connecting hoses and fittings. To prevent cross-contamination between IHSSs, a set of this equipment was dedicated to each of the IHSSs sampled. The second equipment group consisted of a hot water reservoir and heater, a High Efficiency Particulate Air vacuum unit, an activated carbon adsorption unit, and associated connecting hoses and fittings. This equipment was reused for all of the IHSSs sampled, because the equipment was remotely positioned outside of the IHSS and potentially contaminated areas. A schematic of the hot water rinsate sample collection system is shown in Figure 3-19

The hot water spray was applied to and vacuumed from the sample areas in a manner which allowed the entire sample area to be uniformly covered. Hot water was applied at the rate necessary to generate enough sample volume to perform the required sample analyses. In all cases, however, the application rate was kept below 0.17 gallons per square foot to avoid an unrepresentative dilution of the sample.

The hot water rinsate samples were collected from the rinsate sample bag located in the interceptor can/receiver. Sample collection procedures were followed as specified in EG&G SOP FO 27. The approximate volume of sample was determined by weighing the sample bag and its contents, and field parameters including pH, temperature, and conductivity (specific conductance) were measured in accordance with EG&G SOP SW 2. (Field Measurement of Surface Water). Any unusual observations about the liquid, including color or odor were recorded in the field book. All chain of custody forms and

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	7 of 10

field documentation were completed in accordance with the requirements of EG&G SOP FO 13 (Containerizing, Preserving, Handling, and Shipping Soil and Water Samples) and the Work Plan

#### 3.2.3 Final Radiological Surveys

A second set of removable alpha, beta, and, if applicable, beryllium analyses, fixed alpha and beta radiological surveys, and beta and gamma dose rate surveys were performed for each of the one square meter areas sampled during the initial smear sample collection, with the exception of those associated with IHSS 204. The final radiological surveys were conducted and recorded as specified in ROIs 1.1, 1.2 and 3.1. These procedures are the equivalent of EMRG Section 1.1 (Gamma Radiation Surveys), Section 1.2 (Beta Radiation Surveys), and Section 3.1 (Performance of Surface Contamination Surveys), respectively

The second set of smear samples were collected and analyzed using the procedure outlined in Section 3 2 1. A Ludlum Model 12-1A count-rate instrument (or equivalent) was used for measuring direct alpha activity and a Ludlum Model 31 (or equivalent) was used for direct measurement of beta activity. Beta and gamma dose-rate surveys were performed using a Victoreen 450B instrument

#### 3.3 Chemical and Radionuclide Laboratory Analysis Methods

Hot water rinsate samples were analyzed for some or all of the following parameters

- TAL dissolved metals
- TCL VOCs
- TCL semi-volatile organic compounds
- dissolved radionuclides
- cyanide

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	8 of 10

The specific analytes and detection/quantification limits for the OU15 Phase I RFI/RI are identified in the Work Plan by reference to EPA Contract Laboratory Program (CLP) analyses and the General Radiochemistry and Routine Analytical Services Protocol (GRRASP) (EG&G, 1991) Part A of the GRRASP provides hazardous substance list analytes and limits using CLP methods Part B of the GRRASP provides analytes and detection limits for radionuclides

# 3.4 Data Quality Assurance/Quality Control

Four types of QA/QC samples were collected for the hot water rinsate sampling in accordance with the requirements of Section 6.3 of EG&G SOP FO 27. The hot water source or field blanks (taken from the field water source prior to being used for rinsate generation), sample duplicates, equipment rinsate blanks, and trip blanks were analyzed for the same constituents as their associated real samples. A summary of all individual hot water rinsate and QA/QC samples collected is provided in Table 3-2 and is sorted by IHSS. In Building 881, the same hot water source was used for sampling IHSSs 178, 211 and 217, therefore, only one hot water source sample was collected. Since IHSSs 179, 180 and 204 each had a different hot water source, one sample was collected from each source.

The equipment rinsate blanks collected in the field measured the effectiveness of sampling equipment decontamination, but did not measure the impact of the entire hot water rinsate sampling system in an operating mode. Therefore, three equipment blank samples, or hot water rinsate blanks, were collected from the hot water rinsate sampling system on April 27, 1994 at an off-site location. These samples were collected by using the entire sampling system to rinse a clean glass surface. Distilled water was used as the source water. These samples were analyzed to determine the influence of the sampling equipment on the hot water rinsate samples collected during the Stage I and II field investigations. A trip blank sample accompanied the three equipment blank samples

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	9 of 10

#### 3.5 Data Processing and Storage

Hot water rinsate samples collected from floor areas and designated equipment were assigned sequential numbers based on the order in which they were collected. Each sample and associated location was marked on the corresponding IHSS diagram, measured relative to IHSS structures, and described in the designated field book.

In order to maintain consistency with the Rocky Flats Environmental Database System (RFEDS) sample numbering system, a block of sample numbers was assigned by EG&G Environmental Restoration Sample Management for the OU15 Phase I RFI/RI hot water rinsate samples. The RFEDS sample numbers consist of a two digit sample prefix indicating sample type, a five digit serial number identifying the sample, and a suffix identifying the contractor collecting the sample. For example, the sample number BU00011ER indicates a building sample (BU), serial number eleven (00011), collected by ERM-Rocky Mountain, Inc. (ER)

Location codes have also been established in the RFEDS for each sample. Each location code consists of seven digits and describes where its associated sample was collected. The first three digits in each location code identify the building in which the IHSS is located, the second three digits represent the particular IHSS, and the last digit indicates the sample area (e.g., the IHSS [1], perimeter, [2] or pathway [3]). For example, the location code 8811782, identifies that the sample was collected from the perimeter area of IHSS 178 in Building 881. For IHSS 204, a different set of numbers was used to designate the sample area (the last digit in the location code), due to the greater number and variety of hot water rinsate sampling locations. Sample area identifiers for IHSS 204 were defined as follows. The Wash Rack/Drum Washing Basin (1), the floor in Room 501 (2), the floor in Room 502 (3), the chip inlet (4), the floor in Room 31 (5), the floor in Room 32 (6), and the oxide outlet (7)

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	3 0, Final
Inside Building Closures	Page	10 of 10

Data collected during the initial radiological and beryllium smear sampling, and the final radiological surveys were recorded directly on data sheets by EG&G RPTs and Industrial Hygiene technicians. Sample/survey locations were determined based on the layout of one square meter grids. For each IHSS, the position of the sampling/survey squares was plotted on the IHSS diagram and numbered sequentially. Sample/survey results were then identified and tracked by this numbering scheme. These radiological data were not compatible with the RFEDS structure, so they are instead maintained in hard copy form in the project files. Data generated from both the radiological sampling and surveys and the hot water rinsate sampling are managed in accordance with the prescribed QA/QC procedures described in EG&G SOP FO 14 (Field Data Management)

Table 3-1 OU15 Field Investigation Activities

			Smear Sampling	ampling	Hot	Hot Water Rinsate Sampling/Analysis	ısate Samı	oling/Ana	lysis	Fina	l Radiolo	Final Radiological Surveys	veys
										Smear Samples	amples		
IHSS	Data Review	Visual Inspection	Rads	Be	VOCs	Semi- VOCs	Rads	Metals	Cyanıde	Rads	Be	Fixed	Lose- Rate
178	X	×	×		X	X	×			×		×	×
179	X	X	X	X	X	X	X			X	X	X	×
180	X	X	X	X	Х	X	X			X	X	X	X
204	X	X	X		X	×	X						
211	X	X	X		X	X	X	X		X		X	X
217	X	X	X		X	X	X	X	X	X		X	×

Table 3-2 Summary of Hot Water Rinsate Real & QA/QC Samples


Trip Blank Equipment Rinse	BU00010ER BU00013ER			BU00031ER BU00035ER		-	BU00021ER BU00025ER	-	BU00029ER	-
Sample Duplicate T	BU00012ER BU		1	BU00034ER BI			BU00024ER BI	1	BU00028ER	1
Field Blank	BU00001ER (From tap 111 Room 261)			BU00032ER (From tap in Room 145)		-	BU00022ER (From tap in Room 104)	-	-	
Hot Water Rinsate Sample	BU00011ER (IHSS)	BU00014ER (Perimeter)	BU00015ER (Pathway)	BU00033ER (Perimeter)	BU00036FR (IHSS)	BU00037ER (Pathway)	BU00023ER (IHSS)	BU00026ER (Perimeter)	BU00027ER (Pathway)	BU00030ER
Date Sampled	08/16/93			09/12/93			09/01/93		09/05/93	
SSHI	178			179			180			


Table 3-2 Summary of Hot Water Rinsate Real & QA/QC Samples


		Hot Water				
IHSS	Date Sampled	Rinsate Sample	Field Blank	Sample Duplicate	Trip Blank	Equipment Rinse
204	10/11/93	BU00040ER (Wash Rack)	BU00039ER (From tap in Room 501)	BU00041ER	BU00038ER	BU00042ER
		BU00043ER (Rm 501 Perimeter)	-			1
		BU00044ER (Rm 502 IHSS)	1	-	-	
		BU00045ER (Chip Inlet)	-	-		
	11/09/93	BU00047ER (Rm 31 Perimeter)	-	BU00048ER	BU00046ER	BU00049ER
		BU00050ER (Rm 32 IHSS)	-			-
		BU00051ER (Oxide Outlet)	-	1	1	1


Table 3-2 Summary of Hot Water Rinsate Real & QA/QC Samples


Equipment Rinse	BU00004ER	BU00007ER	l	BU00019ER	-
Trıp Blank	BU00005ER			BU00016ER	1
Sample Duplicate	BU00003ER	-	BU00009ER	BU00018ER	1
Field Blank	BU00001ER (From tap in Room 261)	-	1	BU00001ER (From tap in Room 261)	-
Hot Water Rınsate Sample	BU00002ER (IHSS)	BU00006ER (Perimeter)	BU00008ER (Pathway)	BU00017ER (IHSS)	BU00020ER (Perimeter)
Date Sampled	08/09/93	08/11/93		08/17/93	
SSHI	211			217	


















NOTES ① TWO SMEAR SAMPLES WERE COLLECTED FROM THE SURFACE OF THE CHIP ROASTER INLET ROOM 501 **ELEVATOR** 1 NO 3 2 3 4 6 OBSTRUCTED SPACE -RØOM OBSTRUCTED SPACE CHIP ROASTER INLETO **ROOM 503** CHIP ROASTER INLET KEYWORDS ORIGINAL ISSUE XX/XX/93 RCH SRL DAW DLS
DATE REP 1.0015 DESCRIPTION 2 PHASE I DOE CLASS JOB NO U.S. DEPARTMENT OF ENERGY ROCKY FLATS AREA OFFICE GOLDEN COLORADO 3 RFI/RI DESIGNED HEA XX/XX/93 + TECH MEMO LENNIE XX/XX/93 Rocky Flats Plant S NUMBER 1 CHECKED WEAVER XX/XX/93 BLDG./FACILITY 447 ROOM/AREA 501/502 PROVED SCHUBBE XX/XX/93 GOLDEN COLORADO 80401 OUTS PHASE I RET/RI
IHSS 204 RAD
SAMPLE LOCATIONS
DRAWING NEUMER [ISSUE] FROM MASTER SCALE, APPROVED


YES | NO NO NE APPROVED


DOC BIERBAUM XX/XX/93 SIZE IHSS 204 В Α 3-8




WASH RACK/DRUM WASHING BASIN

VC:MIDEOD	T. 1					L	4-	T					т—		٤.
KEYWORDS	^_	ORIGIN	IAL ISSU	Æ		XX/XX	/93 RCI	SPE	DAW	OLS			1		-
1 0015	SSUC		DESC	RIPTION		DAT	E	R	FP		DOE	aus	S J08	NO	)=
2 PHASE 1	V					1	U S	S. DE	PAR	MEN'	T OF E	NERG	Y		'n
3 RFI/RI	1\	/	DESIGNED	HEA	XX/XX/93	, R	OCKY FLA	TS AF	EA O	FFICE	90	LDEN C	OLORADO	)	Ε.
TECH MEMO	1 \	/	DRAWN	SCHACKLIN	12/20/93	]	Ro	ok:	y 1	Fla	ts I	Plan	nt		'n
NUMBER 1	1 '	\ /	CHECKED	WEAVER	XX/XX/93	1									ć
BLDG /FACILITY	1	Χ	APPROVED	SCHUBBE	XX/XX/93	1		G	COLDEN	COL	PADO I	80401			Ľ
447	}	/\	}					001	5 Pi	HASE	i RFI	/Ri			Ē,
ROOM/AREA 501	7					1 -		153	5	20	4 1	RAI	)		
ORD COOR./COL NO.	1/	\	ļ			1 :	SAM	PL	E.	L	DCA	<b>TIC</b>	NS	,	E
	V	\	SUBMITTED	BIERBAUM	XX/XX/93	SIZE	O#	AWN	NUM	BER	1	SSUE	PICK	RE	አ
MASTER		CALE	APPROVED REP			D	11.10	~~		20		<u> </u>	7	$\sim$	3
YES   NO 🔯	1	ONE	APPROVED DOE				IH:	22		.U4	١ ١	A	J-	-9	E










WASH RACK/DRUM WASHING BASIN


KEYWORDS	A	ORIGIN	IAL ISSU	JE		xx/x	X/93	RCH	SRL	DAW	DLS				
1 0015	SSUE		DESC	CRIPTION		DA	TE	_	RI	·P		DOE	av	is J	08 NO
2 PHASE !	$\overline{}$							us	DEI	PART	MEN	T OF I	ENERC	Y	
3 RFI/RI	1	/	DESIGNED	HEA	XX/XX/93	L	ROCKY	FLAT	S AR	EA OF	TICE	G	NJOEN (	COLOR	400
TECH MEMO	١ \	/	DRAWN	SCHACKLIN	12/20/93		F	200	· kes	, F	מויי	ts :	Pla	nt.	
NUMBER 1	'	\ /	CHECKED	WEAVER	XX/XX/93	1	-		,	•					
BLDG /FACILITY		Υ	APPROVED	SCHUBBE	XX/XX/93	1			GC	LDEN	COLC	PADO	80401		
447	1	Λ	1			1			OU 1	5 PI	IASE	1 RF	I/RI		
ROOM/AREA	1 /	/ \	1			┪ —	TH	<u> </u>		20	4	RII	(IC	ΔΤΙ	
501	/	\				4									
GRID COOR /COL NO.	1/	\				ــــــــــــــــــــــــــــــــــــــ	<u> </u>	<u>MI</u>	<u> </u>	<u>t.                                    </u>	<u> </u>	<u> DCA</u>	<u> </u>	<u> עוכ</u>	<u> </u>
	V	'	SUBMITTED	BIERBAUM	XX/XX/93	SIZE		ORA	WNG	NUM	BER	l l	SSUE	,	TOURE
MASTER	5	CALE	APPROVED				11		·	~	0		٨	7	10
YES   NO	7	SNE	APPROVED DOE			101	l II	ロン	5	4	04	<b> </b>	Α	J-	- 12










KEYWORDS	TA	OBICIN	AL ISSUI	-		xx/x	v /0 T	201					_	T	_
1 0015	SSUC	OKIGII		RIPTION		<del></del>	A/ 33	ACA	Щ.	FP	u.s	DOE	-	54 JOB NO	_
2 PHASE I	1			1			.,_	11.5		-	DAEN	T OF	_	1	<u>'</u>
RFI/RI	1	/	DESIGNED	HEA	XX/XX/93	1	ROCKY							COLORADO	
TECH MEMO	1 \		DRAWN	LENNIE	12/20/93		F	205	·ks	, 1	-la	ts :	Pla	n t	_
NUMBER 1	1 '	\ /	CHECKED	BIERBAUM	XX/XX/93	1	-		,	_					
LOG./FACILITY	1	Χ	APPROVED	SCHUBBE	XX/XX/93	1			CC	LDEN	COL	PADO	80401		
881	1	/\										1 RF			_
131C	l /		1			1		ΙH	SS	5	21	7 1	RAI	)	
THE COOR /COL NO.	1/	/				1	SA	M	آد	E	L(	CA	TIC	ŌNS	
	V		SUB-LETTED	BIERBAUM	XX/XX/93	SIZE				NUI			SSUE	PIQURE	_
MASTER			APPROVED RFP				FI		$\overline{}$	2	1-	, 1	$\overline{\Lambda}$	7 1/	_
YES 🗌 NO 🔯	120	ONE	APPROVED DOE			101	- 11	$\Box$	5		17	'	A	J-1:	Э





															[1
															480
															2 E
KEYWORDS	Α	ORIGI	AL ISSU	E		XX/X	X/93	RCH	SRL	PRB	DLS		Т	T	
0015	SSUE		DESC	RIPTION		0/	TE		R	FP		DOE	CLAS	3 JOB	NO.
- PHASE I	1		1			Г		US	DE	PAR'	MEN	T OF I	ENER	3Y	
RFI/RI	1\	/	DESIGNED	HEA	XX/XX/93	<u></u>	ROCKY	FLA	TS AF	REA O	FFICE	0	OLDEN	COLORAD	<u> </u>
TECH MEMO	1 \	. /	DRAWN	LENNIE	12/20/93	]	F	200	e k	, F	rla	ts F	-la:	nt	na C
NUMBER 1	1	\ /	CHECKED	BIERBAUM	XX/XX/93	1				_		_			c E
LOG./FAOUTY	1	γ	APPROVED	SCHUBBE	XX/XX/93	1			G	NACLE	COL	DRADO 8	10401		U
881	1	$/\setminus$	.						0U1	5 Ph	IASE	I RFI	/RI		
OOM/AREA	1 /	/ \				1 -	TH:	$\overline{\varsigma}$	$\overline{\cdot}$	$\overline{21}$	7	RIN	154	<b>NTF</b>	- 1
131C	1/	\	į.	<u> </u>	· · · · · · · · · · · · · · · · · · ·	1	SÄ		_	╆'	í	ハンド	776	1115	_
RED COOR./COL NO.	//		\ <del></del>	BIERBAUM	VV (VV (A1	l	<u> </u>	_		NUI	<u>`</u>		111	7142	<u> </u>
	v	CALE.	APPROVED		XX/XX/93	SIZE			-				SSU€	PiQU	- h
MACTED								10	$\sim$	$\sim$	4 -	7 1	۸ ۱	7	4 77 E.
MASTER	1 1	ONE	REP			łΒi	. 11	٦,	'	2	1 .	/ 1	АΙ	. )	/ 👺





# Section 40

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	1 of 16

#### 4.0 DATA QUALITY EVALUATION

The Phase I RFI/RI was conducted in accordance with the approved Work Plan, the site-wide Quality Assurance Project Plan (QAPjP), and SOPs as amended by the Work Plan This section addresses the quality and useability of the data collected during the OU15 Phase I RFI/RI to determine if the site-specific objectives were achieved Data Quality Objectives (DQOs) were established in the Work Plan to qualitatively and quantitatively evaluate the useability of the data in terms of precision, accuracy, representativeness, completeness, and comparability (PARCC) parameters Definitions of the codes used in the Section 4 0, 5 0, and 6 0 data tables are included in the Table of Contents

## 4.1 Phase I RFI/RI Data Quality Objectives

The site-specific objectives of the OU15 Phase I RFI/RI were established according to the requirements of the IAG and the OU15 Work Plan. The site-specific data quality objectives are described in Section 4.0 of the Work Plan. The objectives were achieved by reviewing new and historical information, visually inspecting and documenting current IHSS conditions, and sampling and analyzing surfaces within each IHSS area. Table 3-1 in Section 3.0 summarizes field investigation activities completed for the OU15 Phase I RFI/RI. Achievement of each site-specific DQO is discussed in the following sections.

#### 4.1.1 Characterize Site Physical Features

Each IHSS was visually inspected to evaluate site physical features and collect pertinent information regarding the nature, extent, and migration potential of contamination. The inspection characterized general building construction, IHSS design, and current condition, and examined floor thickness, slope, drains, coatings (seals/paints), condition, and secondary containment

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	2 of 16

#### 4.1.2 Define Contaminant Sources

Contaminant sources were defined by identifying and characterizing wastes that were historically stored or processed in each IHSS and by determining the presence or absence of contamination within each IHSS. Contaminant source information was collected via a detailed records review. In addition, samples were collected inside IHSS boundaries and analyzed for radionuclides, beryllium, TCL volatile organics, TCL semi-volatile organics, and TAL metals.

#### 4.1.3 Determine Nature and Extent of Contamination

The nature and extent of contamination was determined by evaluating the spatial distribution of IHSS-related contaminants. Spatial distribution was determined by establishing a sampling grid and collecting and analyzing three types of samples including

- surficial smear samples for radionuclide and beryllium analysis,
- hot water rinsate samples for TCL volatile organics, TCL semi-volatile organics, and TAL metals analysis, and
- radiation surveys for fixed radionuclide constituents

In addition, samples were collected from within each IHSS, and from areas around the perimeter and along pathways leading from each IHSS to provide sufficient coverage of the extent of contamination

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	3 of 16

#### 4.1.4 Describe Contaminant Fate and Transport

Contaminant fate and transport was evaluated by assessing the current condition of secondary containment at each IHSS and assessing the potential contamination migration pathways from each IHSS to the environment outside of the IHSS. Information obtained from site inspections, records review, sampling, and analysis were applied in determining the potential for a release, direct release mechanisms, and chemical/radiological gradients from each IHSS.

#### 4.1.5 Support a Baseline Risk Assessment

The satisfaction of each of the DQOs will provide support for a BRA, if required Section 300 430(d) of the National Contingency Plan states that as part of the remedial investigation, a BRA is to be conducted to determine whether contaminants of concern identified at the site pose a current or potential future risk to human health and the environment in the absence of remedial action. However, the OU15 IHSSs are RCRA closure units and must therefore meet the RCRA clean closure performance standards. The clean closure performance standards were defined by reviewing the State RCRA Permit. The data were evaluated to determine if the standard was achieved at each IHSS Based on guidance provided in the "Risk Assessment Guidance for Superfund, Volume I, Human Health Evaluation Manual, Part A" (EPA, 1989) (RAGS Part A), the following criteria indicate the data suitability for a BRA.

- Standard EPA and GRRASP methods were used ensuring an adequate level of data quality assurance
- Detection limits acheived using EPA and GRRASP methods are sufficiently low to support calculations at low risk levels. Few samples were diluted due to interference, and the dilution factors necessary were low (generally 2 0)
- The number of samples, locations, and analytes were sufficient to characterize the nature and extent of contamination

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	4 of 16

- Specific compounds and radionuclides were identified, as opposed to groups of compounds such as Total Petroleum Hydrocarbons, thus allowing for specific compound toxicities to be used
- The data underwent QA/QC scrutiny during the RFEDS process, as well as an evaluation for PARCC parameters provided below

Based on these factors, the data are of sufficient quality to support a BRA, if necessary In addition, the radiological data are of sufficient quality to support a radionuclide-specific dose assessment, if necessary

## 4.2 Data Useability

The analytical program requirements are based on the DQOs and resulting FSP as defined in the Work Plan, Sections 4 0 and 7 0. To ensure data quality, a quality control program was developed and is described in the Quality Assurance Addendum (QAA) in Section 10 0 of the Work Plan. As part of the quality control program for OU15, field QC samples were collected. The quality of data collected is measured in terms of PARCC parameters. In addition, hot water rinsate blank samples, trip blank samples, and field blank (source water) samples were collected and analyzed to characterize other potential contaminant sources.

### 4.2 1 Quality Control

Four types of QA/QC samples were collected for the hot water rinsate sampling in accordance with the requirements of Section 6 3 of EG&G SOP FO 27 A summary of all individual hot water rinsate and QA/QC samples collected is provided in Table 3-2 (sorted by IHSS). The hot water source or field blanks (taken from the field water source prior to being used for rinsate generation), sample duplicates, equipment rinsate blanks, and trip blanks were analyzed for the same constituents as their associated real samples. In Building 881, the same hot water source was used for sampling IHSSs 178,

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	5 of 16

211 and 217, therefore, only one hot water source sample was collected Since IHSSs 179, 180 and 204 each had a different hot water source, one sample was collected from each source Comparison of the proposed hot water rinsate field QC sampling frequency to the actual hot water rinsate field sampling frequency is presented in Table 4-1

Duplicate samples were collected by the sampling team and were used as a relative measure of the precision of the sample collection process. These samples were collected at the same time, using the same procedures, the same equipment, and the same types of containers as required for the real samples. They were also preserved in the same manner and submitted for the same analyses as required for the real samples.

Equipment rinsate blanks were collected from final decontamination rinsate to evaluate the success of the field sampling team's decontamination efforts on non-dedicated sampling equipment. Equipment rinsate blanks were obtained by rinsing cleaned equipment with distilled water prior to sample collection. The rinsate was collected and placed in the appropriate sample containers

Trip blanks consisting of distilled water were prepared by a laboratory technician and accompanied each shipment of water samples for VOC analysis. Trip blanks were stored with the group of samples with which they were associated. Analysis of the trip blanks were used in conjunction with air monitoring data from field activities and other information to assess the influence of ongoing waste operations on the quality of data collected.

Hot water rinsate blanks were collected by reproducing the hot water rinsate sampling procedure using distilled water to rinse a clean glass plate. The results from these samples were used to identify any contaminants which were attributable to the sampling equipment

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	6 of 16

#### 4.2.2 PARCC

Precision, accuracy, and completeness are quantitative measures of data quality, while representativeness and comparability are qualitative statements that express the degree to which sample data represent actual conditions and describe the confidence of one data set as compared to another The PARCC parameters are defined in Appendix A of the QAP<sub>1</sub>P

The analytical data generated using EPA and other well-established methods as identified in the GRRASP and QAP<sub>J</sub>P, are presented in Sections 5 0 and 6 0. The analytical data were reviewed and validated independently of the laboratory and the sample collection contractor, and the results were documented in data validation reports. Standard method-specific data validation procedures developed by EG&G and based on the EPA CLP data validation functional guidelines were used to validate the data.

The three classes of data quality used by EG&G are

- V Valid and usable without qualifications,
- A Acceptable for use with qualifications, and
- R Rejected

Other validation codes, as presented in Table 4-2, fall within these three basic categories A list of laboratory qualifiers is also included in Table 4-2. For the purposes of TM#1, valid and acceptable data were considered of equal utility. As of March 24, 1994, 43% of all Phase I data have been processed for data validation. Of the processed data less than 1% has been rejected.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	7 of 16

#### **Precision**

Precision is a measure of mutual agreement among individual measurements of the same property, under identical conditions. Precision is assessed by calculating the relative percent difference (RPD), which is the quotient of the difference between the field (real) and duplicate analytical result and the average of those results for the given analytes expressed as a percentage

$$RPD = \frac{(V_1 - V_2)}{\frac{1}{2}(V_1 + V_2)} *100\%$$

Where

RPD = Relative Percent Difference

 $V_1$ ,  $V_2$  = the values of the duplicate samples

#### Field Precision

Field duplicates from the hot water rinsate are collected following the field sample collection using the same sampling technique used for the original or "real" samples Comparison of the data results from the real and duplicate samples provides a measure of the sample homogeneity and sampling technique precision with respect to the amount of error attributed to sampling technique and variability in the analyte concentration in the medium being sampled. The field precision objective specified in the QAA is to obtain a RPD of  $\leq 30\%$  for water samples. For metals at concentrations near the quantitation limits, precision is expressed as acceptable if the difference between the real and duplicate results is numerically less than the Contract Required Quantitation Limit (CRQL) or if the RPD criterion is met

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	40, Final
Inside Building Closures	Page	8 of 16

In conjunction with the precision objectives outlined in the QAA, the number of duplicate samples required to demonstrate precision was one duplicate pair for every 10 samples collected or 10% of the field samples. Table 4-1 lists the achieved field QC sample frequency for the samples collected. A list of duplicates and associated field samples (QC partners) is presented by sample number and analyte in Table 4-3. Calculated RPDs are also presented in Table 4-3.

Based on the available analytical results, RPDs were calculated for a total of 225 field duplicate pairs and 34 laboratory replicate pairs. Overall, a total of 72% of the field duplicates and laboratory replicates analyzed met the field precision goals.

Some of the duplicate sample pairs analyzed for radionuclides reported concentrations near the minimum detectable activity (MDA) or were given negative values Reproduceability under these circumstances is difficult because of the analytical limitations and may not reflect poor field precision. Therefore, if the CRQL criterion is applied as described for metals, 67% of the radionuclide duplicates achieved the field precision goals.

Cyanide, semi-volatile organic, and VOC field duplicate and replicate pairs met the field precision goals in 65% of the samples compared

Metal field duplicate and replicate pairs met the field precision goals in approximately 89% of the samples compared

Based on the stringent goal of  $\leq 30\%$  RPDs, the degree to which the field duplicate and laboratory replicate data met the goal is sufficient to meet the overall precision objective for the project. To overcome any possible bias introduced by analytical error, both real and duplicate results were evaluated separately (rather than averaging the two) such that the maximum possible concentration in each sample was screened

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	9 of 16

#### Laboratory Precision

Laboratory precision is evaluated through the use of laboratory duplicates for inorganic analyses and matrix spikes (MS) and matrix spike duplicates (MSD) for the organic analyses. Duplicate precision is calculated as RPD, MS/MSD precision is assessed by calculating a RPD between the percent recoveries observed for the method-specific spiked compounds. Laboratory precision goals are mandated by the analytical method for each group and assessed for achievement during data validation. Data not meeting the precision goals set forth by the method are normally rejected during the RFEDS data validation process.

#### Accuracy

The accuracy of the data obtained in an investigation is a function of the sampling technique, potential for sample contamination during collection and the analytical capabilities of the laboratory. Accuracy means the nearness of a result, or the mean of a set of results, to the true value. Accuracy is assessed by analysis of reference samples of known concentrations, percent recoveries for spiked samples, and by review of blank data (field equipment, trip, or method blanks) which may have an effect on measurement accuracy

### Field Accuracy

Field Accuracy is assessed by comparing sample analyte concentrations to those present in associated field blanks. Four types of samples were collected to evaluate field accuracy

• equipment rinsate blanks, which quantify the efficacy of the equipment decontamination procedures and identify any contaminants associated with sample cross-contamination.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	10 of 16

- trip blanks, which identify cross-contamination of samples from sources at RFP other than the OU15 IHSSs,
- field blanks (source water), which identify contaminants already present in hot water rinsate source water prior to sample collection, and
- hot water rinsate blanks, which identify any contaminants leaching out of the sampling equipment, and which are therefore artifacts of the sampling method

The results for each of these sample types are given below

#### Field Accuracy - Equipment Rinsate Blanks

The equipment rinsate blanks are used to monitor for sample cross-contamination and the effectiveness of the decontamination process. The blanks are collected by rinsing decontaminated sampling equipment with distilled water, placing the liquid in the appropriate sample container and preserving as is required. Table 4-1 presents the proposed and actual frequencies for equipment rinsate sampling relative to the actual number of field samples collected. The field QC sample frequency goal is one in 20 or 5%. One rinsate sample was collected each day for a total of 9 samples, representing an actual frequency of 40%.

Table 4-4 indicates that VOCs, total xylenes, and methylene chloride were detected in the rinsate blanks. As noted in the CLP statement of work for organic analyses, these compounds are common laboratory solvents and are often inadvertently introduced into samples from the laboratory atmosphere. In accordance with the CLP protocol, the data validators assess whether the occurrence of these compounds is due to laboratory contamination by comparing the sample results to the laboratory blanks. Total xylenes were detected in only two samples, BU00013ER and BU00019ER. The reported detections were estimated and below the CRQL (data flagged with a J). Methylene

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	40, Final
Inside Building Closures	Page	11 of 16

chloride was detected in only two samples, BU00025ER and BU00004ER The reported detections were either estimated and below the CRQL or at the CRQL

Table 4-4 also shows the semi-volatile organic compounds detected in the equipment rinsate blanks. Of these samples, bis(2-ethylhexyl)phthalate (DEHP) and hexadecanamide were the only identified semi-volatile organic compounds detected DEHP was detected in four samples, BU00029ER, BU00035ER, BU00042ER, and BU00049ER. Two of the reported concentrations were estimated and below the CRQL and the remaining two were within the same order of magnitude as the CRQL Phthalates are a common laboratory contaminant. Hexadecanamide was reported at an estimated concentration below the CRQL in only one sample (BU00049ER).

Metals were identified in three of the rinsate blanks (BU00004ER, BU00007ER, and BU00019ER) The metals detected in the rinsate blanks were silicon, calcium, sodium, zinc, cesium, strontium, cadmium, copper, and lead Of these, cadmium was the only metal detected at a concentration above the CRQL. The reported cadmium concentration was estimated and acceptable (flagged with a JA)

As presented in Table 4-4, rinsate samples contained Americium-241, Plutonium-239/240, Uranium-233-234, Uranium-235, Uranium-238, Gross  $\alpha$ , and Gross  $\beta$  above the CRQL Based on the reported error range of the analytical technique, however, many of these values could fall below the CRQL at the lower end of the estimated range

Overall, the low concentrations of constituents in the equipment rinsate blanks, as compared to the magnitude of concentrations detected in real samples, indicated that the equipment decontamination procedures were adequate and that significant cross-contamination of samples did not occur

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	12 of 16

#### Field Accuracy - Trip Blanks

Table 4-5 shows the analytical results for the trip blank samples. A total of 8 trip blanks were collected and analyzed. Seven of the samples were analyzed only for VOCs. The eighth sample was analyzed for VOCs, semi-volatile organic compounds, TAL dissolved metals, and cyanide. Table 4-5 indicates that methylene chloride was positively identified in three trip blanks taken from IHSSs 180, 204, and 211. Two of the methylene chloride detections were above the CRQL. Methylene chloride is a common laboratory cross-contaminant, and is easily incorporated into a sample erroneously via deposition from air, since methylene chloride is both highly volatile and highly soluble. The maximum concentration of methylene chloride detected in the trip blanks was  $14 \mu g/l$ 

Several metals were also detected at low concentrations in sample BU00052ER. This sample was the trip blank taken during the hot water rinsate blank sample collection. The metals detected above the CRQL were cadmium at 17 6  $\mu$ g/l, and lead at 4 6  $\mu$ g/l

Overall, the trip blank results indicated that cross-contamination did not occur from non-related sources during sampling events. The only significant exception was methylene chloride, which was either introduced from airborne sources during sampling, or from laboratory cross-contamination during analysis of the trip blanks.

# Field Accuracy - Field Blanks (Source Water Samples)

Operation of the hot water sampling equipment utilized on-site tap water as the water source for generating the rinsate. Contaminants already present in source water were identified by sampling the source water prior to its use for sampling. Table 4-6 shows the results of the sample analyses of source water samples. In addition, since RFP has

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	13 of 16

a single domestic water source, additional analytical data on RFP domestic water obtained from the RFP Industrial Hygiene department are also presented in Table 4-6

The results shown in Table 4-6 indicate that several organic and inorganic compounds were present in the source water. Those that exceeded the CRQL in one or more of the source water samples were

silicon at 3670  $\mu$ g/l, cadmium at 10 8  $\mu$ g/l, calcium at 8120  $\mu$ g/l, iron at 674  $\mu$ g/l, sodium at 6250  $\mu$ g/l, bromodichloromethane up to 6  $\mu$ g/l, chloroform up to 180  $\mu$ g/l, and methylene chloride up to 21  $\mu$ g/l

The inorganic compounds detected are commonly found in water supplies and are not surprising. The detections of bromodichloromethane, chloroform, and methylene chloride may be due to their presence in the source water, or cross-contamination during laboratory analysis. Bromodichloromethane and chloroform are more likely to be present in the source water, whereas methylene chloride is more likely to be a laboratory cross-contaminant. These organic constituents were not expected at any of the IHSSs, partially due to their volatility and correspondingly short environmental half lives, but also because they were not listed as being part of the waste materials handled at any of the IHSSs. Therefore, their presence in source water samples did not interfere significantly with the objectives of the sampling effort to characterize IHSS-related contamination

### Field Accuracy - Hot Water Rinsate Blanks

Hot water rinsate blank samples were collected by applying distilled water to a clean glass surface using the hot water rinsate sampling system. Table 4-7 shows the analytical

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	14 of 16

results from these samples At this time, these results have been received only as hard copy, and have not been validated or entered into the RFEDS database

Table 4-7 shows the presence of DEHP in all three of the hot water rinsate blanks. The DEHP concentrations ranged from 19  $\mu$ g/l to 28  $\mu$ g/l. All three of the samples also showed phenol exceeding the calibration range of the analytical instrument. The samples were diluted and reanalyzed and showed phenol ranging from 180  $\mu$ g/l to 380  $\mu$ g/l

The hot water rinsate blanks also showed the presence of several metals, however, only three were detected above the CRQL. These were cadmium at 5.4  $\mu$ g/l and 11.7  $\mu$ g/l, lead at 4.1  $\mu$ g/l and 5.5  $\mu$ g/l, and zinc at 103  $\mu$ g/l to 133  $\mu$ g/l

The presence of cadmium, lead, and zinc is probably attributable to their presence in the distilled source water or in the metal components of the sampling system. However, the presence of DEHP and phenol is more clearly linked to leaching of these constituents from the sampling equipment. Therefore, these constituents at concentrations similar to those reported above should be considered artifacts of the sampling procedure.

#### Laboratory Accuracy

Accuracy of the laboratory data is assessed through the calculation of the percent recoveries (%R) from MS samples for inorganic analytes, MS/MSD samples for organic analytes, and any in-house or blind certified standard that the laboratory analyzes as part of the required QA/QC program. Acceptable accuracy for inorganic MS samples is routinely a recovery of 75% to 125%. The %R for the organic MS/MSD analyses is mandated by analytical methods for the specific spiked compounds. Acceptable accuracy of the in-house standards is a recovery of 80% and 120%. Use of method blanks analyses in the laboratory also assist in analytical accuracy. All these measurements are

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	15 of 16

evaluated during the RFEDS data validation process. When analytical accuracy goals are not achieved, data are normally rejected

Evaluation of the validation qualifiers cited for data rejection are summarized in Table 4-2 Rejection of data can often be associated with accuracy problems. However, as discussed in the validation section, less than 1% of the validated data has been rejected, which suggests that accuracy is not a significant problem with the presently validated data set

#### Representativeness

Representativeness expresses the degree to which sample data accurately and precisely represent a characteristic(s) of a population, parameter variations at a sampling point, or an environmental condition Representativeness is a qualitative parameter that is most concerned with proper network design, sampling locations, and sampling methods

Representativeness of the sources of contamination in OU15 IHSSs is supported by the extensiveness of the Phase I RFI/RI sampling effort in characterizing the investigation area. Representativeness is considered in project planning and supported by the Work Plan, QAA, and associated SOPs. The Work Plan was designed based on the results of the previous investigations and on the DQOs identified. The sampling activities were designed and conducted to define the existing sources of contamination present in OU15. The plans and procedures are reviewed and approved by appropriate technical and agency representatives. As a result, sampling design for the Phase I RFI/RI is assumed to be representative of site conditions.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	4 0, Final
Inside Building Closures	Page	16 of 16

#### Comparability

Comparability is used to express the confidence with which one set of data can be compared to another set. Comparability is promoted by using similar sampling and analytical methods and reporting data in uniform units. To achieve comparability for the Phase I RFI/RI data, all analyses and sampling techniques prescribed in the Work Plan are EPA accepted or equivalent methods. The data are reported in uniform units for each method and media. A demonstration of the comparability of the data is the general consistency in the results between the various sample locations within each IHSS as well as between different IHSSs.

#### Completeness

The objective of completeness is that the investigation provides enough planned data such that the objectives of the project are met. Completeness for the Phase I RFI/RI is evaluated by comparing the planned number to the actual number of samples collected and analyzed. The analytical results should be validated and deemed valid or acceptable to be considered in an assessment of completeness. The overall completeness goal for the Phase I RFI/RI is 90%

Completeness of the data set at the time of the preparation of this report is affected by the 57% of data not yet validated. As indicated above, the unvalidated data is still incorporated into the determination of the contaminant source definitions, thereby reducing the significance of this factor in the completeness determination.

As shown on Tables 3-1 and 3-2, the Phase I RFI/RI data set was to consist of a specific number of samples for each sample type for each IHSS Based on a comparison with the actual work completed, the Phase I RFI/RI data exceeded the completeness criteria of 90%

Table 4-1 Comparison of Proposed to Actual Hot Water Rinsate QC Sample Frequency

Sample Type	Proposed Frequency	Actual Frequency
Duplicates <sup>1</sup>	1/10 or 10%	9/22 or 40%
Field Blanks	One per source	4/4 or 100%
Equipment Rinsate Blanks <sup>2</sup>	1/20 or 5%	9/22 or 40%
Trip Blanks	1/20 or 5%	7/22 or 32%

NA = Not Applicable

NR = Not Required

 $1/10 = \text{one } Q\bar{C}$  sample per ten samples collected

- Duplicate samples were to be collected at a minimum of 1/10 or once per day of sampling, whichever was more frequent
- Equipment rinsate blanks were to be collected at a minimum of 1/20 or once per day of sampling, whichever was more frequent

# Table 4-2 Laboratory Qualifiers and Validation Codes

LAB <u>QUAL</u>	DESCRIPTION
*	Outside contract required QC limits - organic
*	DUP analysis outside control limits - inorganic
+	MSA correlation coeffecient less than 0 995 - inorganic
Α	TIC suspected aldol-conden product - organic
В	Analyte found in blank and sample - organic
В	Less than method detection limit but greater than or equal to instrument detection limit -inorganic
С	Pesticide where I D confirmed by GC/MS - organic
D	Compounds identified using secondary dilution factor - organic
D	No surrogate/matrix spike recovery, extract diluted
E	Concentration exceeds calibration range of instrument - organic
E	Estimated due to interference - inorganic
F	Estimated, compound off-scale in both columns - organic
G	Native analyte greater than 4 times spike added - inorganic
I	Interference
J	Estimated value less than sample's detection limit
K	Result is between the IDL and MDL (CRDL)
M	Duplication injection precision not met - inorganic
N S	Spiked recovery not within control limits - inorganic  Determined by MSA, can't be with + or W - inorganic
T T	Compound found in TCLP extract blank and sample
Ü	Undetected, analyzed for but not detected
w	Post-digestion spike outside of control limit - inorganic
X	Lab software flag, entered manually - organic
X	Detection limit greater than normal, sample matrix interference - inorganic
X	Result by calculation - GRRASP
Ÿ	Indistinguishable isomer in TIC - organic
Z	Questionable identification, matrix interference of columns - organic
VAL	
CODE	DESCRIPTION
	Indicates the record was not validated
A	Data is acceptable, with qualifications
В	Indicates compund was found in blank and sample
E	Associated value exceeds calibration range, dilute and reanalyze
J	Associated value is estimated quantity
JA P	Estimated, acceptable
R	Data is rejected
U	Analyzed, not detected at or above method detection limit  Data is valid
V VA	Data is valid, acceptable with qualifications
YAY	Analytical results in validation process
Z	Validation was not requested or performed
L	valuation was not requested of performed

Table 4-3
Duplicate Sample Results and Relative Percent Differences



	QC Code	QC Partner	Test Group	Result Type	Compound	Result	Error	Error Qualifier	Detection Limit	Validation Code	RPD
REAL			BNACLP	TRG	BENZOIC ACID	65			50	JA	
DUP BU	BŨ	BU00011ER	BNACLP	TRG	BENZOIC ACID	79			20	JA	19 4%
REAL			BNACLP	TRG	BENZYL ALCOHOL	S		ь,	01	4	
DUP BL	Bſ	BU00011ER	BNACLP	TRG	BENZYL ALCOHOL	7		_	10	∢	33 3%
REAL			BNACLP	TRG	BIS(2-ETHYLHEXYL)PHTHALATE	140			10	JA	
DUP BU	B	BU00011ER	BNACLP	TRG	BIS(2-ETHYLHEXYL)PHTHALATE	091			10	γſ	13 3%
REAL			BNACLP	TRG	BUTYL BENZYL PHTHALATE	38			01	JA	
DUP BI	M	BU00011ER	BNACLP	TRG	BUTYL BENZYL PHTHALATE	51			10	λl	29 2%
REAL			BNACLP	TRG	DI-n-BUTYL PHTHALATE	13			01	>	
DUP BI	M	BU00011ER	BNACLP	TRG	DI-n-BUTYL PHTHALATE	17			01	>	26 7%
REAL			BNACLP	TRG	DI-n-OCTYL PHTHALATE	9		_	10	∢	
DUP BU	B	BU00011ER	BNACLP	TRG	DI-n-OCTYL PHTHALATE	<b>∞</b>		-	10	4	28 6%
REAL			BNACLP	TRG	DIETHYL PHTHALATE	3		ſ	10	4	
DUP BI	B	BU00011ER	BNACLP	TRG	DIETHYL PHTHALATE	3		_	10	∢	%00
REAL			BNACLP	TRG	PHENOL	45			10	>	
DUP B	B	BU00011ER	BNACLP	TRG	PHENOL	9			10	>	36 4%
REAL			DRADS	TRG	GROSS ALPHA	7.9	12		0 82	>	
DUP B	B	BU00011ER	DRADS	TRG	GROSS ALPHA	8.7	13		690	>	<b>%96</b>
REAL			DRADS	REP	GROSS ALPHA	7 9	1 3		0 87	>	<b>%</b> 0 0
REAL			DRADS	TRG	GROSS BETA	=	40		5.5	>	
DUP B	Щ	BU00011ER	DRADS	TRG	GROSS BETA	17	4 1		5 1	>	42 9%
REAL			DRADS	REP	GROSS BETA	17	43		98	>	42 9%
REAL			DRADS	TRG	PLUTONIUM-239/240	023	0 012	В	0000	>	
DUP B	B	BU00011ER	DRADS	TRG	PLUTONIUM-239/240	024	0 012	В	0 007	>	4 3%
REAL			DRADS	TRG	RADIUM-226	37	0 18	BJ	0 26	∢	
DUP B	2	BU00011ER	DRADS	TRG	RADIUM-226	49	0 14	BJ	0 14	∢	27 9%
REAL			DRADS	TRG	URANIUM-233,-234	93	17	В	0 11	∢	
DUP B	В	BU00011ER	DRADS	TRG	URANIUM-233,-234	96	1 8	В	0 037	∢	3 2%
REAL			DRADS	TRG	URANIUM-235	22	0 20	-	0 036	∢	
DUP B	В	BU00011ER	DRADS	TRG	URANIUM-235	44	0 29	<b>-</b>	0 063	<b>∀</b>	%£ 99
REAL			DRADS	TRG	URANIUM-238		0 44	В	0 061	¥	

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	Sample	οc		Test	Result					Detection	Validation	
SSH	Number	Code	QC Partner	Group	Type	Compound	Result	Error	Qualifier	Limit	Code	RPD
178	BU00012ER	DUP	BU00011ER	DRADS	TRG	URANIUM-238	12	0 20	В	0 063	V	18 2%
178	BU00011ER	REAL		VOACLP	TRG	CHLOROFORM	3		_	2	¥	
178	BU00012ER	DUP	BU00011ER	VOACLP	TRG	CHLOROFORM	2		-	5	¥	-40 0%
179	BU00033ER	REAL		BNACLP	DIL	2-Pyrrolidinone, 1-methyl-	64		_		⊀	
179	BU00033ER	REAL		BNACLP	TRG	4,4'-ISOPROPYLIDENEDIPHENOL	71		_		<b>&gt;</b>	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	4,4'-ISOPROPYLIDENEDIPHENOL	71		۰,		Y	<b>%</b> 0 0
179	BU00033ER	REAL		BNACLP	TRG	BENZOIC ACID	48		n	20	Y	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	BENZOIC ACID	21		_	20	¥	-78 3%
179	BU00033ER	REAL		BNACLP	TRG	BENZYL ALCOHOL	2		_	10	>	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	BENZYL ALCOHOL	01		n	01	Y	133 3%
179	BU00033ER	REAL		BNACLP	TRG	BIS(2-ETHYLHEXYL)PHTHALATE	470		ш	01	<b>&gt;</b>	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	BIS(2-ETHYLHEXYL)PHTHALATE	490		ш	01	Y	4 2%
179	BU00033ER	REAL		BNACLP	DIL	BIS(2-ETHYLHEXYL)PHTHALATE	720		Ω	10	¥	
179	BU00034ER	DUP	BU00033ER	BNACLP	DIL	BIS(2-ETHYLHEXYL)PHTHALATE	0/9		D	10	<b>\</b>	-7 2%
179	BU00033ER	REAL		BNACLP	TRG	BUTYL BENZYL PHTHALATE	5		ſ	10	⊁	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	BUTYL BENZYL PHTHALATE	4		ſ	10	>	-22 2%
179	BU00033ER	REAL		BNACLP	TRG	DI-n-OCTYL PHTHALATE	30			10	⅄	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	DI-n-OCTYL PHTHALATE	29			10	<b>\</b>	-3 4%
179	BU00033ER	REAL		BNACLP	DIL	DI-n-OCTYL PHTHALATE	24		ſΩ	01	<b>\</b>	
179	BU00034ER	DUP	BU00033ER	BNACLP	DIL	DI-n-OCTYL PHTHALATE	33		ΓΩ	01	>	316%
179	BUCOO33ER	REAL		BNACLP	TRG	DIETHYL PHTHALATE	3		-	01	<b>&gt;</b>	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	DIETHYL PHTHALATE	01		n	10	<del>۲</del>	107 7%
179	BU00033ER	REAL		BNACLP	TRG	PHENOL	78			10	Y	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	PHENOL	95			01	Y	19 7%
179	BU00033ER	REAL		BNACLP	DIL	PHENOL	8		Ω	10	Y	
179	BU00034ER	DUP	BU00033ER	BNACLP	DIL	PHENOL	8		DI	01	Y	<b>%</b> 0 0
179	BU00033ER	REAL		BNACLP	TRG	Phenol, 4,4'-(1-methylethyli	7.1		'n		λ	
179	BU00034ER	DUP	BU00033ER	BNACLP	TRG	Phenol, 4,4'-(1-methylethyli	7.1		_		⋆	<b>%</b> 0 0
179	BU00033ER	REAL		DRADS	TRG	AMERICIUM-241	0 007	0 004	-	0 001	>	
179	BU00034ER	DUP	BU00033ER	DRADS	TRG	AMERICIUM-241	0 007	0 004	,	0 001	>	<b>%</b> 0 0
179	BU00033ER	REAL		DRADS	TRG	GROSS ALPHA	<u>8</u>	13		0.51	>	

Page 3 of 16

**Duplicate Sample Results and Relative Percent Differences** Table 4-3

12 0 56 V -5 7% 2 8 2 5 V 2 7 2 3 V -7 7% 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Result Type Compound Result
25 V 23 V 00005 V 00007 V B 0040 A B 0012 A B 013 A BJ 0043 A BJ 0043 A BJ 0043 A BJ 0043 A C V J V J V J V J V J V D 10 V J V J V J V J V J V J V J V J	
27 23 V 0004 J 0005 V 0008 0007 V 0050 B 0070 A 0079 B 012 A 0070 B 013 A 0070 B 0035 A 0070 B 0043 A 1	-
0005 0004 J 0005 V 86 0050 B 0007 V 86 0050 B 0040 A 66 0050 B 0070 A 30 079 B 012 A 31 094 B 013 A 017 017 BJ 0043 A 19 29 B 0062 A 16 28 B 015 A 29 J Y 29 J V 29 J V 150 E 10 Y 150 DJ 10 Y 17 J J V 18 DJ 10 Y 47 D 10 Y 10 Y 47 D 10 Y 10 O 10	_
86       0 0 50       B       0 0 40       A         30       0 79       B       0 0 12       A         33       0 9 4       B       0 13       A         0 17       0 17       B J       0 0 0 3       A         0 29       B J       0 0 0 4 3       A         19       2 9       B J       0 0 0 4 3       A         29       J       J       Y       Y         29       J       J       Y       Y         150       E       10       Y         150       E       10       Y         150       D       I       Y	TRG PLUTONIUM-239/240 TRG PI ITONII M-239/240
66       0 0 50       B       0 0 70       A         3 0       0 7 9       B       0 12       A         3 1       0 9 4       B       0 13       A         0 1 7       0 1 7       B 1       0 0 0 35       A         0 1 1       0 2 6       B 1       0 0 0 0 3       A         1 1       2 9       B 1       0 0 0 0 3       A         1 2 9       B 1       0 0 0 0 0 0 0 0 0 0 0 0 0 0 0       A         2 9       B 1       0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
30       079       B       012       A         33       094       B       013       A         017       017       BJ       0043       A         031       026       BJ       0043       A         19       29       B       0062       A         16       28       B       015       A         29       J       Y       Y         29       J       Y       Y         150       B       015       A         150       B       015       A         150       Y       Y         150       Y       Y         15       J       Y         15       J       Y         15       J       Y         16       Y         17       J       Y         18       J       Y         19       J       Y         10       Y	
33       094       B       013       A         017       017       BJ       0035       A         031       026       BJ       0043       A         19       29       B       0062       A         16       28       B       015       A         29       J       Y       Y         29       J       Y       Y         150       E       10       Y         150       E       10       Y         150       D       I       Y         15       J       I       Y         15       J       Y       Y         15       J       Y       Y         16       Y       Y       Y         17       J       Y       Y         18       J       I       Y         19       J       Y       Y         47       D       I       Y         47       D       I       Y         10       W       Y       Y         10       W       Y       Y         10       W       Y	TRG URANIUM-233,-234
017 017 BJ 0035 A 031 026 BJ 0043 A 19 29 B 0062 A 16 28 B 015 A 29 J Y 29 J Y 37 J J 190 E 10 Y 190 E 10 Y 15 J J 10 Y 147 J J 10 Y	TRG URANIUM-233,-234
031 026 BJ 0043 A 19 29 B 0062 A 16 28 B 015 A 29 J Y 29 J Y 37 J J Y 150 E 10 Y 17 J J 10 Y 18 J J J 18 J J J 19 J J 10 J 11 J 11 J 11 J 11 J 11 J 11 J	TRG URANIUM-235
19       29       B       0062       A         16       28       B       015       A         29       J       Y       Y         37       J       Y       Y         150       E       10       Y         190       E       10       Y         230       D       10       Y         15       D       10       Y         37       J       10       Y         47       J       10       Y         47       D       10       Y         47       D       10       Y         47       D       10       Y         47       D       10       Y         6       003       U       0002       V         90       003       U       0009       V         80       19       034       V	TRG URANIUM-235
16       28       B       015       A         29       J       Y       Y         37       J       Y       Y         36       J       I0       Y         190       E       I0       Y         230       D       I0       Y         7       J       I0       Y         15       D       I0       Y         37       J       Y       Y         47       D       I0       Y         6       003       U       0002       V         90       003       U       0009       V         50       19       034       V	TRG URANIUM-238
29 J Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	TRG URANIUM-238
29 J Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	TRG 1,3-ISOBENZOFURANDIONE
37       J       Y         36       J       Y         150       E       10       Y         190       E       10       Y         230       D       10       Y         7       J       10       Y         15       D       J       Y         37       J       Y       Y         47       J       Y       Y         47       D       10       Y         6       003       U       0002       V         9       19       034       V	DIL 1,3-ISOBENZOFURANDIONE
36       J       Y         150       IO       Y         190       E       10       Y         230       D       10       Y         7       J       10       Y         15       D       J       Y         37       J       Y       Y         47       J       Y       Y         47       D       10       Y         47       D       10       Y         47       D       10       Y         47       D       10       Y         6       003       U       0009       V         50       19       034       V	TRG 2-Pyrrolidinone, 1-methyl-
150 190 E 100 Y 230 D 100 Y  11 15 15 15 10 Y  14 17 10 Y  1	DIL 2-Pyrrolidinone, 1-methyl-
190       E       10       Υ         230       D       10       Υ         7       J       10       Υ         15       DJ       10       Υ         37       J       Υ       Υ         47       J       Y       Υ         47       D       10       Y         47       D       10       Y         47       D       10       Y         47       D       10       Y         0008       0 006       J       0 0002       V         0       003       U       0 0099       V         50       19       0 34       V	TRG BIS(2-ETHYLHEXYL)PHTHALATE
230 D 10 Y  7 J J 10 Y  15 DJ 10 Y  37 J Y  47 J Y  47 I0 Y  47 I0 Y  47 I0 Y  47 I0 Y  60008 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	TRG BIS(2-ETHYLHEXYL)PHTHALATE
J 10 Y  DJ 10 Y  J Y  J Y  10 Y	DIL BIS(2-ETHYLHEXYL)PHTHALATE
DJ 10 Y  DJ 10 Y  J Y  J Y  J Y  O 0006 J 0 0002 V  O 003 U 0 0099 V	
DJ 10 Y J Y J 10 Y 10 Y 10 Y 10 Y 0006 J 0002 V 003 U 0009 V	TRG DI-n-OCTYL PHTHALATE
J Y J 10 Y 10 Y 10 Y 0 006 J 0 002 V 003 U 0 009 V 19 034 V	DIL DI-n-OCTYL PHTHALATE
J 10 Y 10 Y 10 Y 10 Y 10 O 006 J 0 0002 V 0009 V 19 O 19 O 034 V	TRG N-METHYLPYRROLIDONE
10 Y 10 Y 10 Y 0 006 J 0 002 V 003 U 0 009 V 19 0 34 V	DIL N-METHYLPYRROLIDONE
10 Y 0 006 J 0 002 V 003 U 0 009 V 1 9 0 34 V	TRG PHENOL
D 10 Y 0 006 J 0 0002 V 003 U 0 009 V 1 9 0 34 V	TRG PHENOL
0 006 J 0 002 V 003 U 0 009 V 1 9 0 34 V	DIL PHENOL
003 U 0 009 V 1 9 0 34 V	TRG AMERICIUM-241
1.9 0.34	TRG AMERICIUM-241
	TRG GROSS ALPHA

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD	<b>%</b> 0 0		21 1%		33 3%		-68 2%	-21 4%		-8 7%		120 0%		14 4%		-25 0%		<b>%</b> 0 0		8 3%	200 0%	200 0%		-18 2%		-2 6%		<b>%</b> 0 0		22 2%
Validation	Code	>	>	>	>	>	A	<b>4</b>	A	∢	∢	∢	¥	A	4	>	>	4	¥	>	<b>&gt;</b>	>	>	<b>&gt;</b>	>	<b>&gt;</b>	<b>&gt;</b>	<b>&gt;</b>	Y	<b>\</b>	>
Detection	Limit	0 42	26	2.5	0 004	0 002	0 11	0 12	0 12	0 0 0 5 6	0 13	0 031	0 13	0 031	0 076	5	S	2	5					10	10	10	10	01	10	10	01
	Qualifier				_	ſ	В	BJ	BJ	В	В	BJ		В	В			ſ	ſ	ſ	ſ	ſ	-	-	-	ш	ш	Q	D	ſ	n
	Error	19	37	4 0	900 0	900 0	0800	0800	0600	1 9	2.2	0 22	0 53	73	9.5																
	Result	20	55	89	0 005	0 007	57	28	0 46	12	=	030	12	28	29	27	21	_	_	23	25	7.1	38	9	5	390	380	520	520	<b>∞</b>	2
II.	e Compound	G GROSS ALPHA	G GROSS BETA	3 GROSS BETA	3 PLUTONIUM-239/240	3 PLUTONIUM-239/240	3 RADIUM-226	3 RADIUM-226	P RADIUM-226	G URANIUM-233,-234	G URANIUM-233,-234	G URANIUM-235	G URANIUM-235	G URANIUM-238	3 URANIUM-238	3 METHYLENE CHLORIDE	3 METHYLENE CHLORIDE	3 TOLUENE	3 TOLUENE	3 1,3-ISOBENZOFURANDIONE	3 1,3-ISOBENZOFURANDIONE	. 2-N-BUTOXYETHANOL	3 4,4'-ISOPROPYLIDENEDIPHENOL	3 BENZYL ALCOHOL	3 BENZYL ALCOHOL	3 BIS(2-ETHYLHEXYL)PHTHALATE	3 BIS(2-ETHYLHEXYL)PHTHALATE	BIS(2-ETHYLHEXYL)PHTHALATE	BIS(2-ETHYLHEXYL)PHTHALATE	3 BUTYL BENZYL PHTHALATE	3 BUTYL BENZYL PHTHALATE
Result	Type	TRG	TRG	TRG	TRG	TRG	TRG	TRG	REP	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	DIL	TRG	TRG	TRG	TRG	TRG	DIL	DIL	TRG	TRG
Test	Group	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	VOACLP	VOACLP	VOACLP	VOACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP
	QC Partner	BU00023ER		BU00023ER		BU00023ER		BU00023ER			BU00023ER		BU00023ER		BU00023ER		BU00023ER		BU00023ER		BU00027ER	BU00027ER	BU00027ER		BU00027ER		BU00027ER		BU00027ER		BU00027ER
οc	Code	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	DUP	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP
Sample		BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00023ER	BU00024ER	BU00027ER	BU00028ER	BU00028ER	BU00028ER	BU00027ER	BU00028ER	BU00027ER	BU00028ER	BU00027ER	BU00028ER	BU00027ER	BU00028ER
	SSHI	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180

Table 4-3

Duplicate Sample Results and Relative Percent Differences

Color   Colo	Sample QC		· '		Test	Result	•				Detection	Validation	4
44     10     Y       41     10     Y       42     DJ     10     Y       41     DJ     10     Y       23     DJ     10     Y       24     DJ     10     Y       47     DJ     10     Y       40     DJ     10     Y       47     DJ     10     Y       40     0.004     0.004     0.001     Y       40     0.004     0.004     0.001     Y       190     40     0.001     Y       180     63     28     V       180     64     30     V       180     63     30     V       180     63     38     0.13     A       180     60	ı	QC Partner Group	Group	ı	Ţ	Туре	Compound	Result	Error	Qualifier	Limit	Code	RPD
41       10       Y         42       DJ       10       Y         41       DJ       10       Y         23       DJ       10       Y         24       DJ       10       Y         40       DJ       10       Y         40       DJ       10       Y         40       DJ       10       Y         40       0.004       DJ       10       Y         40       0.004       DJ       10       Y         150       3.5       0.41       Y         150       4.0       0.015       Y         180       6.4       J       0.001       Y         180       6.4       J       0.001       Y         180       6.3       2.8       Y         180       6.3       2.8       Y         180       6.3       2.8       Y         180       6.3       2.8       Y         190       4.4       1.1       B       0.15       A         44       1.1       B       0.042       A         250       28       B       0.042	BU00027ER REAL BNACLP TRG	BNACLP			TRG		DI-n-BUTYL PHTHALATE	44			10	Υ	
42       DJ       10       Y         41       DJ       10       Y         23       DJ       10       Y         24       DJ       10       Y         40       DJ       10       Y         47       DJ       10       Y         40       DJ       10       Y         47       DJ       10       Y         40       0.004       0.015       V         150       3.5       0.01       Y         190       4.0       0.015       V         180       6.4       3.0       V         180       6.4       3.0       V         180       6.4       3.0       V         180       6.3       2.8       V         180       6.3       2.8       V         180       6.3       2.8       V         180       6.0       1.0       V         180       6.1       1.1       A         21       2.2       1.1       A         22       2.2       1.1       A         250       2.8       B       0.042       A	BU00027ER BNACLP	BU00027ER BNACLP	BNACLP		TRG		DI-n-BUTYL PHTHALATE	41			01	<b>&gt;</b>	-7 1%
HTHALATE 41 DJ 10 Y PHTHALATE 23 10 Y PHTHALATE 23 10 Y PHTHALATE 24 DJ 10 Y PHTHALATE 25 35 DJ 10 Y PHTHALATE 25 DJ 10 DJ 10 A PHTHALATE 25 BB 0042 A PHTHALATE 25 DJ 10 DJ A PHTHALATE 25 BB 0042 A PHTHALATE 25 BB 0042 A PHTHALATE 25 BB DJ 10 DJ	BNACLP	BNACLP	BNACLP		DIL		DI-n-BUTYL PHTHALATE	42		Ō	01	⊁	
PHTHALATE 23 10 Y PHTHALATE 22 10 Y PHTHALATE 23 DJ 10 Y PHTHALATE 24 DJ 10 Y PHTHALATE 25 DJ 10 DJ 10 A PHTHALATE 25 DJ 10 DJ 10 DJ 10 A PHTHALATE 25 DJ 10 DJ 10 DJ 10 A PHTHALATE 25 DJ 10 DJ 10 DJ 10 A PHTHALATE 25 DJ 10 DJ		BU00027ER BNACLP	BNACLP		DIL		DI-n-BUTYL PHTHALATE	41		D	01	<b>&gt;</b>	-2 4%
HTHALATE 22 10 Y PHTHALATE 23 DJ 10 Y PHTHALATE 24 DJ 10 Y PHTHALATE 24 DJ 10 Y 40 40 10 Y 41 150 10 Y 42 40 10 Y 44 11 BJ 015	BU00027ER REAL BNACLP TRG	BNACLP			TRG		DI-n-OCTYL PHTHALATE	23			10	<b>&gt;</b>	
PHTHALATE         23         DJ         10         Y           PHTHALATE         24         DJ         10         Y           47         40         10         Y         10         Y           40         47         DJ         10         Y         Y           41         47         DJ         10         Y         Y           241         -0 002         0 008         U         0 015         Y           241         0 004         0 004         J         0 001         Y           A         180         64         J         0 001         Y           A         180         63         28         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 007         0 004         J         0 004         Y           3,-234         37         53         B         0 015         A           5         4         11         B </td <td>BU00028ER DUP BU00027ER BNACLP TRG</td> <td>BU00027ER BNACLP</td> <td>BNACLP</td> <td></td> <td>TRG</td> <td></td> <td>DI-n-OCTYL PHTHALATE</td> <td>22</td> <td></td> <td></td> <td>01</td> <td><b>&gt;</b></td> <td>4 4%</td>	BU00028ER DUP BU00027ER BNACLP TRG	BU00027ER BNACLP	BNACLP		TRG		DI-n-OCTYL PHTHALATE	22			01	<b>&gt;</b>	4 4%
PHTHALATE         24         DJ         10         Y           40         47         10         Y           40         47         10         Y           40         47         DJ         10         Y           41         42         DJ         10         Y           241         -0 002         0 008         U         0 015         Y           241         150         3.5         0 41         Y           A         190         40         0 36         Y           A         190         40         0 36         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 006         0 004         J         0 004         Y           239/240         0 006         0 004         J         0 004         Y           3,-234         37         53         B         0 15         A           3,-234         40         59         B         0 042         A           5         11         B         0 042<	BU00027ER REAL BNACLP DIL	BNACLP			DIL		DI-n-OCTYL PHTHALATE	23		D	01	<b>X</b>	
47       10       Y         40       10       Y         40       10       Y         41       0.002       0.008       U       0.015       Y         241       0.004       0.004       J       0.0015       Y         241       0.004       0.004       J       0.0015       Y         241       0.004       0.004       J       0.001       Y         A       180       64       3.0       V         180       6.4       3.0       V         180       6.4       3.0       V         239/240       0.006       0.004       J       0.004       V         239/240       0.006       0.004       J       0.004       V         239/240       0.006       0.004       J       0.004       V         239/240       0.007       0.004       J       0.004       V         3,-234       3.7       5.3       B       0.015       A         5       4.5       1.1       B       0.042       A         8       220       28       B       0.042       A         8 <td< td=""><td>BU00028ER DUP BU00027ER BNACLP DIL 1</td><td>BU00027ER BNACLP DIL</td><td>BNACLP DIL</td><td>DIL</td><td></td><td>_</td><td>OI-n-OCTYL PHTHALATE</td><td>24</td><td></td><td>DJ</td><td>01</td><td><b>}</b></td><td>4 3%</td></td<>	BU00028ER DUP BU00027ER BNACLP DIL 1	BU00027ER BNACLP DIL	BNACLP DIL	DIL		_	OI-n-OCTYL PHTHALATE	24		DJ	01	<b>}</b>	4 3%
40       10       Y         47       DJ       10       Y         42       DJ       10       Y         241       -0 002       0 008       U       0 015       Y         241       0 004       0 004       J       0 001       Y         241       150       3 5       0 41       V         A       180       64       3 0       V         180       64       3 0       0 0       V         239/240       0 006       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         33-234       37       53       B       0 15       A         5       45       11       B       0 042       A         5       45       11       B       0 042       A         8       250       28       B       0 15       A         8       250       33       B       0 042 <td< td=""><td></td><td>BNACLP TRG</td><td>TRG</td><td>TRG</td><td></td><td>Д,</td><td>HENOL</td><td>47</td><td></td><td></td><td>01</td><td>¥</td><td></td></td<>		BNACLP TRG	TRG	TRG		Д,	HENOL	47			01	¥	
47       DJ       10       Y         42       DJ       10       Y         241       -0 002       0 008       U       0 015       V         241       0 004       0 004       J       0 001       V         4       150       3 5       0 41       V         180       64       3 0       V         180       63       28       V         190       1       0       0       V         190       1       0       0       V         1       1       0       0       V         1       1       0       0       V         1       1       <	BU00028ER DUP BU00027ER BNACLP TRG F	BU00027ER BNACLP TRG	BNACLP TRG	TRG	_		HENOL	40			01	¥	-16 1%
42       DJ       10       Y         241       -0 002       0 008       U       0 015       V         241       0 004       0 004       J       0 001       V         A       150       35       0 41       V         A       180       64       30       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -3,-234       37       53       B       0 13       A         5       44       11       B       0 042       A         8       250       28       B       0 15       A         8       250       33       B       0 042       A         9       1       0       1       V <td>BU00027ER REAL BNACLP DIL PI</td> <td>BNACLP DIL</td> <td>DIL</td> <td>DIL</td> <td>. 1</td> <td>Ы</td> <td>TENOL</td> <td>47</td> <td></td> <td>D</td> <td>01</td> <td><b>}</b></td> <td></td>	BU00027ER REAL BNACLP DIL PI	BNACLP DIL	DIL	DIL	. 1	Ы	TENOL	47		D	01	<b>}</b>	
241       -0 002       0 008       U       0 015       V         241       0 004       0 004       J       0 001       V         241       150       3 5       0 41       V         A       190       4 0       0 36       V         180       6 4       3 0       V         239/240       0 006       0 004       J       0 004       V         239/240       0 006       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         239/240       0 007       D       D       D       D       V         33-234       37       5 3       B       0 015       A       A         5       4 4       1 1       B       0 042       A         5       4 5       1 1       B       0 042       A         8       250       33       B       0 042       A         8       250       33       B       0 042       A         9       1       1       V	BU00028ER DUP BU00027ER BNACLP DIL PH	BU00027ER BNACLP DIL	BNACLP DIL	DIL		PF	IENOL	42		D	01	<b>&gt;</b>	-11 2%
241       0 0004       0 004       J       0 001       V         A       150       35       0 41       V         A       190       4 0       0 36       V         180       64       30       V         180       64       30       V         180       64       30       V         180       63       28       V         180       63       28       V         239/240       0 006       0 004       J       0 004       V         239/240       0 007       0 004       J       0 004       V         46       0 11       BJ       0 15       A         3,-234       40       59       B       0 12       A         5       44       11       B       0 042       A         8       250       33       B       0 042       A         8       250       33       B       0 042       A         8       250       33       J       10       A         A       150       80       1       V         A       140       77       1	BU00027ER REAL DRADS TRG AM	DRADS TRG	DRADS TRG	TRG	•	Ą	TERICIUM-241	-0 002	800 0	ח	0 0 15	>	
A 150 35 041 V A 190 40 036 V 180 64 30 V 180 63 28 V 239/240 0006 0004 J 0004 V 239/240 0007 0004 J 0001 V 46 011 BJ 015 A 3,-234 37 53 B 014 A 3,-234 40 59 B 0075 A 5 44 11 012 A 8 220 28 B 0042 A 8 220 33 B 042 A 39 J 10 A A 150 80 I V	BU00028ER DUP BU00027ER DRADS TRG AM	BU00027ER DRADS TRG	DRADS TRG	TRG	•	AM	ERICIUM-241	0 004	0 004		0 001	>	<b>%</b> 0 009
A 190 40 036 V 180 64 30 V 180 63 28 V 239/240 0006 0004 J 0004 V 239/240 0007 0004 J 0001 V 46 011 BJ 015 A 3,-234 37 53 B 014 A 3,-234 40 59 B 0075 A 5 44 11  012 A 8 220 28 B 015 A 8 220 28 B 042 A 39 J 10 A 31 150 80 I	_	DRADS TRG	DRADS TRG	TRG	_	GRO	SS ALPHA	150	3.5		0 41	>	
180       64       30       V         180       63       28       V         239/240       0006       0004       J       0004       V         239/240       0006       0004       J       0004       V         239/240       0007       0004       J       0001       V         46       011       BJ       015       A         3,-234       37       53       B       014       A         5       44       11       D       012       A         5       45       11       B       0042       A         8       220       28       B       015       A         8       250       33       B       0042       A         8       250       33       B       0042       A         A       150       80       1       V         A       140       77       1       V	_	BU00027ER DRADS TRG	DRADS TRG	TRG	_	GRO	SS ALPHA	190	4 0		0 36	>	23 5%
180       63       28       V         -339/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 006       0 004       J       0 004       V         -239/240       0 007       0 004       J       0 001       V         3,-234       37       53       B       0 14       A         5       44       11       D       0 12       A         5       45       11       B       0 042       A         8       220       28       B       0 15       A         8       250       33       B       0 042       A         8       250       33       B       0 042       A         39       J       10       A         A       150       80       1       V         A       140       77       1       V	_	DRADS TRG	DRADS TRG	TRG	_	GRO	SS BETA	180	6.4		3.0	>	
0 006 0 004 J 0 0004 V 0 0007 0 0004 J 0 0001 V 46 0 11 BJ 0 115 A 37 53 B 0 114 A 40 59 B 0 0075 A 44 11 BJ 0 0075 A 45 11 B 0 0042 A 520 28 B 0 015 A 520 33 B 0 015 A 530 J 10 A 5150 80 I V 140 77 I V	DUP BU00027ER DRADS TRG	BU00027ER DRADS TRG	DRADS TRG	TRG	_	GRO	SS BETA	180	63		2 8	>	<b>%</b> 0 0
39/240 0 0007 0 0004 J 0 0001 V 46 0 111 BJ 0 115 A 51 0 100 B 0 113 A 51 0 100 B 0 114 A 40 59 B 0 0075 A 44 111 B 0 012 A 45 111 B 0 0042 A 520 28 B 0 015 A 520 28 B 0 015 A 520 33 B 0 0042 A 39 J 10 A 150 80 I V 140 77 I V		DRADS TRG	TRG	TRG		PLU	TONIUM-239/240	900 0	0 004	-	0 004	>	
46       0 11       BJ       0 15       A         51       0 10       B       0 13       A         53       B       0 14       A         40       59       B       0 075       A         44       11       0 12       A         45       11       B       0 042       A         220       28       B       0 15       A         250       33       B       0 042       A         39       J       10       A         150       80       I       V         140       77       I       V	DUP BU00027ER DRADS TRG	BU00027ER DRADS TRG	DRADS TRG	TRG	_	곱	UTONIUM-239/240	0 007	0 004	_	0 001	>	15 4%
51 0 10 B 0 13 A 37 53 B 0 14 A 40 59 B 0075 A 44 11 0 012 A 45 11 B 0042 A 220 28 B 015 A 250 33 B 015 A 39 J 10 A 150 80 I V	BU00027ER REAL DRADS TRG RA	DRADS TRG	TRG	TRG		2	NDIUM-226	46	0 11	BJ	0 15	∢	
-234 37 53 B 014 A 40 59 B 0075 A 44 11 012 A 45 11 B 0042 A 220 28 B 015 A 250 33 B 0042 A 39 J 10 A 33 J 10 A 150 80 I V	_	BU00027ER DRADS TRG I	BU00027ER DRADS TRG I	TRG	_	≥	ADIUM-226	51	0 10	В	0 13	¥	10 3%
-234       40       59       B       0075       A         44       11       012       A         45       11       B       0042       A         220       28       B       015       A         250       33       B       0042       A         39       J       10       A         150       80       I       V         140       77       I       V	_	DRADS TRG	DRADS TRG	TRG	_	R R	ANIUM-233,-234	37	53	В	0 14	<b>V</b>	
44       11       012       A         45       11       B       0042       A         220       28       B       015       A         250       33       B       0042       A         39       J       10       A         33       J       10       A         150       80       I       V         140       77       I       V	_	BU00027ER DRADS TRG (	DRADS TRG 1	TRG	_	35	ANIUM-233,-234	40	5 9	В	0 075	Y	7 8%
45       11       B       0042       A         220       28       B       015       A         250       33       B       0042       A         39       J       10       A         33       J       10       A         150       80       I       V         140       77       I       V	_	DRADS TRG (	TRG	TRG	_	3	ANIUM-235	4 4	_		0 12	¥	
220 28 B 015 A 250 33 B 0042 A 39 J 10 A 33 J 10 A 150 80 I V	_	BU00027ER DRADS TRG 1	BU00027ER DRADS TRG 1	TRG	_	K	ANIUM-235	4 5	-	В	0 042	¥	2 2%
250 33 B 0042 A 39 J 10 A 33 J 10 A 150 80 I V 140 77 I V	_	DRADS TRG U	TRG	TRG	_	S.	ANIUM-238	220	28	В	0 15	A	
39 J 10 A 33 J 10 A 150 80 I V 140 77 I V	_	BU00027ER DRADS TRG I	BU00027ER DRADS TRG I	TRG	_	3	ANIUM-238	250	33	В	0 042	¥	12 8%
33 J 10 A 150 80 I V 140 77 I V	_	BNACLP DIL I	DIL	DIL	_	PH	ENOL	39		ſ	10	¥	
150 80 1 V 140 77 1 V	BU00041ER DUP BU00040ER BNACLP DIL P	BU00040ER BNACLP DIL	BU00040ER BNACLP DIL	DIL		Д	HENOL	33		Ţ	10	¥	-16 7%
140 77 I V	BU00040ER REAL DRADS TRG (	DRADS TRG	DRADS TRG	TRG	_	~	GROSS ALPHA	150	8 0		_	>	
	BU00041ER DUP BU00040ER DRADS TRG	BU00040ER DRADS TRG	DRADS TRG	TRG	_	_	GROSS ALPHA	140	11		-	>	<b>%</b> 6 9-

Table 4-3
Duplicate Sample Results and Relative Percent Differences

Group  DRADS  DRACLP  BNACLP  BNACLP	Compound GROSS ALPHA	Result			1		
DRADS BNACLP	GROSS ALPHA	1	Error	Cualifier	rimit	Code	RPD
DRADS BNACLP		150	7.8		_		%0 O
DRADS BNACLP	GROSS BETA	72	36		7	¥	
DRADS BNACLP	GROSS BETA	78	3 8		7	¥	<b>%</b> 0 <b>8</b>
DRADS DRADS DRADS DRADS DRADS DRADS DRADS DRADS DRADS BNACLP	GROSS BETA	80	3 8		2		10 5%
DRADS DRADS DRADS DRADS DRADS DRADS DRADS DRADS BNACLP	URANIUM-233,-234	24	2.9		0.5	>	
DRADS DRADS DRADS DRADS DRADS DRADS DRADS BNACLP	URANIUM-233,-234	56	3.1		90	>	<b>%</b> 0 <b>8</b>
DRADS DRADS DRADS DRADS DRADS DRADS BNACLP	URANIUM-233,-234	21	2.4		0 4		-13 3%
DRADS DRADS DRADS DRADS DRADS DRADS BNACLP	URANIUM-235	3.5	11 0		0.2	>	
DRADS DRADS DRADS DRADS BNACLP	URANIUM-235	53	96 0		0 2	>	40 9%
DRADS DRADS DRADS BNACLP	URANIUM-235	33	0 63		0.2		-5 9%
DRADS DRADS BNACLP	URANIUM-238	180	61		0.5	>	
DRADS BNACLP	URANIUM-238	200	70		0.5	>	10 5%
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	URANIUM-238	160	91		0 4		-11 8%
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1,3-Isobenzofurandione	38		•		7	
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1 3-Isobenzofurandione	78		_		7	<b>%</b> 0 69
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1,3-Isobenzofurandione	34		_		7	
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1,3-Isobenzofurandione	42		-		7	21 1%
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1-Hevanol, 2-ethyl-	36		_		2	
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	1-Hevanol, 2-ethyl-	78		_		7	73 7%
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	Benzoic acid, 4-(1, 1-dimethyl	130		_		2	
BNACLP BNACLP BNACLP BNACLP BNACLP BNACLP	Benzoic acid, 4-(1, 1-dimethyl	081		_		7	32 3%
BNACLP BNACLP BNACLP BNACLP BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	240		田	10	7	
BNACLP BNACLP BNACLP BNACLP BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	450		ш	01	7	%6 09
BNACLP BNACLP BNACLP BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	780		D	01	>	
BNACLP BNACLP BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	790		D	01	>	1 3%
BNACLP	DI-n-OCTYL PHTHALATE	2		_	01	¥	
BNACLP	DI-n-OCTYL PHTHALATE	4		_	01	¥	<i>%L</i> 99
	DI-n-OCTYL PHTHALATE	20		n	01	Z	184 6%
BUN004/EK BNACLF IKG	Hexadecanamide	160		_		7	200 0%
BNACLP TRG	Hevadecanoic Acid	81		_		7	
BU00047ER BNACLP TRG	Heyadecanoic Acid	31		_		7	53 1%

Page 7 of 16

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD		118%		33 3%		-7 1%		-2 3%		<b>%</b> 0 0		8 7%		16 7%		%2 99		-16 0%		4 1%		6 5%		%5 6		<b>%</b> 0 0		40 0%		32 6%		516%
Validation	Code	Y	<b>&gt;</b>	<b>&gt;</b>	>	<b>&gt;</b>	<b>&gt;</b>	<b>&gt;</b>	<b>\</b>	>	>	>	>	Z	7	∢	>	Z	7	>	>	>	>	Z	Z	>	7	Z	>	Ν	Ν	2	Z
Detection	Limit	2	3	7	2	0.5	0.5	0 2	0.2	0.5	0.5	10	10	10	10	10	10	20	20	20	20	01	01	01	01	01	01	10	01	10	10	01	01
	Qualifier										В			Ω	Ω	-	כ	ш	ш	Q	Ω			ſΩ	ď	В	BE	BD	BD			Q	D
	Error	86	11	3.1	3.5	32	3.2	0 79	080	20	21																						
	Result	160	180	45	63	29	27	4 4	43	210	210	110	120	110	130	5	10	270	230	250	240	01	Ξ	10	Π	160	160	140	210	54	75	46	78
ılı	pe Compound	G GROSS ALPHA	G GROSS ALPHA	G GROSS BETA	G GROSS BETA	G URANIUM-233,-234	G URANIUM-233,-234	G URANIUM-235	G URANIUM-235	.G URANIUM-238	.G URANIUM-238	G 2-METHYLPHENOL	G 2-METHYLPHENOL	1 2-METHYLPHENOL	1 2-METHYLPHENOL	.G 2-NITROPHENOL	G 2-NITROPHENOL	G BENZOIC ACID	G BENZOIC ACID	I BENZOIC ACID	I BENZOIC ACID	G BENZYL ALCOHOL	G BENZYL ALCOHOL	I BENZYL ALCOHOL	I BENZYL ALCOHOL	G BIS(2-ETHYLHEXYL)PHTHALATE	G BIS(2-ETHYLHEXYL)PHTHALATE	I BIS(2-ETHYLHEXYL)PHTHALATE	I BIS(2-ETHYLHEXYL)PHTHALATE	G BUTYL BENZYL PHTHALATE	G BUTYL BENZYL PHTHALATE	I BUTYL BENZYL PHTHALATE	I BUTYL BENZYL PHTHALATE
Result	Typ	TRG	H.	II.	E	TRG	T.	E.	TRG	T	TR	TR	TR	DLI		T.	T.	T.	TR	DL1		TRG		DLI						TRG	P TRG	P DL1	P DLI
Test	Group	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP
	QC Partner		BU00047ER		BU00047ER		BU00047ER		BU00047ER		BU00047ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER
00	$\tilde{Code}$	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP
Sample		m	BU00048ER	BU00047ER	BU00048ER	BU00047ER	BU00048ER	BU00047ER	BU00048ER	BU00047ER	BU00048ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	I BU00002ER	BU00003ER	BU00002ER	BU00003ER
	SSHI	204	204	204	204	204	204	204	204	204	204	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD		<i>%L 99-</i>		<b>%</b> 0 0		35 3%		133 3%		%I 9-		12 5%		1 7%	<b>%8 8-</b>		%9 9	-5 4%		-8 3%	-1 9%		2 0%	-4 0%			4 1%		-17 1%		
Validation	Code	~	4	¥	¥	7	7	¥	>	Z	7	>	>	>	>	7	>	Ν	7	Ν	Υſ	7	>	>	7	>	>	>	>	>	¥	*
Detection	Limit	92	10	10	10	01	10	10	10	10	10	10	01	100	100	100	200	200	200	100	001	100	200	200	200	0 004	0 61	0 65	26	26	0 003	700
	Qualifier	D	ſ	ſ	_	Ď	DĬ	_	n	П	Э	Q	Ω	В	В	В	В	В	В				В	В	В	BJ					В	۵
	Error																									900 0	0 93	10	2.5	2.4	0 024	01.0
	Result	10	5	7	7	7	10	2	10	170	160	150	170	11 8	12	108	396	42 3	37 5	9250	8510	0806	177	186	170	007	7 1	7.4	61	91	15	3/
	Compound	DI-n-BUTYL PHTHALATE	DI-n-BUTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	ISOPHORONE	ISOPHORONE	PHENOL	PHENOL	PHENOL	PHENOL	LITHIUM	LITHIUM	LITHIUM	MOLYBDENUM	MOLYBDENUM	MOLYBDENUM	SILICON	SILICON	SILICON	STRONTIUM	STRONTIUM	STRONTIUM	AMERICIUM-241	GROSS ALPHA	GROSS ALPHA	GROSS BETA	GROSS BETA	PLUTONIUM-239/240	700 74 110 74
Kesult	Type	TRG	TRG	TRG	TRG	DL1	DLI	TRG	TRG	TRG	TRG	DL1	DLI	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	TRG	TRG	TRG	TRG	Ć dr
l est	Group	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	
	QC Partner		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER		BU00002ER			BU00002ER			BU00002ER			BU00002ER				BU00002ER		BU00002ER		
ن کا	Code	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	REAL	DUP	REAL	DUP	REAL	1 4 11
Sample	Number	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BUOOOOZER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	BU00002ER	0.7.0000110
	SSHI	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD	-129 1%	200 0%	200 0%	200 0%		<b>%</b> 0 0	95 7%		9 5%	<b>%</b> 2 99-		%0 6	-5 3%		-133 3%	-35 3%		5 2%	-6 3%		-13 3%	<b>%8 8-</b>		-65 7%	83 4%		<b>%</b> 9 69-	4 5%	
Validation	Code	V	¥	<b>∢</b>	<	>	>	2	JA	>	2	>	>	Z	JA	JA	Z	Ρſ	JA	Z	>	>	2	Ν	JA	2	>	>	7	JA
Detection	Limit	0 10	690 0	690 0	0 12	200	700	200	01	10	01	200	200	200	5	5	S	2000	2000	2000	25	25	25	100	100	100	5	5	5	2000
	Error Qualifier	ſ	æ	-		Ω	Ω	В	В	В	В	В	В	В		n									n					В
	Error	0 0 0 0	17	0 29	0 48																									
	Result	14	6.2	25	65	981	186	52.7	2	2 2	10	28 8	315	27 3	17	34	11 9	37400	39400	35100	34 4	30 1	315	135	68 2	328	16	4 4	8 7	2690
	Сотроинд	RADIUM-226	URANIUM-233,-234	URANIUM-235	URANIUM-238	ALUMINUM	ALUMINUM	ALUMINUM	ARSENIC	ARSENIC	ARSENIC	BARIUM	BARIUM	BARIUM	CADMIUM	CADMIUM	CADMIUM	CALCIUM	CALCIUM	CALCIUM	COPPER	COPPER	COPPER	IRON	IRON	IRON	LEAD	LEAD	LEAD	MAGNESIUM
Result	Type	TRG	TRG	TRG	TRG	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG
Test	Group	DRADS	DRADS	DRADS	DRADS	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	<b>SMETCL</b>	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL
	QC Partner	BU00002ER	BU00002ER	BU00002ER	BU00002ER		BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER		
$\mathcal{G}_{\mathcal{C}}$	Code	DUP	DUP	DUP	DUP	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL
Sample	Number	BU00003ER	BU00003ER	BU00003ER	BU00003ER	BU00002ER	BU00003ER	BUOOOOZER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER
	SSHI	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	21	211	211	211	211	211	211	211	211	211	211	211	211	211

Table 4-3
Duplicate Sample Results and Relative Percent Differences

tion	e RPD	\$ 1%	-1 1%		-37 3%	25 0%		9 2%	12 5%		4 5%	<b>%</b> 0 0		4 8%	4 0%		-11 1%	-8 2%		-0 4%	0 2%		-12 6%	-22 9%		-22 5%	5 3%		-107 7%		-22 2%	
Validation	Code	JA	7	JA	JA	7	>	>	2	>	>	Z	>	>	2	JA	JA	7	Ϋ́	JA	2	>	>	Z	>	>	2	>	∢	>	∢	
Detection	Limit	2000	2000	15	15	15	7	7	2	40	40	40	2000	2000	2000	2	5	\$	2000	2000	2000	20	20	20	70	70	20	01	10	5	\$	
	Error Qualifier	В	В	В	B	æ	В	В	æ	Ω	В	Ω				Ω	n	В				<b>6</b>	В	В				n	-,	n	-	
	Result	2830	7660	3.5	2.4	4.5	15	91	0 17	98	6	98	25600	24400	24600	38	3.4	3.5	53900	53700	54000	18 5	163	147	40 5	32 3	42.7	10	3	5	4	
	Сотроинд	MAGNESIUM	MAGNESIUM	MANGANESE	MANGANESE	MANGANESE	MERCURY	MERCURY	MERCURY	NICKEL	NICKEL	NICKEL	POTASSIUM	POTASSIUM	POTASSIUM	SELENIUM	SELENIUM	SELENIUM	SODIUM	SODIUM	SODIUM	VANADIUM	VANADIUM	VANADIUM	ZINC	ZINC	ZINC	2-BUTANONE	2-BUTANONE	METHYLENE CHLORIDE	METHYLENE CHLORIDE	
Result	Type	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	DUP	TRG	TRG	TRG	TRG	
Test	Group	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	<b>SMETCL</b>	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	VOACLP	VOACLP	VOACLP	VOACLP											
	QC Partner	BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER			BU00002ER		BU00002ER	
$j\sigma$	Code	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	REAL	DOP	REAL	REAL	DUP	REAL	REAL	DUP	REAL	DUP	
Sample	Number	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00002ER	BU00003ER	BU00002ER	BU00003ER	
	SSHI	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD		%6 81-		-28 6%		-143%		<b>25 7%</b>		-18 2%		51 2%		-15 9%		54 5%		-28 6%		69 4%		-48 1%		55 4%		<b>%8</b> 0		-13 6%		%I <i>L</i> -		-0 3%
Validation	Code	Z	2	∢	∢	Z	Z	>	>	2	2	Ν	JA	>	>	Z	2	>	>	2	7	>	>	2	7	>	>	ΙĄ	ΙĄ	ΙĄ	Ν	>	>
Detection	Limit	50	20	10	10	01	10	10	01	10	01	10	10	01	10	10	10	01	01	10	01	01	01	01	01	100	100	200	200	100	100	700	200
	Qualifier	DJ	DJ	_	ſ	BE	BE	BD	BD	ш	田	Q	D			ā	D			Ω	M			G	D	В	В	B	B			В	В
	Error																																
	Result	52	43	∞	9	300	260	220	390	300	250	11	130	34	29	20	35	24	81	91	33	<i>L</i> 9	4	30	53	12 1	12.2	10 2	68	5110	4760	78 8	78 6
	Compound	BENZOIC ACID	BENZOIC ACID	BENZYL ALCOHOL	BENZYL ALCOHOL	BIS(2-ETHYLHEXYL)PHTHALATE	BIS(2-ETHYLHEXYL)PHTHALATE	BIS(2-ETHYLHEXYL)PHTHALATE	BIS(2-ETHYLHEXYL)PHTHALATE	BUTYL BENZYL PHTHALATE	BUTYL BENZYL PHTHALATE	BUTYL BENZYL PHTHALATE	BUTYL BENZYL PHTHALATE	DI-n-BUTYL PHTHALATE	DI-n-BUTYL PHTHALATE	DI-n-BUTYL PHTHALATE	DI-n-BUTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	DI-n-OCTYL PHTHALATE	PHENOL	PHENOL	PHENOL	PHENOL	LITHIUM	LITHIUM	MOLYBDENUM	MOLYBDENUM	SILICON	SILICON	STRONTIUM	STRONTIUM
Result	Type	DEI	DL1	TRG	TRG	TRG	TRG	DL1	DL1	TRG	TRG	DL1	DLI	TRG	TRG	DLI	DL1	TRG	TRG	DL1	DLI	TRG	TRG	DLI	DLI	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG
Test	Group	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	BNACLP	METAD	METAD	METAD	METAD	METAD	METAD	METAD	METAD
	QC Partner		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER
οō	Code	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP
Sample	Number	BU00008ER	BU00000ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00000ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00000ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER
	SSHI	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211

Page 12 of 16

Table 4-3

Duplicate Sample Results and Relative Percent Differences

	RPD		-200 0%	20 0%		<b>%</b> 2 99-		28 2%		-42 4%	43 1%		-14 3%		-200 0%		-46 2%		-12 5%		<b>%</b> 0 0		16 <i>7</i> %		119 5%		-1 5%		-18 9%		<b>%</b> 9 6-		-57 9%
Validation	Code	>	>	>	>	>	>	>	∢	4	∢	∢	∢	∢	∢	∢	4	>	>	JA	Ν	>	>	Ρſ	Ν	JA	Ν	>	>	>	>	JA	λί
Detection	Limit	900 0	0 004	0 002	1 4	0 54	3.0	26	0 001	0 003	0 005	0 14	0 14	0.053	0 044	0 053	0 074	09	09	01	0	200	200	5	5	2000	2000	01	01	25	25	001	001
	Qualifier	Ω	n	BJ					В	В				_	Ω	-	<u>_</u>	æ	n	В	n	8	В	n				В	n				
	Error	0 004	0 002	0 004	14	0 54	2 2	2 1	0 008	900 0	0 022	99 0	0 56	0 22	0 222	0 29	0 21																
	Result	003	0	0 005	4 8	2 4	6.7	8 9	03	013	0 031	1 5	13	61	0	32	2	28 9	25 5	_	-	13.7	16 2	3.4	13.5	13600	13400	8	6.7	437	39.7	323	178
ĮĮ	Compound	3 AMERICIUM-241	3 AMERICIUM-241	AMERICIUM-241	GROSS ALPHA	GROSS ALPHA	GROSS BETA	GROSS BETA	BEUTONIUM-239/240	BLUTONIUM-239/240	PLUTONIUM-239/240	3 URANIUM-233,-234		J. URANIUM-235	3 URANIUM-235	3 URANIUM-238	J. URANIUM-238	3 ANTIMONY	3 ANTIMONY	3 ARSENIC	3 ARSENIC	3 BARIUM	) BARIUM	3 CADMIUM	3 CADMIUM	) CALCIUM	CALCIUM	CHROMIUM	CHROMIUM CHROMIUM	GOPPER COPPER	GOPPER COPPER	IRON .	J IRON
Resul	Type	TRG	TRG	REP	TRG	TRG	TRG	TRG	TRG	TRG	REP	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG	TRG
Test	Group	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	DRADS	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL
	QC Partner		BU00008ER			BU00008ER		BU00008ER		BU00008ER			BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER		BU00008ER
$j\sigma$	Code	REAL	DUP	REAL	REAL	DUP	REAL	DUP	REAL	DUP	REAL	REAL	DUP	REAL	DUP	REAL	DOP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP
Sample	Number	BU00008ER	BU00009ER	BU00008ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00000ER	BU00008ER	BU00008ER	BU00009ER	BU00008ER	BU00000ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER	BU00008ER	BU00009ER
	SSHI	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211	211

Table 4-3
Duplicate Sample Results and Relative Percent Differences

Sample	50 OC	1		Test	Result	,			,	Detection	Validation	
IHSS Number Code QC Partner Group	QC Partner		Gro	4	Type	Compound	Result	Error	Error Qualifier	Limit	Code	RPD
BU00008ER REAL SMETCI		SMETC	SMETC		TRG	LEAD	7.5			5	>	
BU00009ER DUP BU00008ER SMETCL	BU00008ER	_	SMETCL		TRG	LEAD	89			5	>	<b>%8</b> 6-
BU00008ER REAL SMETCL		SMETCL	SMETCL		TRG	MAGNESIUM	2000		В	2000	ΙΥ	
BU00009ER DUP BU00008ER SMETCL	BU00008ER SMETCL	SMETCL			TRG	MAGNESIUM	1980		В	2000	ΙΥ	<b>%0 1-</b>
SMETCL	SMETCL	SMETCL			TRG	MANGANESE	63		В	15	ΙΑ	
DUP BU00008ER SMETCL	BU00008ER SMETCL	SMETCL		_	TRG	MANGANESE	7.9		В	15	JA	22 5%
BU00008ER REAL SMETCL T	SMETCL			[	TRG	POTASSIUM	15300			2000	>	
DUP BU00008ER SMETCL	BU00008ER SMETCL	SMETCL		Ε	TRG	POTASSIUM	16500			2000	>	7 5%
REAL SMETCL	SMETCL	SMETCL		F	TRG	SODIUM	28800			2000	γ	
DUP BU00008ER SMETCL	BU00008ER SMETCL	SMETCL	_	Ë	TRG	SODIUM	28800			2000	Ν	<b>%</b> 0 0
BU00008ER REAL SMETCL TRG	SMETCL			TR	(7	VANADIUM	Π		മ	20	>	
BU00009ER DUP BU00008ER SMETCL TRG	BU00008ER SMETCL	SMETCL		TRG		VANADIUM	83		В	20	>	-28 0%
BU00008ER REAL SMETCL TRG	SMETCL	,	,	TRG		ZINC	816			70	>	
BU00009ER DUP BU00008ER SMETCL TRG	BU00008ER SMETCL	SMETCL		TRG		ZINC	746			70	>	-20 7%
BU00017ER REAL BNACLP TRG	BNACLP			TRG		BENZOIC ACID	Ξ		_	20	∢	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		BENZOIC ACID	6		<u>.</u>	20	∢	-20 0%
BU00017ER REAL BNACLP TRG	BNACLP			TRG		BENZYL ALCOHOL	2		_	01	∢	
DUP BU00017ER BNACLP	BU00017ER BNACLP	BNACLP		TRG		BENZYL ALCOHOL	2		_	10	∢	<b>%</b> 0 0
BU00017ER REAL BNACLP TRG	BNACLP			TRG		BIS(2-ETHYLHEXYL)PHTHALATE	53			01	λl	
BU000018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		BIS(2-ETHYLHEXYL)PHTHALATE	53			2	ΙĄ	<b>%</b> 0 0
BUOWITER REAL BNACLP TRG	BNACLP			TRG		BUTYL BENZYL PHTHALATE	21			01	Ρſ	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		BUTYL BENZYL PHTHALATE	23			01	λl	%1 6
BU00017ER REAL BNACLP TRG	BNACLP			TRG		DI-n-BUTYL PHTHALATE	01		n	01	>	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		DI-n-BUTYL PHTHALATE	7		-	01	∢	-133 3%
BU00017ER REAL BNACLP TRG	BNACLP	BNACLP		TRG		DI-n-OCTYL PHTHALATE	2		_	01	∢	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		DI-n-OCTYL PHTHALATE	7		-	01	∢	<b>%</b> 0 0
BU00017ER REAL BNACLP TRG	BNACLP			TRG		DIETHYL PHTHALATE	9		-	01	∢	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRG		DIETHYL PHTHALATE	9		_	01	∢	<b>%</b> 0 0
BU00017ER REAL BNACLP TRG	BNACLP			TRO		PHENOL	81			01	>	
BU00018ER DUP BU00017ER BNACLP TRG	BU00017ER BNACLP	BNACLP		TRO	۲٦	PHENOL	81			01	>	%00
BU00017ER REAL METAD TRG	METAD	_	_	TRO		LITHIUM	256			100	>	
BU00018ER DUP BU00017ER METAD TRG	BU00017ER METAD	METAD		TRG		LITHIUM	247			001	>	-3 6%

Table 4-3 Duplicate Sample Results and Relative Percent Differences

Table 4-3
Duplicate Sample Results and Relative Percent Differences

	RPD		-1 6%		-6 1%		2 1%		<b>%8 8-</b>		1 3%		1 4%		%00		%19		0 7%		-2 5%		-3 7%		-4 7%		3 4%		7 4%		<b>%</b> 0 0		%0 0
Validation	Code	>	>	>	>	>	>	JA	JA	>	>	γſ	JA	>	>	>	>	>	>	>	>	>	>	Υſ	Ν	>	>	>	>	>	>	A	∢
Detection	Limit	10	10	20	50	25	25	100	001	5	\$	2000	2000	15	15	2	7	40	40	2000	2000	01	01	2000	2000	20	70	10	01	S	S	5	\$
	Error Qualifier																															-	_
	Result	37.5	369	72.2	6 2 9	281	287	143	131	153	155	14000	14200	1200	1200	16	17	2630	2670	5270	5140	22 1	213	17400	16600	986	1020	26	28	5	5		-
	Compound	CHROMIUM	CHROMIUM	COBALT	COBALT	COPPER	COPPER	IRON	IRON	LEAD	LEAD	MAGNESIUM	MAGNESIUM	MANGANESE	MANGANESE	MERCURY	MERCURY	NICKEL	NICKEL	POTASSIUM	POTASSIUM	SILVER	SILVER	SODIUM	SODIUM	ZINC	ZINC	4-METHYL-2-PENTANONE	4-METHYL-2-PENTANONE	CHLOROFORM	CHLOROFORM	ETHYLBENZENE	ETHYLBENZENE
Result	Type	TRG	DIL	DIL	TRG	TRG	TRG	TRG	TRG	TRG																							
Test	Group	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	SMETCL	VOACLP	VOACLP	VOACLP	VOACLP	VOACLP	VOACLP							
	QC Partner		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER		BU00017ER
20	Code	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP	REAL	DUP
Sample	Number	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER	BU00017ER	BU00018ER
	SSHI	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217	217

Table 4-3
Duplicate Sample Results and Relative Percent Differences

Sample	oc		Test	Result					Detection	Jetection Validation	
S. Number	Code	QC Partner	Group	Type	Compound	Result	Error	Result Error Qualifier Limit	Limit	Code	RPD
7 BU00017ER	REAL		VOACLP	TRG	TOTAL XYLENES	=			5	>	
217 BU00018ER	DUP	BU00017ER	VOACLP	TRG	TOTAL XYLENES	=			5	>	<b>%</b> 0 0
7 BU00017ER	REAL		WQPL	TRG	CYANIDE	142			5	λl	
217 BU00018ER	DUP	BU00017ER	WQPL	TRG	CYANIDE	171			5	Ν	18 5%
217 BU00017ER	REAL	WQPL DUP	WQPL	DUP	CYANIDE	8 66			2	7	-34 9%

Table 4-4
Equipment Rinsate Blank Sample Results

CCUI	Sample	QC Partner	Sample	Test	Compound	Kesult	Cnits	Error	Error Qualifier	Detection	Validation
i	Number		Date	Group						Limit	Code
178	BU00013ER		16-Aug-93	DRADS	PLUTONIUM-239/240	011	PCIAL	0 0 0 0	В	0 003	>
178	BU00013ER		16-Aug-93	DRADS	URANIUM-233,-234	99	PCIAL	0.35	В	0 061	A
178	BU00013ER		16-Aug-93	DRADS	URANIUM-238	7	PCIAL	0 36	В	0 036	Α
178	BU00013ER		16-Aug-93	VOACLP	TOTAL XYLENES	7	NG/L		~	\$	∢
179	BU00035ER	BU00033ER	15-Sep-93	BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	∞	NG/L		-	10	>
179	BU00035ER	BU00033LR	15-Sep-93	BNACLP	UNKNOWN TIC	\$	NG/U		-,		>
179	BU00035ER	BU00013LR	15-Sep-93	BNACLP	UNKNOWN TIC	73	NG/L		-		>
179	BU00035ER	BU00033ER	15-Sep-93	BNACLP	UNKNOWN TIC	9	NGV		_		>-
179	BU00035ER	BU00033ER	15-Sep-93	BNACLP	UNKNOWN TIC	42	NG/L		-		>
179	BU00035ER	BU00033ER	15-Sep-93	BNACLP	Unknown-1	5	NG/L		-		>-
179	BU00035ER	BU00033FR	15-Sep-93	BNACLP	Unknown-2	73	NG/L		-		>
179	BU00035FR	BU00011FR	15-Scp-93	BNACLP	Unknown-3	9	NG/J		_		<b>&gt;</b>
179	BU00035ER	BU000331 R	15-Sep-93	BNACLP	Unknown-4	42	NG/U		-		>
179	BU00035ER	BU000131 R	15-Sep-93	DRADS	GROSS ALPHA	0 58	PCI/L	0 26	-	0 28	>
179	BU00035ER	BU000331 R	15-Sep-93	DRADS	PLUTONIUM-239/240	0 002	PCI/L	0 002	~	0 001	>
179	BU00035ER	BU000331 R	15-Sep-93	DRADS	URANIUM-233,-234	0 65	PCIAL	0 42	В	0.054	¥
179	BU00035ER	BU000331 R	15-Sep-93	DRADS	URANIUM-235	0 065	PCI/L	0 13	BJ	0 054	V
621	BU00035ER	BU000131 R	15-Sep-93	DRADS	URANIUM-238	86 0	PCI/L	0 53	В	0 054	∢
180	BU00025FR	BU000231 R	01-Scp-93	BNAC1 P	UNKNOWN TIC	6	NGA		-		>
180	BU00025ER	BU000231 R	01-Sep-93	BNACLP	UNKNOWN TIC	9	NG/L		~		<b>&gt;</b>
081	BU00025ER	BU000231 R	01-Sep-93	BNACLP	UNKNOWN TIC	15	NGV		ī		<b>&gt;</b>
180	BU00025ER	BU000231 R	01-Sep-93	BNACLP	UNKNOWN TIC	180	$\Omega G \mathcal{N}$		ī		>
180	BU00025ER	BU00023LR	01-Sep-93	BNACLP	UNKNOWN TIC	01	NG/U		-		>
180	BU00025ER	BU000231 R	01-Sep-93	BNACLP	UNKNOWN TIC	7	NGV		ſ		>
180	BU00025ER	BU000231 R	01-Sep-93	BNACLP	Unknown-1	6	NGV		~		<b>&gt;</b>
081	BU00025LR	BU000231 R	01-Scp-93	BNACLP	Unknown-2	9	NG/J		ſ		<b>&gt;</b>
180	BU000251 R	BU000231 R	01-Sep-93	BNACLP	Unknown-3	15	NG/L		_		>
180	BU00025ER	BU00023LR	01-Sep-93	BNACLP	Unknown-4	180	NGV		ſ		<b>\</b>
180	BU00025ER	BU000231 R	01-Sep-93	BNACLP	Unknown-5	01	UG/J		_		<b>&gt;</b>
				8	` ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	1	(:		•		

Page 2 of 4

Table 4-4
Equipment Rinsate Blank Sample Results

SSHI	Sample	QC Partner	Sample	Test	Compound	Result	Unds	Error	Error Qualifier	Detection	Validation
	Number		Date	Group						Limit	Code
180	BU00025ER	BU00023ER	01-Sep-93	DRADS	AMERICIUM-241	800 0	PCI/L	0 008	'n	0 003	>
180	BU00025ER	BU00023ER	01-Sep-93	DRADS	URANIUM-233,-234	<i>L</i> 90	PCIAL	0 35	В	0 035	4
180	BU00025ER	BU00023ER	01-Sep-93	DRADS	URANIUM-238	13	PCI/L	0 20	В	0 035	∢
180	BU00025ER	BU00023ER	01-Sep-93	VOACLP	METHYLENE CHLORIDE	S	NG/L			\$	>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	17	NG/L			10	<b>&gt;</b> -
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	UNKNOWN TIC	6	NG/I		-		>
180	BU00029LR	BU000271 R	02-Sep-93	BNACLP	UNKNOWN TIC	9	UGA		ſ		>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	UNKNOWN TIC	21	$\Omega$ C/L		_		>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	UNKNOWN TIC	210	UG/L		ſ		<b>&gt;</b>
180	BU000291 R	BU000271 R	02-5cp-93	BNACLP	UNKNOWN TIC	12	NG/I		<u>,</u>		>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	UNKNOWN TIC	12	NG/L		ſ		<b>&gt;</b>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	Unknown-1	6	NG/L		_		>
180	BU000291 R	BU00027LR	02-5cp-93	BNACI P	Unknown-2	9	UG/J		_		>
180	BU00029ER	BU00027FR	02-Sep-93	BNACLP	Unknown-3	21	UG/L		~		<b>&gt;</b>
180	BU00029ER	BU00027ER	02-Sep-93	BNACI P	Unknown-4	210	NG/L		ь,		>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	Unknown-5	12	NGA		ſ		>
180	BU00029ER	BU00027ER	02-Sep-93	BNACLP	Unknown-6	12	NG/L		ſ		>
081	BU00029ER	BU00027ER	02-Sep-93	DRADS	AMERICIUM-241	0 003	PCI/L	0 004	7	0 001	>
081	BU00029ER	BU00027ER	02-Sep-93	DRADS	GROSS ALPHA	4 4	PCI/L	0 61		0.51	>
180	BU00029ER	BU00027ER	02-Sep-93	DRADS	GROSS BETA	7.5	PCIAL	2.0		2.5	>
180	BU00029ER	B1J00027FR	02-Sep-93	DRADS	URANIUM-233,-234	91	PCI/L	0 57	В	0 11	∢
180	BU00029ER	BU00027ER	02-Scp-93	DRADS	URANIUM-235	0 084	PCIAL	0 13	-	0 067	<
180	BU00029LR	BU00027ER	02-Sep-93	DRADS	URANIUM-238	32	PCIAL	0.85	В	190 0	∢
204	BU00042ER	BU00040LR	11-04-93	BNACLP	BIS(2-ETHYLHEXYI )PH111ALA11	91	NG/L			10	>
204	BU00042ER	BU00040ER	11-04-93	BNACLP	UNKNOWN TIC	\$	UGAL		~		7
204	BU00042ER	BU00040ER	11-04-93	BNACLP	UNKNOWN TIC	9	NG/L		•		7
204	BU00042LR	BU00040LR	11-04-93	BNACLP	UNKNOWN TIC	œ	NG/L		r		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	7	NG/L		_		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	8	UGAL		-		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	4	UGAL		ſ		2
204	BU00042LR	BU00040ER	11-04-93	BNACLP	UNKNOWN TIC	88	NGAL		-		2

Page 3 of 4

Table 4-4
Equipment Rinsate Blank Sample Results

SSHI	Sample	QC Partner	Sample	Test	Compound	Result	Units	Error Qualifier	1	Detection	Validation
	Number		Date	Group					•	Limit	Code
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	8	NG/L		_		Z
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	15	NG/L		-		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	12	NGAL		BJ		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	UNKNOWN TIC	5	NG/L		_		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-1	<b>∞</b>	NG/L		_		2
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-10	5	NG/L		-		2
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-11	9	NG/L		-		2
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-2	7	NG/L		r		2
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-3	<b>∞</b>	NG/L		ī		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-4	4	UGAL		<b>-</b>		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-5	68	NG/L		_		2
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-6	<b>&amp;</b>	NG/I		_		7
204	BU000421.R	BU00040LR	11-04-93	BNACI P	Unknown-7	15	UG/L		-		2
204	BU000421 R	BU00040ER	11-Oct-93	BNACI P	Unknown-8	12	NG/L		BJ		7
204	BU00042ER	BU00040ER	11-Oct-93	BNACLP	Unknown-9	5	NG/L		ſ		2
204	BU00042ER	BU00040ER	11-Oct-93	DRADS	GROSS ALPHA	09	PCIAL	8 -		_	>
204	BU00042ER	BU00040ER	11-Oct-93	DRADS	GROSS BETA	2.7	PCIAL	13	ſ	2	>
204	BU00042ER	B1J00040ER	11-Oct-93	DRADS	URANIUM-233,-234	66 0	PCI/L	0 35		0.2	>
204	BU00042ER	BU00040ER	11-Oct-93	DRADS	URANIUM-238	6.2	PCIAL	_		0.2	>
204	BU00049FR	B1J00047ER	09-Nov-93	BNACLP	BIS(2-ETHYLHEXYL)PHTHALA1F	5	UG/L		ſ	01	<
204	BU000049FR	BU000471 R	09-Nov-93	BNAC1 P	Hexadecanamide	24	UC/J		-		`
204	B1J00049LR	B1J00047ER	09-Nov-93	BNACLP	Unknown-1	17	NG/L		_		7
204	BU000491 R	B1000471 R	09-Nov-93	BNACLP	Unknown-2	<u>.</u>	NG/L		-		7
204	BU000491 R	B1000047ER	109-Nov-93	BNACLP	Unknown-3	250	ND()		_		2
204	BU00049ER	BU00047ER	09-Nov-93	BNACLP	Unknown-4	17	NG/L		_		2
204	BU00049ER	BU00047ER	09-Nov-93	BNACLP	Unknown-5	91	NG/L		,		7
204	BU000491.R	BU00047ER	09-Nov-93	BNACLP	Unknown-6	10	NG/L		-		7
204	BU <b>00</b> 049I R	BU00047ER	09-Nov-93	DRADS	URANIUM-238	89 0	PCIAL	0 29		0.2	<del>\</del>
211	BU000041 R		09-Aug-93	DMETADD	SILICON	223	NGA			100	Υſ
211	B1J000041 R		09-Aug-93	DMETADD	STRONTIUM	4.5	NG/L		В	200	>
211	BU000041 R		09-Aug-93	DRADS	AMERICIUM-241	600	PCI/IL	900 0	BJ	0 002	>

Table 4-4
Equipment Rinsate Blank Sample Results

tion Validation	nut Code	OO JA	00 JA	> 0	<b>A</b>	90 JA	O JA	<b>&gt;</b> 0.	01 V	42 A	YY .	OO JA	OO JA	> 0	>	> ;	> %	37 V	A 6	Υſ	> <	>	OO JA	۰ ۲	•
r Detec	Limit	2000	2000	Ā	δ,	01	10	20	0 001	00	ς,	20	2000	20	000	3	900 0	00	0 0	ζ)	7	S	2000	20	
Error Qualifier Detection		В	В	В	-	В	В	В	BJ	BJ		В	В	В	۵	<b>a</b>		ī	<u>-</u>		В		В	В	•
Error									0 004	010							0 012	0 15	0 15						
Units		UG/L	UG/L	NG/L	NG/J	NG/L	NG/L	NG/J	PCI/L	PCIAL	NG/L	NG/L	NG/L	NG/L	501	7000	PCM	PCI/L	PCI/L	UG/L	N <sub>D</sub> U	ΝDΩ	NG/L	NG/J	
Result		1140	272	2	4	43	70 4	26	900	150	64	652	264	6.4	<i>C</i> 7	\ \frac{1}{2}	0 030	0 13	0 12	16 3	64	136	310	8 2	•
Compound		CALCIUM	SODIUM	ZINC	METHYLENE CHLORIDE	CESIUM	SILICON	STRONTIUM	AMERICIUM-241	URANIUM-233,-234	CADMIUM	CALCIUM	SODIUM	ZINC	CTRONTH IA		AMERICIUM-241	URANIUM-233,-234	URANIUM-238	CADMIUM	COPPUR	11 AD	SODIUM	ZINC	
Test	Group	DSMETCLP	DSMETCLP	DSMETCLP	VOACLP	DMETADD	DMETADD	DMETADD	DRADS	DRADS	DSMETCLP	DSMETCLP	DSMLTCLP	DSMLTCLP	CICL TANG	Dent Line	DRADS	DRADS	DRADS	DSMLTCLP	DSMI FCLP	DSMI ICI P	DSMI ICLP	DSMETCLP	
Sample	Date	09-Aug-93	09-Aug-93	09-Aug-93	09-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	11-Aug-93	17 Ang 03	CC-9mV-11	17-Aug-93	17-Aug-93	17-Aug-93	17-Aug-93	17-Aug-93	17-Aug-93	17-Aug-93	17-Aug-93	
QC Partner																									
Sample	Number	BU00004ER	BU00004ER	BU00004ER	BU00004ER	BU00007ER	BU00007ER	BU00007ER	BU00007ER	BU00007ER	BU00007ER	BU00007ER	BU00007ER	BU00007FR	9100010E	וווווווווווווווווווווווווווווווווווווו	BU00019ER	BU00019ER	BU00019ER	BU00019ER	BU00019ER	BU00019I-R	BU00019ER	BU00019ER	000000000000000000000000000000000000000
IHSS		211	211	211	211	211	211	211	211	211	211	211	211	211	717	/ 17	217	217	217	217	217	217	217	217	

Table 4-5
Trip Blank Sample Results

SSHI	Sample Number	Sample Date	Test Group	Compound	Result (ug/l)	Error	Qualıfier	Detection Limit (ug/l)	Validation Code
180	BU00021ER	01-Sep-93	VOACLP	METHYLENE CHLORIDE	14			\$	>
204	BU00046ER	09-Nov-93	VOACLP	METHYLENE CHLORIDE	7		ſ	\$	∢
211	BU00005ER	09-Aug-93	VOACLP	METHY LENE CHLORIDE	7			\$	>
*	BU00052ER	27 Apr-94	DMETADD	LITHIUM	102		В		
	BU00052ER	27 Apr 94	DMETADD	STRONIUM	0.81		В		
	BU00052FR	27 Apr-94	DSMETCLP	ANIIMONY	306		8		
	BU00052ER	27 Apr-94	DSMETCLP	ARSENIC	8.2		8		
	BU00052ER	27 Apr-94	DSMFTCLP	BERYLI IUM	0 64		æ		
	BU00052LR	27 Apr 94	DSMETCI P	CADMIUM	176				
	BU00052FR	27 Apr-94	DSMETCLP	CALCIUM	54 4		B		
	BU00052FR	27 Apr-94	DSMETCLP	COPPLR	~		8		
	BU000521 R	27 Apr-94	DSMI FCI P	IRON	463		æ		
	BU00052f R	27 Apr 94	DSMLTCLP	LEAD	46				
	BU000521 R	27 Apr 94	DSMFTCLP	MAGNESIUM	46.5		В		
	BU000521 R	27 Apr-94	DSML1C1 P	POLASSIUM	510		8		
	BU000521 R	27 Apr 94	DSMETCI P	SEI FNIUM	19		В		
	BU000521 R	27 Apr 94	DSME ICI P	SILVER	4		В		
	BU00052LR	27 Apr-94	DSMETCI P	SODIUM	332		B		
	BU00052LR	27 Apr-94	DSMETCLP	VANADIUM	12.2		æ		
	131 10001521 R	27 Apr 94	DSMETCI P	ZINC	38		8		

\* Trip blank for hot water rinsate blank collection

Table 4-6 Field Blank (Source Water) Sample Results

SSHI	Sample	Sample	Test Group	Compound	Result	Qualifier	Detection	Validation
	Number	Date			(VBn)		Limit (ug/l)	Code
179	BU00032ER	15-Sep-93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	\$	ſ	10	*
211	BU00001ER	09-Aug-93	DMETADD	SILICON	3670		100	JA
211	BU00001ER	09-Aug-93	DMETADD	STRONTIUM	43 4	В	200	>
211	BU00001ER	09-Aug-93	DSMETCLP	BARIUM	15.5	В	200	>
211	BU00001ER	09 Aug 93	DSMETCLP	CADMIUM	108		\$	JA
211	BU00001ER	09-Aug-93	DSMETCLP	CALCIUM	8120		2000	JA
211	BU00001ER	09-Aug 93	DSMETCLP	СОРРЕЯ	129	В	25	>
211	BU00001ER	09-Aug-93	DSMETCLP	IRON	674		100	JA
211	BU00001FR	09 Aug 93	DSMETCI P	LEAD	8	В	8	>
211	BU00001I R	09 Aug 93	DSMETCLP	MAGNESIUM	1460	В	2000	Ρſ
211	BU00001ER	09 Aug 93	DSMETCLP	MANGANESE	8 7	В	15	γ
211	BU00001FR	09-Aug 93	DSMETCLP	SODIUM	6250		2000	ΡΥ
211	BU000011 R	09-Aug 93	DSMFICIP	/INC	2.5	В	20	>
180	BU000221 R	01 Sep 93	VOACLP	BROMODICHI OROME FHANL	7	~	\$	¥
204	BU00039ER	11 0a 93	VOACLP	BROMODICIILOROMETIIANE	33	ſ	\$	¥
211	BU00001LR	09-Aug 93	VOACLP	BROMODICHLOROMETHANE	4	-	\$	¥
		8-Mar 93	VOACLP	BROMODICHLOROMETHANE	9			
		8-Mar 93	VOACLP	BROMODICHI OROMETHANE	\$			
		14-1 ch 94	VOACLP	BROMODICHI OROMETHANE	4 4			
		14 Feb-94	VOACLP	BROMODICHLOROMETHANE	4 8			
		14 1 Jb-94	VOACI P	BROMODICHI OROMETHANE	4 4			
179	BU00032LR	15-Sup 93	VOACLP	CHLOROI ORM	100		•	>
180	BU00022FR	01-Sep 93	VOACLP	CHLOROFORM	120		\$	>
204	BU00039ER	11 Oct 93	VOACLP	CHLOROFORM	95		\$	>
211	BU00001ER	09-Aug-93	VOACLP	CHLOROFORM	180		\$	>
		16-Aug 93	VOACLP	CHLOROFORM	104			
		16-Aug 93	VOACLP	CHLOROFORM	116			
		16-Aug-93	VOACLP	CHLOROFORM	125			
		10-May 93	VOACLP	CHLOROFORM	36			
		10-May-93	VOACLP	CHLOROFORM	43			
		10-May-93	VOACLP	CHLOROFORM	48			


Table 4-6 Field Blank (Source Water) Sample Results

VOACLP         CHLOROFORM         44           VOACLP         CHLOROFORM         43           VOACLP         CHLOROFORM         43           VOACLP         CHLOROFORM         62           VOACLP         CHLOROFORM         43           VOACLP         CHLOROFORM         43           VOACLP         CHLOROFORM         30           VOACLP         CHLOROFORM         38           VOACLP         CHLOROFORM         30           VOACLP         CHLOROFORM         30		Limit (ugA)	Code
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROTORM CHLOROTORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM CHLOROFORM			
CHLOROFORM CHLOROFORM			
CHLOROFORM			
VOACLP CHLOROFORM 47			
VOACLP CHLOROFORM 40			
VOACLP CHLOROFORM 42			
VOACLP DIBROMOCHLOROMETHANE 03			
VOACLP DIBROMOCHLOROMETHANE 04			
VOACLP DIBROMOCHLOROMETHANE 02			
VOACLP METHYLENE CHLORIDE 21		\$	>
VOACLP METHYLENE CHLORIDE 3	ŗ	s	Ą
VOACLP TRICHLOROETHENE	7	s	¥
	IANE IANE	IANE IANE	IANE IANE

Table 4-7
Hot Water Runsate Blank Sample Results

Sample Number	Sample Date	Test Group	Compound	Result (ug/l)	Qualifier	Detection Limit (ug/l)	Validation Code
BU00053ER	27-Apr-94	BNACLP	BIS(2-ETHYLHE\YL)PHTHALATE	28			
BU00054ER	27-Apr-94	BNACLP	BIS(2-ETHYLHE\YL)PHTHALATE	19			
BU00055ER	27-Арг-94	BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	22			
BU00053ER	27-Apr-94	BNACLP	PHENOL	180	E		
BU00054ER	27-Apr-94	BNACLP	PHENOL	220	E		
BU00055ER	27-Арг-94	BNACLP	PHENOL	360	E		
BU00053ER	27-Apr-94	DMETADD	LITHIUM	67	В		
BU00053ER	27-Арг-94	DMETADD	SILICON	78 5	В		
BU00054ER	27-Арг-94	DMETADD	SILICON	89 5	В		
BU00055ER	27-Apr-94	DMETADD	SILICON	89 5	В		
BU00053ER	27-Арг-94	DMETADD	STRONTIUM	3 5	В		
BU00054ER	27-Apr-94	DMETADD	STRONTIUM	2 7	В		
BU00055ER	27-Apr-94	DMETADD	STRONTIUM	2 4	В		
BU00053ER	27-Арг-94	DSMETCLP	ARSENIC	16	В		
BU00054ER	27-Apr-94	DSMETCLP	ARSENIC	1.5	В		
BU00055ER	27-Apr-94	DSMETCLP	ARSENIC	16	В		
BU00053ER	27-Apr-94	DSMETCLP	BARIUM	2 7	В		
BU00055ER	27-Арг-94	DSMETCLP	BARIUM	3 4	В		
BU00053ER	27-Apr-94	DSMETCLP	BERYLLIUM	0 64	В		
BU00053ER	27-Apr-94	DSMETCLP	CADMIUM	2 2	В		
BU00054ER	27-Арг-94	DSMETCLP	CADMIUM	117	-		
BU00055ER	27-Apr-94	DSMETCLP	CADMIUM	5.4			
BU00053ER	27-Apr-94	DSMETCLP	CALCIUM	931	В		
BU00054ER	27-Apr-94	DSMETCLP	CALCIUM	854	В		
BU00055ER	27-Apr-94	DSMETCLP	CALCIUM	753	В		
BU00053ER	27 Apr-94	DSMETCLP	COPPER	24 8	В		
BU00054ER	27-Арг-94	DSMETCLP	COPPER	15.5	В		
BU00055ER	27-Apr-94	DSMETCLP	COPPER	22 7	В		
BU00053ER	27-Apr-94	DSMETCLP	IRON	123	В		
BU00054ER	27-Apr-94	DSMETCLP	IRON	94	В		
BU00055ER	27-Apr-94	DSMETCLP	IRON	12 1	В		
BU00053ER	27-Apr-94	DSMETCLP	LEAD	41			
BU00054ER	27-Apr-94	DSMETCLP	LEAD	5.5			
BU00055ER	27-Apr-94	DSMETCLP	LEAD	28	В		
BU00053ER	27-Apr-94	DSMETCLP	MAGNESIUM	79 9	В		
BU00055ER	27-Apr-94	DSMETCLP	MAGNESIUM	186	В		
BU00053ER	27-Apr-94 27-Apr-94	DSMETCLP	MANGANESE	5 2	В		
BU00054ER	27-Apr-94	DSMETCLP	MANGANESE	3 5	В		
BU00055ER	27-Apr-94 27-Apr-94	DSMETCLP	MANGANESE	28	В		
BU00053ER	27-Apr-94 27 Apr-94	DSMETCLP	POTASSIUM	1020	В		
BU00053ER BU00054ER	27 Apr-94 27-Apr-94	DSMETCLP	POTASSIUM	475	В		
BU00055ER	27-Арг-94 27-Арг-94	DSMETCLP	POTASSIUM	501	В		
BU00053ER	27-Apr-94 27-Apr-94	DSMETCLP	SODIUM	1370	В		
			SODIUM	965	В		
BU00054ER	27-Apr-94	DSMETCLE		963 961	В		
BU00055ER	27-Apr-94	DSMETCLE	SODIUM		ь		
BU00053ER	27 Apr-94	DSMETCLP	ZINC	104			
BU00054ER	27 Apr 94	DSMETCLP	ZINC	103			
BU00055ER	27-Apr 94	DSMETCLP	ZINC	133			

Section 5.0



Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM.01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page <sup>,</sup>	1 of 11

## 5.0 EVALUATION OF RCRA-REGULATED CONSTITUENTS

As described in Section 1 0, the evaluation of the data collected pursuant to the FSP for OU15 involved two distinct steps. The first step is an evaluation of the RCRA-regulated constituents as they relate to the closure performance standards within each IHSS, as well as an examination of the potential for releases from each IHSS. The potential for releases was addressed in Section 2.0. A comparison of the data collected for each IHSS for RCRA-regulated constituents to the appropriate performance standards is presented in this section.

# 5.1 Approach

This section presents the results of the Stage I and II field investigations for the six IHSSs which compose OU15. Only those individual constituents that were detected by the laboratory analysis of the hot water rinsate samples are reported in the sections below. The hot water rinsate sample results presented in this section are a combination of validated and unvalidated data, since the validation process has not yet been completed for all the OU15 samples.

The approach taken in this section to evaluate the existing database against the specified RCRA closure performance standards involved comparing the results of chemical analyses of the hot water rinsate samples against the specific closure performance standards. The performance standards are described below, followed by a description of the rationale followed in comparing the analytical data to those standards.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page	2 of 11

#### 5.1.1 Data Evaluation

The data evaluated in this section included only those chemical results for RCRA-regulated constituents (i.e., constituents listed in 6 CCR 1007-3 Part 261 Appendix VIII) In addition, only positively detected results were included in the analysis. Various fields in the RFEDS database were examined to define positively detected results. The selection criteria includes

- Only results for RCRA-regulated constituents were evaluated in this section All results for radionuclide analyses were evaluated separately in Section 6.0
- Results qualified with a "U," indicating that the compound was not detected above the instrument detection limit in the sample, were eliminated from further consideration
- Results for organic compounds qualified with a "B," indicating that the compound was detected in a blank sample at a similar concentration, were considered laboratory artifacts and eliminated from further consideration
- Only results with a QC CODE of "REAL" or "DUP" were included Other QC CODE values indicate blank samples or other quality assurance samples
- Only results with a RESULT TYPE of "TRG," "DL1," or "DIL" were evaluated Other RESULT TYPE codes indicate non-target parameters such as tentatively identified compounds and unknowns
- Results reported in units of percent (%) indicate matrix spike compounds added to a sample by the laboratory for quality assurance purposes. These records were not considered further
- Results with a qualifier code of "J" for organics or "B" for inorganics were not included since these qualifiers indicate that the reported concentration is an estimate below the CRQL
- All data manually collected (1 e, smear sample results and dose-rate survey results) were included for further evaluation. These results were evaluated separately in Section 6 0.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page	3 of 11

The remaining results were included in the RCRA evaluation. It must be noted that at the time of publication, the validation process had not been completed by RFEDS. A fully validated data set will be provided in the Phase I RFI/RI Report

### 5.1.2 RCRA Closure Performance Standards

This section describes the closure performance standards required by the State RCRA Permit issued October 30, 1991 for RFP The standards require the following

- a Close the hazardous and mixed waste units in a manner that minimizes the need for further maintenance and controls, minimizes or eliminates the threat to human health and the environment, and minimizes or eliminates the post-closure escape of hazardous waste, hazardous waste constituents, leachate, contaminated rainfall, or waste decomposition products to the ground, surface waters, or the atmosphere
- b The closure performance standard for used rinsate from decontamination of concrete secondary containment areas shall be as follow
  - (1) There must be no detectable levels of hazardous organic constituents,
  - (2) It must not exhibit any characteristic of a hazardous waste as defined in 6 CCR 1007-3 Part 261, Subpart C, and
  - (3) The levels of Toxicity Characteristic (TC) metals must be at or below the background level in the unused rinsate solution
- c Parameter selection for the used rinsate analysis will be based on the specific wastes stored at the unit. These wastes are specified in Part III of the State RCRA permit

At the request of CDH, the OU15 IHSSs will also meet the above closure performance standards. The RCRA-regulated constituents of regulatory concern were defined for each

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	5 0, Final
Inside Building Closures	Page	4 of 11

IHSS in the Work Plan, and are as follows

- IHSS 178 radionuclides, Freon TF, and 1,1,1-trichloroethane
- IHSS 179 radionuclides, chlorinated solvents, beryllium, Freon TF, 1,1,1-trichloroethane, and carbon dioxide
- IHSS 180 uranium, radionuclides, beryllium, Freon TF, 1,1,1-trichloroethane, and carbon dioxide
- IHSS 204 uranium, solvents, Freon TF, and 1,1,1-trichloroethane
- IHSS 211 radionuclides, carbon tetrachloride, acetone, methyl alcohol, butyl alcohol, and various TAL metals
- IHSS 217 aqueous cyanide solutions (other contaminants, excluding pesticides and PCBs are possible)

These lists of compounds for each IHSS are used in the evaluations below to support the analysis of RCRA-regulated substances at each IHSS

#### 5.2 IHSS 178

Table 5-1 shows the results of hot water rinsate sampling performed in IHSS 178. The table shows only those compounds positively identified and detected at or above the method detection limit within IHSS 178. Of the five compounds detected, only DEHP, butyl benzyl phthalate, and phenol are RCRA Appendix VIII compounds and are therefore of concern for the RCRA closure of IHSS 178.

DEHP was detected in hot water rinsate blank samples at concentrations up to  $28 \mu g/l$  DEHP was detected at IHSS 178 in sample number BU00011ER, and its duplicate BU00012ER, at 140  $\mu g/l$  and 160  $\mu g/l$ , respectively. These concentrations are less than one order of magnitude greater than the blank concentration. RAGS Part A (EPA, 1989) indicates that, for common cross-contaminants such as DEHP, concentrations within one

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	5 0, Final
Inside Building Closures	Page	5 of 11

order of magnitude of a blank concentration can be attributed to cross-contamination. Therefore, the DEHP concentrations have been attributed to leaching from plastic components in the sample collection equipment.

Butyl benzyl phthalate is most commonly used in flooring materials and polyvinyl chloride (PVC). Although not specifically detected in the hot water rinsate blank samples, this and other phthalates are commonly leached from paints, plastics, and flooring materials. Butyl benzyl phthalate was detected in hot water rinsate samples from IHSSs 178, 211, and 217. These detections are attributed to plastics in the sampling equipment and in flooring materials, and are therefore assumed not to be present as RCRA waste materials at IHSS 178. Furthermore, the list of RCRA-regulated constituents of regulatory concern at IHSS 178, given in Section 5.1.2, does not include phthalates in general, nor butyl benzyl phthalate specifically

Phenol was detected in the hot water rinsate blank samples at concentrations up to 380  $\mu$ g/l. Therefore, the phenol detections of 45  $\mu$ g/l and 65  $\mu$ g/l at IHSS 178 are attributed to the hot water rinsate sampling equipment

Since no releases were identified in the historical records or visual inspection reports for IHSS 178, and no RCRA-regulated constituents of regulatory concern were identified in the IHSS sampling, perimeter and pathway sampling results are not presented. No verification sampling or Stage III sampling is recommended for IHSS 178

### 5.3 IHSS 179

Table 5-2 shows the results of hot water rinsate sampling performed in IHSS 179 Two compounds were detected, both RCRA Appendix VIII compounds These were DEHP and phenol

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page	6 of 11

DEHP was detected in hot water rinsate blank samples at concentrations up to  $28 \mu g/l$  DEHP was detected at IHSS 179 in sample number BU00036ER at 220  $\mu g/l$  This concentration is less than one order of magnitude greater than the blank concentration and is therefore attributed to leaching from plastic components in the sample collection equipment

Phenol was detected in the hot water rinsate blank samples at concentrations up to 380  $\mu$ g/l. Therefore, the phenol detection of 53  $\mu$ g/l at IHSS 179 is attributed to the hot water rinsate sampling equipment

Since no releases were identified in the historical records or visual inspection reports for IHSS 179, and no RCRA-regulated constituents of regulatory concern were identified in the IHSS sampling, perimeter and pathway sampling results are not presented. No verification sampling or Stage III sampling is recommended for IHSS 179.

#### 5.4 IHSS 180

Table 5-3 shows the results of hot water rinsate sampling performed in IHSS 180 Three compounds were detected, all RCRA Appendix VIII compounds These were DEHP, phenol, and methylene chloride

DEHP was detected in hot water rinsate blank samples at concentrations up to  $28 \mu g/l$  DEHP was detected at IHSS 180 in sample number BU00023ER and its duplicate BU00024ER at 150  $\mu g/l$  and 190  $\mu g/l$ , respectively. These concentrations are less than one order of magnitude greater than the blank concentration and are therefore attributed to leaching from plastic components in the sample collection equipment

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page	7 of 11

Phenol was detected in the hot water rinsate blank samples at concentrations up to 380  $\mu$ g/l. Therefore, the phenol detections of 47  $\mu$ g/l (in both the real sample and its duplicate) at IHSS 180 are attributed to the hot water rinsate sampling equipment

Methylene chloride was detected in source water (field blank) samples at concentrations up to 21  $\mu$ g/l. It was also detected in the trip blanks for IHSSs 180, 204, and 211 at concentrations up to 14  $\mu$ g/l. Therefore, the presence of methylene chloride in sample number BU00023ER and its duplicate BU00024ER at 27  $\mu$ g/l and 21  $\mu$ g/l, respectively, is attributed to the source water

Since no releases were identified in the historical records or visual inspection reports for IHSS 180, and no RCRA-regulated constituents of regulatory concern were identified in the IHSS sampling, perimeter and pathway sampling results are not presented. No verification sampling or Stage III sampling is recommended for IHSS 180.

#### 5.5 IHSS 204

Table 5-4 shows the results of hot water rinsate sampling performed in IHSS 204 Five compounds were detected, three of which are RCRA Appendix VIII compounds These were DEHP, di-n-octyl phthalate, and phenol

Based on the listing of RCRA-regulated constituents of regulatory concern at IHSS 204 (a RCRA treatment unit) given in Section 5 1 2, only VOCs, such as solvents and coolants from uranium machining, are of regulatory concern and are therefore subject to evaluation in this section. No VOCs or coolants were detected at IHSS 204

Since no releases were identified in the historical records or visual inspection reports for IHSS 204, and no RCRA-regulated constituents of regulatory concern were identified in

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	50, Final
Inside Building Closures	Page	8 of 11

the IHSS sampling, perimeter and pathway sampling results are not presented. No verification sampling or Stage III sampling is recommended for IHSS 204

#### 5.6 IHSS 211

Table 5-5 shows the results of hot water rinsate sampling performed in IHSS 211 Six organic compounds and nine inorganic compounds were detected. Two of the organic compounds (butyl benzyl phthalate and phenol) and two of the inorganic compounds (cadmium and lead) are RCRA Appendix VIII compounds

Butyl benzyl phthalate is most commonly used in flooring materials and PVC. Although not specifically detected in the hot water rinsate blank samples, this and other phthalates are commonly leached from paints, plastics, and flooring materials. Butyl benzyl phthalate was detected in hot water rinsate samples from IHSSs 178, 211, and 217. These detections are attributed to plastics in the sampling equipment and in flooring materials, and are therefore assumed not to be present as RCRA waste materials at IHSS 211. Furthermore, the list of RCRA-regulated constituents of regulatory concern at IHSS 211, given in Section 5.1.2, does not include phthalates in general, nor butyl benzyl phthalate specifically

Phenol was detected in the hot water rinsate blank samples at concentrations up to 380  $\mu$ g/l. Therefore, the phenol detections of 170  $\mu$ g/l and 160  $\mu$ g/l at IHSS 211 are attributed to the hot water rinsate sampling equipment

Cadmium was detected in sample number BU00002ER at 17  $\mu$ g/l. The duplicate of this sample (BU00003ER) reported cadmium as "non-detect". The detection limit in the real and duplicate samples was 5  $\mu$ g/l. Cadmium was detected in one source water sample for IHSS 211 at 10 8  $\mu$ g/l. It was also reported in a trip blank at 17 6  $\mu$ g/l, in hot water rinsate blanks at concentrations ranging from 2.2  $\mu$ g/l to 11.7  $\mu$ g/l, and in equipment

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	5 0, Final
Inside Building Closures	Page	9 of 11

rinse blanks at 6 4  $\mu$ g/l and 16 3  $\mu$ g/l Therefore, the presence of cadmium in hot water rinsate samples taken from IHSS 211 is attributed to the source water

Lead was detected in sample number BU00002ER and its duplicate BU00003ER at concentrations of 9 1 and 4 4  $\mu$ g/l, respectively. Lead was detected in the source water sample from IHSS 211 at 1 8  $\mu$ g/l. Lead was also detected in the IHSS 211 trip blank at 4 6  $\mu$ g/l, in the hot water rinsate blank samples at concentrations ranging from 2 8  $\mu$ g/l to 5 5  $\mu$ g/l, and in the equipment rinse blank samples from IHSS 217 at 13 6  $\mu$ g/l. Therefore, the lead concentrations detected in hot water rinsate samples taken at IHSS 211 are attributed to source water

Since no releases were identified in the historical records or visual inspection reports for IHSS 211, and no RCRA-regulated constituents of regulatory concern were identified in the IHSS sampling, perimeter and pathway sampling results are not presented. No verification sampling or Stage III sampling is recommended for IHSS 211

#### 5.7 IHSS 217

Table 5-6 shows the results of hot water rinsate sampling performed in IHSS 217 Six organic compounds and eighteen inorganic compounds were detected. Four of the organic compounds (DEHP,butyl benzyl phthalate, phenol, and chloroform) and seven of the inorganic compounds (beryllium, cadmium, chromium, mercury, nickel, silver, and cyanide) are RCRA Appendix VIII compounds

Based on the listing of RCRA-regulated constituents of regulatory concern at IHSS 217 (a RCRA treatment unit), only cyanide is of regulatory concern and is therefore subject to evaluation in this section. Cyanide was detected in sample number BU00017ER and it's duplicate at  $142 \mu g/l$  and  $171 \mu g/l$ . Verification sampling will need to be conducted for cyanide at IHSS 217. Cyanide was not detected in the sample from the IHSS 217.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	5 0, Final
Inside Building Closures	Page	10 of 11

perimeter area (the floor adjacent to the laboratory table and hood), therefore, no Stage III sampling is recommended for IHSS 217

# 5.8 Summary of RCRA Evaluation

The analyses of hot water rinsate samples presented above for each IHSS indicated that only IHSS 217 showed the presence of a RCRA-regulated constituent of regulatory concern attributable to the IHSS. The hot water rinsate samples collected at IHSS 217 showed positively identified detectable levels of cyanide. The presence of cyanide could not be attributed to any other source.

Several of the other IHSSs showed the presence of phthalates DEHP was positively identified in hot water rinsate blank samples. All of the phthalates detected are commonly associated with leaching from paints, plastics, and flooring material. None of the phthalates was identified as a RCRA-regulated constituent of regulatory concern at any IHSS. Therefore, the presence of phthalates was attributed to leaching from the plastic components of the sampling equipment and to leaching from flooring materials and paints.

Phenol was detected at several IHSSs, but was also identified in the hot water rinsate blank samples. Therefore, the presence of phenol was attributed to the sampling equipment. Methylene chloride was detected at one IHSS, but was also detected in trip blanks and source water (field blank) samples, and was therefore attributed to cross-contamination. Finally, a few metals were detected in hot water rinsate from IHSS 211. However, these metals were also present at similar concentrations in the source water (field blank samples). Therefore, the presence of these metals was attributed to their presence in the source water used for the hot water rinsate sampling.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	5 0, Final
Inside Building Closures	Page	11 of 11

The visual inspections and review of historical records for all IHSSs did not reveal any evidence of spills or releases from any IHSS which might have caused exterior or outdoor contamination. Therefore, no Stage III investigation is recommended

Based on the results of this analysis, verification sampling to confirm or deny the presence of cyanide is recommended for IHSS 217 No other verification sampling or Stage III investigation is recommended at this time

Table 5-1
Organic Compounds Detected in IHSS Hot Water Rinsate Samples
IHSS 178

Building	SSHI	Location	Sample Number	Sample Date	Test Group	Compound	Result (ug/l)	Qualifier	Detection Limit (ug/l)	n Validation Code	QC Code	QC Pariner	Appendix VIII Compound?
881	178	HSS	BU00011ER	16-Aug 93	BNACLP	BENZOIC ACID	89		S	Ąſ	REAL		
881	178	IHSS	BU00011ER	16-Aug 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	140		10	Υſ	REAL		YES
881	178	IHSS	BU00011ER	16-Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	38		10	Υſ	REAL		YES
881	178	IHSS	BU00011ER	16-Aug 93	BNACLP	DI-n-BUTYL PHTHALATE	13		10	>	REAL		
881	178	IHSS	BU00011ER	16-Aug 93	BNACLP	PHENOL	45		01	>	REAL		YES
881	178	IHSS	BU00012ER	16-Aug 93	BNACLP	BENZOIC ACID	۶		8	Αſ	DOP	BU00011ER	
188	178	IHSS	BU00012ER	16-Aug 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	991		10	Υſ	DO	BUOOOLIER	YES
188	178	IHSS	BU00012ER	16-Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	21		10	Υſ	DO	BU00011ER	YES
881	178	IHSS	BU00012ER	16-Aug 93	BNACLP	DI n-BUTYL PHTHALATE	11		10	>	DG DG	BU00011ER	
881	178	IHSS	BU00012ER	16-Aug 93	BNACLP	PHENOL	\$9		01	>	DUP	BU00011ER	YES

Page 1 of 1

Table 5-2
Organic Compounds Detected in IHSS Hot Water Ruisate Samples
IHSS 179

- 1	

Appendix VIII Compound?	YES
QC Code QC Partner	
	REAL REAL
Validation Code	¥
Detection Limit (ug/l)	<b>10</b>
Qualifier	
Result (ug/l)	220 53
Compound	ВІS(2 ЕТНҮІ.НЕХҮІ.)РНТНАІ.АТЕ РНЕNOL
Test Group	BNACLP
Sample Date	15 Sep 93 15 Sep-93
Sample Number	BU00036ER BU00036ER
Location	IHSS
SSIII	179
Building	865 865

Table 5-3
Organic Compounds Detected in IHSS Hot Water Rinsate Samples IHSS 180

Appendix VIII Compound?	YES	YES	YES	YES	YES	YES
QC Pariner				BU00023ER	BU00023ER	BU00023ER
QC Code	REAL	REAL	REAL	DUP	DO	DOP
n Validation Code	Α.	<b>,</b>	>	*	٨	>
Detection Limit (ug/l)	10	10	2	10	10	S
Qualifier				ш		
Result (ug/l)	150	41	27	8	47	21
Compound	BIS(2 ETHYLHEXYL)PHTHALATE	PHENOL	METHYLENE CHLORIDE	BIS(2 ETHYLHEXYL)PHTHALATE	PHENOL	METHYLENE CHLORIDE
Test Group	BNACLP	BNACLP	VOACLP	BNACLP	BNACLP	VOACLP
Sample Date	01 Sep-93	01-Sep-93	01 Sep-93	01 Sep-93	01 Sep-93	01 Sep-93
Sample Number	BU00023ER	BU00023ER	BU00023ER	BU00024ER	BU00024ER	BU00024ER
Location	IHSS	IHSS	IHSS	IHSS	IHSS	IHSS
SSHI	081	180	180	180	180	180
Building	883	883	883	883	883	883

Page 1 of 1

Table 5-4
Organic Compounds Detected in Hot Water Rinsate Samples
IHSS 204

Building	SSIII	Building IHSS Location	Sample Number	Sample Date Test Group Compound	Test Group	Compound	Result (ug/t)	Qualifier	Detection Validation Limit (ug/t) Code	Validation Code	QC Code	QC Partner	Appendix VIII Compound?
447	204	Room 502	BU00044ER	11-0ct 93	BNACLP	BIS(2-ETHYLHEXYL)PHTHALATE	280	3	01	7	REAL		Yes
447	204	Room 502	BU00044ER	11 Oct 93	BNACLP	DI n-OCTYL PHTHALATE	13		01	>	REAL		Yes
447	204	Room 502	BU00044ER	11 Oct 93	BNACLP	PHENOL	23		01	>	REAL		Yes
447	707	Inlet	BU00045ER	11 Oct 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	230	ш	10	2	REAL		Yes
447	204	Inlet	BU00045ER	11 Oct 93	BNACLP	DI n-OCTYL PHTHALATE	78		01	>	REAL		Yes
447	204	Inlet	BU00045ER	11 Oct 93	BNACLP	PHENOL	86		10	>	REAL		Yes
447	204	Room 32	BU00050ER	09 Nov-93	BNACLP	BENZOIC ACID	091	щ	20	∢	REAL		
447	704	Room 32	BU00050ER	09 Nov-93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	99		01	>	REAL		Yes
447	<b>3</b> 5	Room 32	BU00050ER	09 Nov 93	BNACLP	DI n-OCTYL PHTHALATE	91		92	>	REAL		Yes
447	204	Room 32	BU00050ER	09 Nov 93	BNACLP	PHENOL	28		0	>	REAL		Yes
447	704	Outlet	BU00051ER	09 Nov 93	BNACLP	2 NITROPHENOL	13		01	>	REAL		
447	<b>70</b>	Outlet	BU00051ER	09 Nov 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	23		01	>	REAL		Yes
447	204	Outlet	BU00051ER	09 Nov 93	BNACLP	DI n-OCTYL PHTHALATE	43		01	>	REAL		Yes
447	204	Outlet	BU00051ER	09 Nov 93	BNACLP	PHENOL	044	ய	10	2	REAL		Yes

Table 5-5
Organic and Inorganic Compounds Detected in IHSS Hot Water Ruisate Samples IHSS 211

Building IHSS Location	SSHI	Location	Sample Number	Sample Date	Test Group	Compound	Result (ugA)	Qualifier	Detection Limit (ug/l)	Validation Code	QC Code QC Partner* Appendix VIII	Appendix VIII Compound?
883	211	IHSS	BU00002ER	09 Aug 93	BNACLP	2 METHYLPHENOL	017		01	>	REAL.	
881	211	HSS	BU00002ER	09 Aug 93	BNACLP	BENZOIC ACID	270	Ħ	20	2	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	BNACLP	BENZYL ALCOHOL	10		10	>	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	54		10	Υſ	REAL	YES
881	211	IHSS	BU00002ER	09 Aug 93	BNACLP	PHENOL	170	ш	10	2	REAL	XES
881	211	IHSS	BU00002ER	09 Aug 93	DMETADD	SILICON	9250		100	Ąſ	REAL	1
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	CADMIUM	11		S	Ϋ́	REAL	YES
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	CALCIUM	37400		2000	Ϋ́	REAL	}
881	211	HSS	BU00002ER	09 Aug 93	DSMETCLP	COPPER	34 4		25	>	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	IRON	135		100	Υſ	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	LEAD	91		\$	>	REAL	YES
188	211	HSS	BU00002ER	09 Aug 93	DSMETCLP	POTASSIUM	25600		2000	>	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	SODIUM	53900		2000	Ąſ	REAL	
881	211	IHSS	BU00002ER	09 Aug 93	DSMETCLP	ZINC	40 5		70	>	REAL	
881	211	HSS	BU00002ER	09 Aug 93	VOACLP	TOTAL XYLENES	6		\$	>	REAL	
188	211	IHSS	BU00003ER	09 Aug 93	BNACLP	2 METHYLPHENOL	120		10	>	DUP BU00002ER	
881	211	IHSS	BU00003ER	09 Aug 93	BNACLP	BENZOIC ACID	230	ш	20	2		
881	211	DHSS	BU00003ER	09 Aug 93	BNACLP	BENZYL ALCOHOL	=		10	>		
881	211	HSS	BU00003ER	09 Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	25		10	Ŋ		YES
881	211	IHSS	BU00003ER	09 Aug 93	BNACLP	PHENOL	160	ப	10	2	DUP BU00002ER	YES
881	211	IHSS	BU00003ER	09 Aug 93	DMETADD	SII ICON	8510		100	٧	DUP BU00002ER	
188	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	CALCIUM	39400		2000	Ąſ	DUP BU00002ER	
881	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	COPPER	30 1		25	>		
881	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	LEAD	4 4		5	>		YES
881	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	POTASSIUM	24400		2000	>		
881	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	SODIUM	53700		2000	Υſ		
1881	211	IHSS	BU00003ER	09 Aug 93	DSMETCLP	ZINC	323		20	>		
881	211	IHSS	BU00003ER	09 Aug 93	VOACLP	TOTAL XYLENES	81		\$	>		

The data for IHSS 211 QC Partner samples was not input into RFEDS but has been manually entered here.

R 30502\techmem revtables vis\217015S \LS

Table 5-6
Organic and Inorganic Compounds Detected in IHSS Hot Water Rinsate Samples IHSS 217

	HSS HSS HSS HSS HSS HSS				Compound	(ng/l)	Vudujier Limit	Lımıd (ug/l)	Code		Ko conte	Compound?
	HSS HSS HSS HSS HSS	BU00017ER	17 Aug 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	53		01	Ąſ	REAL		YES
	HSS HSS HSS HSS	BU00017ER	17 Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	21		10	Αſ	REAL		YES
	HSS HSS HISS	BU00017ER	17 Aug 93	BNACLP	PHENOL	38		01	>	REAL		YES
	HSS HISS	BU00017ER	17 Aug 93	DMETADD	LITHIUM	256	-	92	>	REAL		
	HISS	BU00017ER	17 Aug 93	DMETADD	SITICON	3630	-	901	Υſ	REAL		
	1	BU00017ER	17 Aug 93	DSMETCLP	BERYLLIUM	12		5	Υſ	REAL		YES
	HSS	BU00017ER	17 Aug 93	DSMETCI P	CADMIUM	758		5	٧ſ	REAL		YES
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	CALCIUM	42300	ズ	2000	γſ	REAL		
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	CHROMIUM	37.5		10	>	REAL		YES
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	COBALT	72.2		90	>	REAL.		
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	COPPER	281		25	>	<b>REAL</b>		
	HSS	BU00017ER	17 Aug 93	DSMETCLP	IRON	143	-	100	γſ	REAL		
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	MAGNESIUM	14000	3	2000	Υſ	REAL		
	HSS	BU00017ER	17 Aug 93	DSMETCLP	MANGANESE	1200		15	>	REAL		
881 217	HSS	BU00017ER	17 Aug 93	DSMETCLP	MERCURY	16		7	>	REAL		YES
881 217	IHSS	BU00017ER	17 Aug 93	DSMETCLP	NICKEL	5630	•	40	>	REAL		YES
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	POTASSIUM	5270	ぶ	2000	^	REAL		
	IHSS	BU00017ER	17 Aug 93	DSMETCLP	SILVER	22 1		10	>	REAL		YES
881 217	HSS	BU00017ER	17 Aug 93	DSMETCLP	SODIUM	17400	<i>x</i>	2000	Υſ	REAL		
	HSS	BU00017ER	17 Aug 93	DSMETCLP	ZINC	986	•	20	>	REAL		
	HSS	BU0001 7ER	17 Aug 93	VOACLP	4 METHYL 2 PENTANONE	26		01	>	RFAI		
	IHSS	BU00017ER	17 Aug 93	VOACLP	CHLOROFORM	s,		\$	>	REAL		YES
	HSS	BU00017ER	17 Aug 93	VOACLP	TOTAL XYLENES	=		2	>	REAL		
881 217	IHSS	BU0001 7ER	17 Aug 93	WQPL	CYANIDE	142		2	Ν	REAL		YES
881 217	IHSS	BU00018ER	17 Aug 93	BNACLP	BIS(2 ETHYLHEXYL)PHTHALATE	53		01	Υſ	DUP	BU00017ER	YES
881 217	SSHI	BU00018ER	17 Aug 93	BNACLP	BUTYL BENZYL PHTHALATE	23	-	10	Υſ	DO	BU00017ER	YES
	IHSS	BU00018FR	17 Aug 93	BNACLP	PHENOL	<u>«</u>	-	01	>	DUP	BU00017ER	YES
881 217	HSS	BU00018ER	17 Aug 93	DMETADD	LITHIUM	247		200	>	DUP	BU00017ER	
	IHSS	BU00018ER	17 Aug 93	DMETADD	SILICON	3690	-	901	Υſ	DOL	BU00017ER	
	IHSS	BU00018ER	17 Aug 93	DSMETCLP	BERYLLIUM	74		\$	γſ	DOP	BU00017ER	YES
	IHSS	BU00018ER	17 Aug 93	DSMETCLP	САДМИЛМ	73.5		\$	Υſ	DUP	BU00017ER	YES
	DHSS	BU00018ER	17 Aug 93	DSMETCLP	CALCIUM	42700	<b>У</b>	2000	Υſ	DUP	BU00017ER	
	IHSS	BU00018ER	17 Aug 93	DSMETCLP	CHROMIUM	369	•	90	>	DOP	BU00017ER	YES
	IHSS	BU00018ER	17 Aug 93	DSMETCL.P	COBALT	619	•	50	>	DO	BU00017ER	
	IHSS	BU00018ER	17 Aug 93	DSMETCLP	COPPER	287	- •	25	>	DOL	BU00017FR	
881 217	IHSS	BU00018ER	17 Aug 93	DSMETCLP	IRON	131	-	901	Υſ	DO	BU00017ER	
881 217	IHSS	BU00018ER	17 Aug 93	DSMETCLP	MAGNESIUM	14200	**	2000	Υſ	DO	BU00017ER	
	DHSS	BU00018ER	17 Aug 93	DSMETCLP	MANGANESE	1200	•	15	>	DO	BU00017ER	
881 217	HSS	BU00018ER	17 Aug 93	DSMETCLP	MERCURY	1.1		7	>	DO	BU00017ER	YES

Table 5-6
Organic and Inorganic Compounds Detected in IHSS Hot Water Ruisate Samples
IHSS 217

Appendix VIII Compound?	YES		YES				YES		YES
QC Code QC Partner	BU00017ER	BU00017ER	BU00017ER	BU00017ER	BU00017ER	BU00017ER	BU00017ER	BU00017ER	BU00017ER
QC Code	DUP	DO	DUP	DOP	DOP	DUP	DUP	DO	DOL
Validation Code	^	>	>	Αſ	>	>	>	>	٧ſ
Detection Limit (ug/l)	40	2000	10	2000	20	10	\$	\$	5
Qualifier									
Result (ug/l)	5670	5140	21 3	16600	1020	28	s	Ξ	171
Сотроипа	NICKEL	POTASSIUM	SILVER	SODIUM	ZINC	4 METHYL 2 PENTANONE	CHLOROFORM	TOTAL XYLENES	CYANIDE
Test Group	DSMETCLP	DSMETCLP	DSMETCLP	DSMETCLP	DSMETCLP	VOACLP	VOACLP	VOACLP	WQPL
Sample Date	17 Aug 93	17 Aug 93	17 Aug 93	17 Aug 93					
Sample Number	BU00018ER	BU00018ER	BU00018ER	BU00018ER	BU00018ER	BU00018ER	BU00018ER	BU00018ER	BU00018ER
IIISS Location	IHSS	HSS	IHSS	IHSS	IHSS	IHSS	BISS	IIISS	HSS
IIISS	217	217	217	217	217	217	217	217	217
Building	881	188	188	881	881	881	188	881	881

Section 60

...

the same of the sa

£9/# 3.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	1 of 16

### 6.0 CERCLA EVALUATION

This section presents the decision process used for each IHSS to determine the need for further action with respect to radionuclides and beryllium. Section 6.1 describes the approach taken to evaluating radionuclide and beryllium data. Sections 6.2 through 6.7 present the decision process applied to each IHSS. Section 6.8 provides a summary of the decision process for all IHSSs.

## 6.1 Approach

To determine whether any of the IHSSs require additional CERCLA evaluation prior to closure, the radionuclide data collected during the Stage I and II field investigations were evaluated using dose-estimation methods. If the estimated doses from radionuclides present within an IHSS fell below the appropriate regulatory criteria, then no further action was recommended, and the IHSS was considered suitable for closure

Beryllium data were addressed in a different manner to allow for consistency with RFP beryllium control procedures and ongoing building reuse and Decontamination and Decommissioning (D&D) efforts. The results of the beryllium smear samples are presented for IHSSs 179 and 180 in Sections 6.3 and 6.4, respectively. Conclusions as to the need for further action with regard to beryllium contamination are presented in Section 6.8.

#### 6.1.1 Radionuclide Data Evaluation

This section discusses the data which will be used to evaluate radionuclides at each of the six IHSSs. The specific data are presented in data tables for each IHSS in Sections 6.2 through 6.7. The radiological data collected during the Stage I and II field work included the following

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	2 of 16

- fixed alpha and beta radiation surveys,
- beta and gamma dose-rate data, expressed as millirems of radiation exposure per unit of time,
- gross alpha and beta counts for smear samples, expressed as radiological activity per unit area, and
- radionuclide-specific data for hot water rinsate samples, expressed as radiological activity per unit volume (these were converted to a unit area basis consistent with the smear sampling data as described below)

The fixed alpha and beta radiation surveys will not be evaluated further. Due to the high detection limits of the instruments used, and the variability of the results, these data are not of the appropriate quality for a dose analysis. For alpha radiation, only the removable portion of the total radiation is important, because alpha radiation is only a health concern via ingestion or inhalation. External alpha radiation will not generally penetrate even the outer layers of skin. For beta radiation, the removable portion is characterized by the beta smear samples, while the external irradiation component from fixed beta radiation is characterized by the beta dose-rate surveys. The data provided by the removable alpha and beta smear samples, and the beta and gamma dose-rate surveys are of higher quality, and are sufficient to complete the radiological analysis of each IHSS. Therefore, the fixed radiation surveys are not required to complete the objectives of the analysis.

The radionuclides which were evaluated for OU15 included all those positively identified at OU15. The radionuclides detected were Americium-241 (Am-241), Radium-226 (Ra-226), Plutonium-239 (Pu-239), Plutonium-240 (Pu-240), Uranium-233 (U-233), Uranium-234 (U-234), Uranium-235 (U-235), and Uranium-238 (U-238)

The current project database has not yet been fully validated in RFEDS A full set of validated hot water rinsate analytical data will be provided in the Phase I RFI/RI Report

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	3 of 16

Further validation of the data set may result in small changes to the reported activities, however, it is not expected that the changes will be of a magnitude which would alter the conclusions of this analysis

The radionuclide activity levels presented in data tables in Sections 6.2 through 6.7 are converted from the reported result in pC1/l to a dust equivalent activity in pC1/g, as follows

$$C_{dust} = C_{rinsate} * \frac{RV}{A * SD}$$

where

 $C_{dust}$  = dust equivalent activity (pC1/g)

 $C_{rinsate}$  = hot water rinsate activity (pC1/l)

RV = rinsate volume (1)

A = rinsate sample area (m<sup>2</sup>)

SD = surface dust amount (g/m<sup>2</sup>)

The surface dust amount was assumed to be  $560 \text{ mg/m}^2$ , or  $0.56 \text{ g/m}^2$  (Hawley, 1985) An example calculation is provided below for a Pu-239/240 activity of 7.9 pCi/l, a rinsate volume of 15.09 l, and a rinsate area of  $10 \text{ m}^2$ 

$$C_{dust} = 7.9 * \frac{15.09}{10 * 0.56} = 21.3 pCi/g$$

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	4 of 16

### 6.1.2 Radionuclide Standards

The results of the field radiation surveys and the smear and hot water rinsate sampling undertaken at OU15 were compared to the Code of Federal Regulations (CFR) and DOE standards outlined in Section 3 0 of the Work Plan and listed below

10 CFR 20, App B	Protection against radiation,
29 CFR 1910 96 (b)	Exposure of individuals to radiation in restricted areas,
29 CFR 1910 96 (c)	Exposure of airborne radioactive materials,
29 CFR 1910 96 (l)	Notification of incidents,
DOE Order 5400 5	Radiation protection of the public and the environment, and
DOE Order 5480 11	Radiation protection for occupational workers

Dose-based screening levels express the maximum rate (e g , hourly or daily) at which individuals may be exposed to radiation. Dose-rates are typically expressed as millirems per year or rems per year, and indicate the maximum acceptable whole-body dose an individual may receive over the indicated time period. Dose-based screening levels do not relate directly to excess cancer risk, and are commonly used by health-physicists or promulgated as guidance by DOE, the Atomic Energy Commission, and the Nuclear Regulatory Commission (NRC)

The specific dose-rate standards that are used to establish the screening levels for all radionuclides for the OU15 Stage I and II data are listed below

Technical Memorandum Number 1 for Operable Unit 15 Phase I RFI/RI Inside Building Closures	Manual Section Page	RFP/ER-OU15 01-TM 01-93 6 0, Final 5 of 16
Whole body, head and trunk, active blood-forming organs, lens of eyes, or gonads		1-1/4 rem per calendar quarter
hands and forearms, feet and ankles		18-¾ rem per calendar quarter
skin of whole body		7-1/2 rem per calendar quarter

In addition to dose-rate limitations, concentrations of specific airborne radionuclides are presented in the regulations which correspond to the specified dose-rate limitations. These airborne concentration limitations were used to establish the screening levels for the OU15 Stage I and II data. Acceptable air concentrations of radionuclides were converted to acceptable dust concentrations using the following equation, which is presented in "Residual Radioactive Contamination from Decommissioning" (NRC, 1990).

$$C_{dust}\left(\frac{pCt}{g}\right) = \frac{C_{air}\left(\frac{pCt}{m^3}\right)}{DL\left(\frac{g}{m^3}\right)}$$

where DL is the dust loading in air. The dust loading value used was 100  $\mu$ g/m³ (NRC, 1993). An example calculation is provided below for Am-241, for which the given airborne standard is 6.00 x 10-12  $\mu$ Ci/ml

$$DustEquivalent = \frac{6.00 * 10^{-12} \ \mu C \iota / ml}{100 \mu g / m^3} * \frac{10^6 ml}{m^3} * \frac{10^6 \mu g}{g} * \frac{10^6 pC \iota}{\mu C \iota} = 6.00 * 10^4 pC \iota / g$$

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	6 of 16

The standards given for the radionuclides and their equivalent dust concentrations are provided below

Radionuclide	Occupational Airborne Concentration Limit (µCi/ml)	Dust Equivalent (pC1/g)
Am-241 (soluble)	6 00e-12	6 00e+4
Ra-226 (soluble)	3 00e-11	3 00e+5
Pu-239 (soluble)	2 00e-12	2 00e+4
Pu-240 (soluble)	2 00e-12	2 00e+4
U-233 (soluble)	5 00e-10	5 00e+6
U-234 (soluble)*	6 00e-10	6 00e+6
U-235 (soluble)*	5 00e-10	5 00e+6
U-238 (soluble)*	7 00e-11	7 00e+5

<sup>\*</sup> For soluble mixtures of U-234, U-235, and U-238 in air, chemical toxicity may be the limiting factor The CFR and DOE standards listed in this section provide details on calculating the concentration values

The radionuclide analytical results were compared to the dose-rate and airborne concentration screening levels criteria identified above. Where the data showed an exceedence of any of the above screening criteria, a whole-body dose estimate was made using International Commission on Radiological Protection (ICRP) dose conversion factors provided in Federal Guidance Reports 11 and 12 (EPA, 1988, EPA, 1993). A computer code was used to perform the dose conversion calculations, although no fate and transport calculations were made.

Dose conversions were calculated using the Hanford Environmental Dosimetry System (Generation II, or GENII) The GENII computer code was developed through the Hanford Environmental Dosimetry Upgrade Project in November 1988, and is designed to implement the internal dosimetry models recommended by the ICRP Additional

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	7 of 16

details on the operation of the GENII code can be found in "GENII - The Hanford Environmental Dosimetry Software System, Volumes 1 through 3" (Napier, et al, 1988) The GENII code was recommended for use in evaluating exposures to residual radionuclides within buildings by the NRC (NRC, 1990)

The radiological screening was performed in four steps, as follows

- The hot water rinsate radionuclide results shown in Tables 6-1, 6-4, 6-8, 6-12, 6-14, and 6-17 were screened against the dust equivalent screening levels provided above
- The post-rinsate alpha and beta smear sample results presented in Tables 6-2, 6-5, 6-9, 6-15, and 6-18 were also screened against the levels shown above. Since the specific radionuclide inventory making up the total alpha and beta counts is unknown, the conservative assumption was made to screen against the radionuclide with the lowest acceptable level in dust. All of the radionuclides detected at OU15 are alpha particle emitters. Therefore, the lowest level shown above (2 00 x  $10^4$  pC1/g in dust for Pu-239/240) was used to screen all alpha smear data. Of the radionuclides detected at OU15, none are direct beta-emitters. However, U-235 and U-238 decay to produce Thorium-231 and Thorium-234 (Th-231 and Th-234). The standards for these isotopes are higher (1 x  $10^6$   $\mu$ C1/ml and 6 x  $10^{-8}$   $\mu$ C1/ml in air, respectively) than any of the isotopes analyzed as part of the OU15 Phase I RFI/RI. Therefore, to be conservative, all beta smear samples were screened against the acceptable dust level for U-238
- The beta and gamma dose-rate survey results presented in Tables 6-3, 6-6, 6-10, 6-16, and 6-19 were screened against the whole body dose limit of 1-14 rem per calendar quarter, listed above. This dose limit was converted assuming a standard worker exposure of 500 hours per quarter, resulting in a screening level of 2.5 mrem/hr.
- In IHSSs where any of the hot water rinsate radionuclide results, the alpha and beta smear sample results, or the beta and gamma dose-rate surveys failed the initial screening, the post-rinsate smear data were used with the GENII computer code to determine the pathway-specific and organ-specific doses resulting from the maximum total alpha or beta activity detected anywhere in the IHSS. The approach used to determine doses was based on the NRC indoor dust exposure scenario (NRC, 1990). In addition, the use of the highest activity detected in the IHSS instead of an average activity yielded a conservative estimate of the total

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	8 of 16

dose Finally, since the radionuclide inventory in the total alpha and beta smear results was unknown, a GENII run was made using the total activity for each of the radionuclides detected at OU15 The highest predicted dose-rate was then compared to the quarterly dose-rate limit to complete the screening analysis

The results of the four-step radiological screening for each IHSS are presented in Sections 6.2 through 6.7

#### 6.2 IHSS 178

The analytical data for radionuclides detected in the hot water rinsate samples from IHSS 178 are included in Table 6-1. The analytical results of the radiological smear samples collected initially and during the final radiological surveys (pre- and post-rinsate samples) are presented in Table 6-2. The results of the beta and gamma dose-rate surveys are summarized in Table 6-3.

The results of the four-step radionuclide screening process are presented below

## Step 1

No radionuclides detected in the hot water rinsate samples exceeded the permissible radionuclide levels presented in Section 6.1.2

# Step 2

None of the post-rinsate smear samples exhibited total alpha activity exceeding the permissible radionuclide levels presented in Section 6.1.2. In addition, none of the post-rinsate smear samples exhibited total beta activity exceeding permissible U-238 levels presented in Section 6.1.2.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	9 of 16

### Step 3

None of the areas surveyed for beta and gamma dose-rate exceeded the established screening limit of 2.5 mrem/hr

# Step 4

Since none of the data collected in steps 1 through 3 at IHSS 178 exceeded the screening criteria, no GENII analysis was performed for this IHSS

## 6.3 IHSS 179

The analytical results for the hot water rinsate samples, alpha and beta smear samples, and beta and gamma dose-rate surveys for IHSS 179 are provided in Tables 6-4 through 6-6. The results of the beryllium smear samples collected initially and during the final radiological surveys (pre- and post-rinsate samples) are provided in Table 6-7.

The results of the four-step radionuclide screening process are presented below

## Step 1

No radionuclides detected in the hot water rinsate samples exceeded the permissible radionuclide levels presented in Section 6.1.2

# Step 2

None of the post-rinsate smear samples exhibited total alpha or beta activity exceeding the permissible levels presented in Section 6.1.2

# Step 3

None of the areas surveyed for beta and gamma dose-rate in IHSS 179 exceeded the established screening limit of 2.5 mrem/hr

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	10 of 16

#### Step 4

Since none of the data collected in steps 1 through 3 at IHSS 179 exceeded the screening criteria, no GENII analysis was performed for this IHSS

#### 6.4 IHSS 180

The analytical results for the hot water rinsate samples, alpha and beta smear samples, beta and gamma dose-rate surveys, and beryllium smears for IHSS 180 are provided in Tables 6-8 through 6-11

The results of the four-step radionuclide screening process are presented below

### Step 1

No radionuclides detected in the hot water rinsate samples exceeded the permissible radionuclide levels presented in Section 6 1 2

## Step 2

None of the post-rinsate smear samples from IHSS 180 exhibited total alpha or beta activity exceeding the permissible U-238 level presented in Section 6 1 2

#### Step 3

Seven of the sampling areas surveyed for beta dose-rate exceeded the established screening limit of 2.5 mrem/hr. Therefore, additional evaluation of radiological exposure was conducted in Step 4. None of the areas exceeded the screening limit for gamma dose-rate.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	11 of 16

#### Step 4

Some of the beta dose-rate surveys at IHSS 180 failed the conservative screening criteria established under Step 3. Therefore, the GENII model was used to estimate the whole-body dose expected as a result of occupational exposures in IHSS 180. To provide a conservative analysis, the highest total alpha or beta reading from the post-rinsate smear sampling data (69 dpm/100 cm², total beta at sampling area 10 [See Table 6-9 and Figure 3-5]) was used to generate the dust and airborne concentrations for input to the GENII model

The GENII model assumes that the exposed individual receives a radiological dose via incidental ingestion of dust, inhalation of airborne dust, and direct external irradiation. The dust concentration used for the ingestion and irradiation pathways was converted from the smear sample concentration using an assumed dust loading of 560 mg/m<sup>2</sup> on surfaces (Hawley, 1985) and 100  $\mu$ g/m<sup>3</sup> in air (NRC, 1993). This resulted in a radionuclide concentration in dust of 5.6 x 10<sup>6</sup> pCi/kg. The air concentration was estimated at 0.560 pCi/m<sup>3</sup>, as described in Section 6.1.2

Since the specific radionuclide inventory comprising the total alpha and beta radiation reading was unknown, the GENII model was run once for each of the six radionuclides detected at OU15. In each GENII run, the total activity was input assuming that it was all attributable to one of the six radionuclides under evaluation. The maximum predicted dose from any of the six runs was then used as a basis for evaluating the screening results. The results for IHSS 180 were

Technical Memorandum Number 1 for Operable Unit 15 Phase I RFI/RI	Manual Section	RFP/ER-OU15 01-TM 01-93 6 0, Final
Inside Building Closures	Page	12 of 16

Radionuclide	Annual Effective Dose Equivalent
Am-241	3 7 rem/yr
Pu-239/240	0 38 rem/yr
Ra-226	0 86 rem/yr
U-233/234	0 17 rem/yr
U-235	0 58 rem/yr
U-238	0 15 rem/yr

The GENII results for an occupational exposure show annual effective dose equivalents below the limit value of 5 rem/yr (1¼ rem/quarter). The GENII assessment was conservative in that the maximum total alpha or beta radiation reading was used, and the worst-case was selected in terms of the radionuclide inventory comprising the total alpha or beta count.

#### 6.5 IHSS 204

The analytical results for the hot water rinsate samples and alpha and beta smear samples for IHSS 204 are provided in Tables 6-12 and 6-13

IHSS 204 will remain an operational unit within the Building 447 RCA and will continue to be used for processing radioactive material. Therefore, the Work Plan did not include post-rinsate smear sampling or beta and gamma dose-rate surveys for IHSS 204. No radionuclides detected in the hot water rinsate samples from IHSS 204 exceeded the permissible radionuclide levels presented in Section 6.1.2. Since final closure with respect to radiological contamination cannot be addressed at this time because of the

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	13 of 16

continued operation of the unit, the radiological screening was not carried any further for IHSS 204

#### 6.6 IHSS 211

The analytical results for the hot water rinsate samples, alpha and beta smear samples, and beta and gamma dose-rate surveys for IHSS 211 are provided in Tables 6-14 through 6-16

The results of the four-step radionuclide screening process are presented below

#### Step 1

No radionuclides detected in the hot water rinsate samples exceeded the permissible radionuclide levels presented in Section 6 1 2

#### Step 2

None of the post-rinsate smear samples from IHSS 211 exhibited total alpha or beta activity exceeding the permissible radionuclide levels presented in Section 6.1.2

### Step 3

None of the areas surveyed for beta and gamma dose-rate in IHSS 211 exceeded the established screening limit of 2.5 mrem/hr

#### Step 4

Because none of the data collected at IHSS 211 exceeded the screening criteria described in Steps 1 through 3, no GENII analysis was performed for this IHSS

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	14 of 16

#### 6.7 IHSS 217

The analytical results for the hot water rinsate samples, alpha and beta smear samples, and beta and gamma dose-rate surveys for IHSS 217 are provided in Tables 6-17 through 6-19

The results of the four-step radionuclide screening process are presented below

### Step 1

No radionuclides detected in the hot water rinsate samples from IHSS 217 exceeded the permissible radionuclide levels presented in Section 6 1 2

### Step 2

None of the post-rinsate smear samples from IHSS 217 exhibited total alpha or beta activity exceeding the permissible radionuclide levels presented in Section 6.1.2

### Step 3

None of the areas surveyed for beta and gamma dose-rate in IHSS 217 exceeded the established screening limit of 2.5 mrem/hr

#### Step 4

Since none of the data collected at IHSS 217 exceeded the screening criteria described in Steps 1 through 3, no GENII analysis was performed for this IHSS

### 6.8 Summary of CERCLA Evaluation

The CERCLA evaluation for OU15 consisted of comparing radionuclide data to appropriate regulatory criteria and standards, as well as to NRC, DOE, and RFP guidance, and presenting beryllium smear data. The radionuclide evaluation is

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	15 of 16

summarized in Section 6 8 1, and the presence of beryllium in two of the OU15 IHSSs is addressed in Section 6 8 2

#### 6.8.1 Radionuclide Evaluation

Radionuclide results from the hot water rinsate samples, total alpha and beta counts from smear samples, and beta and gamma dose-rate data from dose-rate surveys were compared to radiation standards for workers. The standards included maximum permissible airborne radionuclide levels and maximum permissible dose-rate levels for all exposure pathways. None of the IHSSs showed radionuclide levels which yielded calculated exceedences of the maximum permissible radionuclide levels in air. IHSS 180 showed beta dose-rate survey data which exceeded the initial screening level of 2.5 mrem/hr. However, GENII calculations of total dose from specific radionuclides at IHSS 180 showed that the dose-rate standards were not exceeded at IHSS 180.

Based on these results, no further investigatory action is proposed for OU15 with respect to radionuclides

### 6.8.2 Beryllium Contamination

The presence of beryllium surface contamination in excess of the RFP beryllium smear control level of 25 micrograms per square foot (approximately 2 7 micrograms per 100 square centimeters), as established in the RFP Health and Safety Practices HSP 13 04, was detected during smear sampling in IHSSs 179 and 180. However, the pattern of detections and the relative magnitude of the results within and around each of the IHSSs did not indicate that the beryllium surface contamination was attributable to the storage of wastes in the IHSSs. A pattern of detections showing higher beryllium levels within the IHSS versus areas around the IHSS would be indicative that the IHSS was the beryllium source. Instead the sampling results suggested that the presence of beryllium

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	60, Final
Inside Building Closures	Page	16 of 16

may be associated with other operations in the respective buildings. The beryllium detections were apparently random in location and magnitude with respect to the IHSS, and did not indicate a higher frequency or magnitude of detections within the IHSS versus outside the IHSS. Beryllium may have been commingled with the RCRA-regulated wastes stored in drums in the IHSSs, but was not itself subject to regulation. Beryllium is only RCRA-regulated as a discarded or off-specification chemical product that is essentially pure in form. Such a waste (e.g., beryllium dust) would carry an EPA Code of P015.

IHSSs 179 and 180 should be able to proceed with the RCRA closure process despite the presence of beryllium. The RCRA clean closure performance standards specified in the RFP State RCRA Permit address only TC metals, which do not include beryllium Furthermore, results from the OU15 Stage I and II field investigations did not indicate that beryllium contamination had migrated from the IHSS locations to outside the buildings. Although not a RCRA concern, beryllium contamination in IHSSs 179 and 180 will need to be addressed prior to completing building D&D or economic redevelopment. Beryllium contamination will be addressed for ongoing building operations on a building-wide basis in accordance with the requirements of HSP 13 04.

										Detection					Rusate	
Building IHSS Location	SSHI	Location	Sample Number	Sample Date	Test Group	Test Group Radionuclide	Result (pCVL)	Error	Error Qualifier	Lund (pCvL)	Valudation Code	Code	QC Partner	Kınsate Volume (L)	Area (m^2)	Concentration in Dust* (pCVg)
188	178	IHSS	BU00011ER	16-Aug 93	DRADS	GROSS ALPHA	19	12		0.82	>	REAL		15 09	10	213e+1
883	178	HSS	BU00011ER	16-Aug 93	DRADS	GROSS BETA	=	40		\$ \$	>	REAL		15 09	01	2 96e+1
188	178	IHSS	BU00011ER	16-Aug 93	DRADS	PLUTONIUM 239/240	023	0 012	æ	600 0	>	REAL		15 09	9	6 20e-2
188	178	IHSS	BU00011ER	16-Aug 93	DRADS	RADIUM 226	37	0 18	BJ	0 26	۷	REAL		15 09	01	9 970-1
188	178	IHSS	BU00011ER	16-Aug 93	DRADS	URANIUM-233 -234	93	17	æ	110	∢	REAL.		15 09	2	2 51 0+1
881	178	IHSS	BU00011ER	16-Aug 93	DRADS	URANIUM 235	22	0 20	-	0 036	<	REAL		15 09	9	5 93e 1
881	178	IHSS	BU00011ER	16-Aug 93	DRADS	URANIUM 238	-	0 44	B	0 001	∢	REAL		15 09	10	2 69 <del>c</del> +0
188	178	IHSS	BU0001 2ER	16-Aug 93	DRADS	GROSS ALPHA	6.2	13		69 0	>	DUP	BU00011ER	15 09	10	2 346+1
881	178	IHSS	BU00012ER	16-Aug 93	DRADS	GROSS BETA	11	<del>.</del>		5.1	>	DCF	BU00011ER	15 09	01	4 58e+1
881	178	IHSS	BU00012ER	16-Aug 93	DRADS	PLUTONIUM-239/240	024	0 012	B	0000	>	DUP	BU00011ER	15 09	01	647e2
188	178	IHSS	BU00012ER	16-Aug 93	DRADS	RADIUM 226	49	014	BI	0 14	∢	DOP	BU00011ER	15 09	10	1 32e+0
881	178	IHSS	BU00012ER	16-Aug 93	DRADS	URANIUM 233 234	96	- 8	В	0 037	<	DOP	BU00011ER	15 09	10	2 59e+1
881	178	IHSS	BU00012ER	16-Aug 93	DRADS	URANTUM 235	4	0 29	-	0 063	∢	DGP	BU00011ER	15 09	91	1 196+0
188	178	HSS	BU00012ER	16-Aug 93	DRADS	URANTUM 238	12	0 20	æ	0 063	⋖	DOL	BU00011ER	15 09	01	3 236+0
188	178	Permeter	BU00014ER	16-Aug 93	DRADS	GROSS ALPHA	\$2	0.79		0 47	>	REAL		11 73	9	1 82e+1
881	178	Peruneter	BU00014ER	16-Aug 93	DRADS	GROSS BETA	2	5 6		39	>	REAL		11 73	9	3 49e+1
881	178	Perimeter	BU00014ER	16-Aug 93	DRADS	PLUTONIUM 239/240	05	0100	മ	0 000	>	REAL		11.73	9	6 98e 2
881	178	Peruneter	BU00014ER	16-Aug 93	DRADS	RADIUM 226	41	0 20	B	0 27	∢	REAL		11 73	9	1 64e+0
188	178	Peruneter	BU00014ER	16-Aug 93	DRADS	URANIUM 233 234	\$ \$	12	B	0 035	∢	REAL		11 73	9	1 92e+1
188	178	Peruneter	BU00014ER	16-Aug 93	DRADS	URANIUM 235	21	610	-	0900	∢	REAL		11 73	9	7 33e 1
188	178	Peruneter	BU00014ER	16 Aug 93	DRADS	URANIUM 238	<b>8</b>	0 38	£	0 035	∢	REAL		11 73	9	2 83 <del>c+</del> 0
188	178	Pathway	BU0001 SER	16-Aug 93	DRADS	AMERICTUM 241	610	0 010 0		0 002	>	REAL		13 29	90 90	5 12e 2
188	178	Pathway	BU0001 SER	16-Aug 93	DRADS	GROSS ALPHA	<b>8</b> 2	2.2		0.83	>	REAL		13 29	œ œ	7 556+1
188	178	Pathway	BU0001 5ER	16-Aug 93	DRADS	GROSS BETA	21	4		5.4	>	REAL		13 29	90 90	5 66e+1
188	1.78	Pathway	BU0001 SER	16 Aug 93	DRADS	PLUTONIUM 239/240	046	9100		0 008	>	REAL		13 29	œ œ	1 24e 1
188	178	Pathway	BU0001 5ER	16 Aug 93	DRADS	RADIUM 226	45	610	BJ	0 27	∢	REAL		13 29	89 89	1 21e+0
188	178	Pathway	BU0001 SER	16-Aug 93	DRADS	URANIUM 233 234	92	36	83	0 058	∢	REAL		13 29	90 90	7 01e+1
881	178	Pathway	BU0001 SER	16-Aug 93	DRADS	URANTUM 235	88	0 42		0 058	∢	REAL		13 29	89 89	2 64e+0
881	178	Pathway	BU0001 SER	16 Aug 93	DRADS	URANTUM 238	94	0 41	B	0 058	۷	REAL		13 29	80 80	2 54 <del>c+</del> 0

Calculated assuming 560 mg of dust per square meter

Table 6-2 Smear Sample Results IHSS 178

						Pre-Runsate Dust	rate Dust			Post-Run	Post-Rinsate Dust
				Pre-Rinsate Smear Sample	mear Sample	Concentration.	tration.	Post-Rinsale	Post-Rinsale Smear Sample	Concentration,	tration *
Building	Room	SSHI	Area	Atpha (4pm/100 cm^2)	Beta (dpm/100 cm^2)	Alpha (pCVg)	Beta (pCvg)	Alpha (dpm/100 cm^2)	Beta (dpm/100 cm^2)	Alpha (pCvg)	Beta (pCvg)
881	165	178	-	ю	0	246+2	0 0000	0	18	0 0e+0	1 4e+3
883	165	178	7	0	0	0 0e+0	0.06+0	0	0	0.0e+0	0 0c+0
188	165	178	6	0	18	0 06+0	1 4e+3	0	æ	0.06+0	2 4c+2
881	165	178	4	0	m	0 0e+0	2 4c+2	0	6	0 0e+0	7 2e+2
883	165	178	\$		0	2 4c+2	0 06+0		0	2 4c+2	0.06+0
881	165	178	9	6	0	7 2c+2	0 0e+0	3	0	2 4c+2	0 0e+0
881	165	178	7	0	12	0 0 <del>c+</del> 0	9 7c+2	6	15	2 4c+2	1 26+3
188	165	178	•	0	24	0 0e+0	19e+3	ø	a	72c+2	72c+2
188	165	178	٥	8	0	2 4c+2	0 0 <del>c+</del> 0	0	21	0.000	1 7e+3
881	165	178	10	6	0	7 2c+2	7 2c+2	0	0	0.000	0 0e+0
881	165	178	=	0	0	0.06+0	0.000	E	0	2 4c+2	0.06+0
881	165	178	12	0	30	0.06+0	2 4c+3	3	3	2 4c+2	2 4e+2
188	165	178	13	0	0	0 Oc+0	0.06+0	0	27	0.06+0	2 2c+3
881	165	178	4	0	15	0 0e+0	1 2e+3	0	3	0.06+0	3 2e+3
881	165	178	15	0		0 0e+0	2 4c+2	3	0	2 4c+2	0 0c+0
881	165	178	91	•	0	4 8c+2	0 0c+0	0	9	0.06+0	4 8c+2
188	165	178	11	0	0	0.06+0	0 06+0	Φ	33	72e+2	2.76+3
881	165	178	8	0	6	0.06+0	7 2c+2	9	18	4 8e+2	1 46+3
883	165	178	61	3	0	24c+2	0.06+0	0	0	0.000	0 0e+0
188	165	178	20	3	9	2 4e+2	4 8c+2	9	0	4 8c+2	0 0c+0
188	165	178	21	0	0	0.06+0	0.06+0	0	0	0.06+0	0.06+0
881	165	178	22	0	0	0 0e+0	0 06+0	0	0	0.06+0	0.06+0
881	165	178	23	3	93	2 4e+2	2 4c+2	0	27	0.06+0	2 2c+3
881	165	178	74	0	6	0.06+0	7 2e+2	0	30	0.06+0	2 4c+3
881	165	178	25	0	9	0 0e+0	4 8e+2	0	0	0 06+0	0.06+0
188	165	178	56	9	0	4 8c+2	0.06+0	0	36	0.06+0	2 9e+3
881	165	178	27	m	0	2 4c+2	0.06+0	9	0	4 8c+2	0 0e+0
881	165	178	78	8	9	24e+2	4 8c+2	0	0	0.0€+0	0 0e+0
881	165	178	53	0	98	0 0e+0	1 4c+3	0	0	0.06+0	0.06+0
188	165	178	8	0	0	0.0€+0	0 06+0	0	39	0	2 10+2

\* Calculated assuming 560 mg dust per square meter

Table 6-3
Beta and Gamma Dose-Rate Survey Data
IHSS 178

				Gamma Dose-Rate	Beta Dose-Rate
Building	Room	IHSS	Area	(mrem/hr)	(mrem/hr)
001		1.50		•	۰
881	165	178	1	0	0
881	165	178	2	0	0
881	165	178	3	0	0
881	165	178	4	0	0
188	165	178	5	0	0
881	165	178	6	0	0
881	165	178	7	0	0
881	165	178	8	0	0
881	165	178	9	0	0
881	165	178	10	0	0
881	165	178	11	0	0
881	165	178	12	0	0
881	165	178	13	0	0
881	165	178	14	0	0
881	165	178	15	0	0
881	165	178	16	0	0
881	165	178	17	0	0 4
881	165	178	18	0	0 4
881	165	178	19	0	0 4
881	165	178	20	0	0 4
881	165	178	21	0	0 4
881	165	178	22	0	0 4
881	165	178	23	0	0 4
881	165	178	24	0	0 4
881	165	178	25	0	0 4
881	165	178	26	0	0 4
881	165	178	27	0	0 4
881	165	178	28	0	0 4
881	165	178	29	0	0 4
881	165	178	30	0	0 4

Table 6-4
Radionuclides Detected in Hot Water Rinsate Samples IHSS 179

Building	SSHI	Building IIISS Location	Sample Number	Sample Date	Text Group	Radionuclide	Result (pCVL)	Error	Qualifier	Detection Limit (pCvL)	Validation Code	QC Code	QC Partner	Rosade Volume (L)	Rusate Area (m^2)	Concentration in Dust* (pCVg)
865	179	Peruneter	BU00033ER	15 Sep-93	DRADS	AMERICTUM 241	0 007	0004	-	1000	>	REAL		1891	7	2 846-2
865	179	Peruneter	BU00033ER	15 Sep-93	DRADS	GROSS ALPHA	<u>82</u>	13		0.51	>	REAL		1591	7	7 31e+1
865	179	Perimeter	BU00033ER	15 Sep-93	DRADS	GROSS BETA	23	28		2.5	>	REAL		1881	7	1 10e+2
865	179	Peruneter	BU00033ER	15 Sep 93	DRADS	PLUTONIUM 239/240	0 005	000	-	0 005	>	REAL		1591	7	2 03e-2
865	179	Peruneter	BU00033ER	15 Sep-93	DRADS	RADIUM 226	98	0 0 0 0	В	0 040	∢	REAL		1591	7	3 49e+0
865	179	Permeter	BU00033ER	15 Sep-93	DRADS	URANIUM 233 234	30	0 79	В	012	∢	REAL		1591	7	1 22e+1
865	179	Peruneter	BU00033ER	15 Sep-93	DRADS	URANIUM 235	017	017	<b>26</b>	0 035	∢	REAL		1591	7	6 90e 1
865	179	Peruneter	BU00033ER	15 Sep-93	DRADS	URANIUM 238	19	29	В	0 062	¥	REAL		1891	7	7 716+1
865	179	Perimeter	BU00034ER	15 Sep-93	DRADS	AMERICTUM 241	0 000	900	~	0 00	>	DO	BU00033ER	1591	7	284e2
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	GROSS ALPHA	11	12		0 56	>	ana	BU00033ER	1591	1	6 90e+1
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	GROSS BETA	25	27		23	>	DUP	BU00033ER	1591	7	1 01e+2
865	179	Perimeter	BU00034ER	15 Sep-93	DRADS	PLUTONIUM 239/240	0015	900 0		0 000	>	DOP	BU00033ER	1591	7	6 09e 2
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	RADIUM 226	8	0 0 0 0	В	0 0 0 0	A	DOP	BU00033ER	1591	7	2 68c+0
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	URANIUM 233 234	33	0 94	В	013	¥	DUP	BU00033ER	1591	7	1 346+1
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	URANIUM 235	0 31	0 26	B	0 043	4	DCP	BU00033ER	18 91	1	1 26e+0
865	179	Peruneter	BU00034ER	15 Sep-93	DRADS	URANTUM 238	91	28	æ	0.15	∢	DOP	BUOO033ER	1891	7	6 49e+1
865	179	IHSS	BU00036ER	15 Sep-93	DRADS	AMERICIUM 241	0 0 18	800 0		0 00	>	REAL		606	m	974e 2
865	179	IHSS	BU00036ER	15 Sep-93	DRADS	GROSS ALPHA	06	0.89		0 49	>	REAL		606	6	4 87e+1
865	179	IHSS	BU00036ER	15 Sep 93	DRADS	GROSS BETA	13	23		26	>	REAL		60 6	۳	7 03e+1
865	179	DHSS	BU00036ER	15 Sep-93	DRADS	PLUTONIUM 239/240	0 014	9000		0 004	>	REAL		60 6	٣	7 58e 2
865	179	IHSS	BU00036ER	15 Sep 93	DRADS	URANIUM 233 234	19	890	<b>6</b> 3	0 13	۷	REAL		60 6	٣	1 03e+1
865	179	IHSS	BU00036ER	15 Sep 93	DRADS	URANIUM 235	010	015	B	0 043	∢	REAL		60 6	æ	5 41e 1
865	179	IHSS	BU00036ER	15 Sep-93	DRADS	URANIUM 238	92	<u>«</u>	B	0 043	∢	REAL		606	E	4 98c+1
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	GROSS ALPHA	120	41		90	>	REAL		9 52	133	1 53e+2
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	GROSS BETA	130	69		4.1	>	REAL		9 52	133	1 66e+2
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	PLUTONIUM 239/240	9000	9000	-	9000	>	REAL.		9 52	133	7 67e 3
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	RADIUM 226	19	0 0 0 0	В	0 0 0 0	∢	REAL		9 52	133	8 56e l
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	URANIUM 233 234	<b>8</b> 2	28	83	0 037	∢	REAL		9 52	133	2 30e+1
865	179	Pathway	BU00037ER	15 Sep-93	DRADS	URANIUM 235	23	690	Ø	0 037	4	REAL		9 52	133	2 94e+0
865	179	Pathway	BI MOOTTED	15 Can. 01	DD A DC	1 TO A NITT D. 4 730	ç.		•							

Calculated assuming 560 mg per square meter

Page 1 of 1

Table 6-5 Smear Sample Results IHSS 179

						Pre-Rms	Pre-Rinsate Dust			Post-Rin	Post-Rinsate Dust
				Pre-Rinsate Smear Sample	mear Sample	Concen	Concentration*	Post-Rinsate S	Post-Rusate Smear Sample	Concen	Concentration*
:	ſ		•		Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Sulding	Koom	HSS	Area	(dpm/100 cm^2)	(dpm/100 cm^2)	(bCvg)	(bCvg)	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCvg)
865	145	179	-	12	24	9 7e+2	1 9e+3	15	42	1 2c+3	3 46+3
865	145	179	7	9	15	4 8c+2	1 2c+3	21	39	1 7e+3	3 le+3
865	145	179	3	12	12	9.7 <del>c+</del> 2	9 7 <del>c+</del> 2	15	27	1 2e+3	2 2e+3
865	145	179	4	6	0	7 2c+2	0 0 <del>c+</del> 0	12	42	9 7e+2	3 4c+3
865	145	179	\$	15	6	1 2 <del>c+</del> 3	7 2c+2	42	45	3 4c+3	3 6e+3
865	145	179	9	æ	15	2 4 <del>c+</del> 2	1 2c+3	45	36	3 6e+3	2 9e+3
865	145	179	7	6	12	72e+2	9 7 <del>c+</del> 2	21	51	1 7c+3	4 10+3
865	145	179	<b>∞</b>	3	0	2 4c+2	0 0e+0	33	8	2.7 <del>c+</del> 3	8 0e+3
865	145	179	6	3	6	2 4c+2	7 2e+2	15	36	1 2e+3	29e+3
865	145	179	10	12	0	9.7c+2	0 0c+0	27	36	2 2e+3	2 9c+3
865	145	179	=	9	24	4 8c+2	1 9e+3	33	09	2 7c+3	4 8c+3
865	145	179	12	3	0	2 4c+2	0 0c+0	27	54	2 2c+3	4 3c+3
865	145	179	13	12	0	9.7 <del>c+</del> 2	0 0 0 0	69	99	5 6c+3	5 3e+3
865	145	179	14	3	39	2 4c+2	3 10+3	15	72	1 2e+3	5 8c+3
865	145	179	15	3	82	2 4c+2	1 4e+3	53	69	4 3c+3	\$ 6e+3
865	145	179	16	6	12	7 2c+2	9 7e+2	21	8	1 7e+3	7 2e+3
865	145	179	11	12	9	9 7c+2	4 8e+2	21	15	1 7e+3	1 2e+3
865	145	179	<u>8</u> 2	6	0	7 2c+2	0 0e+0	39	72	3 le+3	5 8c+3
865	145	179	19	6	9	7 2e+2	4 8c+2	39	30	3 le+3	2 4c+3
865	145	179	70	12	0	9 7 <del>c+</del> 2	0 0e+0	21	99	1 7e+3	5 3e+3
865	145	179	21	9	42	4 8c+2	3 4e+3	21	69	1 7e+3	5 6e+3
865	145	179	22	9	0	4 8c+2	0 0e+0	39	72	3 16+3	5 8e+3
865	145	179	23	9	15	4 8c+2	1 2e+3	9	39	4 8c+2	3 16+3

\* Calculated assuming 560 mg dust per square meter

Table 6-6
Beta and Gamma Dose-Rate Survey Data
IHSS 179

				Gamma Dose-Rate	Beta Dose-Rate
Building	Room	IHSS	Area	(mrem/hr)	(mrem/hr)
865	145	179	1	0	0
865	145	179	2	0	0
865	145	179	3	0	0
865	145	179	4	0	0
865	145	179	5	0	0
865	145	179	6	0	0
865	145	179	7	0	0
865	145	179	8	0 4	0
865	145	179	9	0	1 2
865	145	179	10	0 2	0
865	145	179	11	0	0
865	145	179	12	0	0
865	145	179	13	0	0
865	145	179	14	0	16
865	145	179	15	0	0
865	145	179	16	0	0
865	145	179	17	0	0
865	145	179	18	0	0
865	145	179	19	0	0
865	145	179	20	0	0
865	145	179	21	0	0
865	145	179	22	0	0
865	145	179	23	0	0

Table 6-7 Beryllium Smear Data IHSS 179

				Pre-Rinsate Smear Sample Beryllium	Post-Rinsate Smear Sample Beryllium	Pre-Rinsate Dust Concentration Beryllium*	Post-Rinsate Dus Concentration Beryllium*
uilding	Room	IHSS	Area	(ug/100cm^2)	(ug/100cm^2)	(mg/kg)	(mg/kg)
865	145	179	1	2	0	3 57e+2	
865	145	179	2	0	0		
865	145	179	3	4	1	7 14e+2	1 79e+2
865	145	179	4	0	0		
865	145	179	5	0	0		
865	145	179	6	1	0	1 79e+2	
865	145	179	7	0	4		7 14e+2
865	145	179	8	2	1	3 57e+2	1 79e+2
865	145	179	9	0	0		
865	145	179	10	0	2		3 57e+2
865	145	179	11	4	3	7 14e+2	5 36e+2
865	145	179	12	0	0		
865	145	179	13	1	1	1 79e+2	1 79e+2
865	145	179	14	3	0	5 36e+2	
865	145	179	15	0	0		
865	145	179	16	0	0		
865	145	179	17	1	0	1 79e+2	
865	145	179	18	0	0		
865	145	179	19	4	2	7 14e+2	3 57e+2
865	145	179	20	0	0		
865	145	179	21	0	0		
865	145	179	22	0	1		1 79e+2
865	145	179	23	not counted	0		

<sup>\*</sup> Values calculated assuming 560 mg dust per square meter

Page 1 of 2

Table 6-8
Radionuclides Detected in Hot Water Rinsate Samples
IHSS 180

	CCHI	Building IHSS Location	Number	Sumpre Date	l est Group	Chemical	(pC/L)	Error	Error Qualifier	Lumu (pCvL)	Vaudation Code	Sode Code	QC Partner	Kınsate Volume (L)	Area (m^2)	Concentration in Dust* (pCVg)
883	180	HSS	BU00023ER	01 Sep-93	DRADS	AMERICIUM 241	800 0	9000	1	0 002	^	REAL		1861	18	3 636-2
883	180	IHSS	BU00023ER	01 Sep-93	DRADS	GROSS ALPHA	8	19		0 34	>	REAL		1981	7.8	2270+2
883	180	IHSS	BU00023ER	01 Sep-93	DRADS	GROSS BETA	\$\$	3.7		26	>	REAL		1861	7.8	2 49e+2
883	180	IHSS	BU00023ER	01 Sep-93	DRADS	PLUTONIUM 239/240	0 005	9000	-	0 004	>	REAL		1861	7.8	227e2
883	180	IHSS	BU00023ER	01 Sep 93	DRADS	RADIUM 226	53	0800	£	011	∢	REAL		18 61	7.8	2 59e+0
883	180	IHSS	BU00023ER	01 Sep-93	DRADS	URANIUM 233 234	12	1 9	Ø	0 056	<	REAL		1981	7.8	5 44e+1
883	180	IHSS	BU00023ER	01 Sep-93	DRADS	URANIUM 235	0 30	0 22	B	0 031	۷	REAL		1861	7.8	1 36e+0
883	180	SSHI	BU00023ER	01 Sep-93	DRADS	URANIUM 238	88	7.3	Ø	0 031	¥	REAL		1861	7.8	2 63e+2
883	180	IHSS	BU00024ER	01 Sep 93	DRADS	GROSS ALPHA	8	19		0.42	>	DUP	BU00023ER	1861	7.8	2 27e+2
883	180	IHSS	BU00024ER	01 Sep-93	DRADS	GROSS BETA	89	40		2.5	>	DOP	BU00023ER	1861	7.8	3 086+2
883	180	IHSS	BU00024ER	01 Sep-93	DRADS	PLUTONIUM 239/240	0 007	9000	•	0 002	>	DUP	BU00023ER	1861	7.8	317e2
883	180	HSS	BU00024ER	01 Sep-93	DRADS	RADIUM 226	78	0800	B	0 12	< <	£ C	BU00023ER	1981	7.8	1 27e+0
883	180	IHSS	BU00024ER	01 Sep 93	DRADS	URANIUM 233 234	=	2 2	m	013	4	DO	BU00023ER	1861	7.8	4 99e+1
883	180	IHSS	BU00024ER	01 Sep-93	DRADS	URANIUM 235	12	0 53		013	<	DOP	BU00023ER	1861	7.8	5 44e+0
883	180	IHSS	BU00024ER	01 Sep 93	DRADS	URANTUM 238	19	9 8	æ	9/00	∢	DUP	BU00023ER	1981	7.8	3 04e+2
883	180	Permeter	B1 100026ER	01 Sep 93	DRADS	AMERICH M 241	0 00	9000	-	0.005	>	REAL		13.76	12.2	14162
883	180	Perumeter	BU00026ER	01 Sep 93	DRADS	GROSS ALPHA	270	8	ı	0.58	>	REAL		13.76	12.2	5 44e+2
883	180	Peruneter	BU00026ER	01 Sep-93	DRADS	GROSS BETA	300	-8		27	>	REAL		13.76	12.2	6 04e+2
883	180	Peruneter	BU00026ER	01 Sep 93	DRADS	PLUTONIUM 239/240	0 007	9000	-	900 0	>	REAL		13 76	12.2	1 41e 2
883	180	Peruneter	BU00026ER	01 Sep 93	DRADS	RADIUM 226	4	0900	BJ	0900	٧	REAL		1376	12.2	8 06e 1
883	180	Peruneter	BU00026ER	01 Sep 93	DRADS	URANIUM 233 234	8	9 1	B	0 087	¥	REAL		13 76	12.2	1 216+2
883	180	Peruneter	BU00026ER	01 Sep 93	DRADS	URANIUM 235	76	2.0		0 087	∢	REAL.		13 76	12.2	1 956+1
883	180	Peruncter	BU00026ER	ऋ	DRADS	URANIUM 238	380	24	B	0 049	∢	REAL		13.76	12.2	7 65e+2
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	GROSS ALPHA	150	3.5		041	>	REAL		21 3	12.7	4 49 <del>c+</del> 2
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	GROSS BETA	180	6.4		3.0	>	REAL		21 3	12.7	5 39e+2
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	PLUTONIUM 239/240	900 0	000	-	0 004	>	REAL		21 3	127	1 80e 2
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	RADIUM 226	46	110	æ	0.15	∢	REAL		21 3	127	1 38e+0
883	180	Pathway	BU00027ER	02 Sep-93	DRADS	URANIUM 233 234	37	53	B	0 14	٧	REAL.		21 3	12.7	1116+2
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	URANIUM 235	4 4	=		0 12	∢	REAL		21 3	12.7	1 326+1
883	180	Pathway	BU00027ER	02 Sep 93	DRADS	URANIUM 238	220	28	æ	015	¥	REAL		21 3	12.7	6 59e+2
883	180	Pathway	BU00028ER	02 Sep-93	DRADS	AMERICIUM 241	0 004	0 00	-	0000	>	DOP	BU00027ER	213	127	1 20e 2
883	180	Pathway	BU00028ER	02 Sep 93	DRADS	GROSS ALPHA	8	40		0 36	>	DO	BU00027ER	21 3	12.7	5 69e+2
883	180	Pathway	BU00028ER	02 Sep 93	DRADS	GROSS BETA	180	63		2 8	>	DOP	BU00027ER	21 3	127	\$ 39et 2
883	180	Pathway	BU00028ER	02 Sep-93	DRADS	PLUTONIUM 239/240	0 007	0000	7	0 001	>	DC	BU00027ER	21 3	12.7	2 10e-2
883	180	Pathway	Bt/00028ER	02 Sep-93	DRADS	RADIUM 226	51	010	B	013	٧	DO	BU00027ER	21 3	12.7	1 53e+0
883	180	Pathway	BU00028ER	02 Sep 93	DRADS	URANIUM 233 234	40	89	B	0 075	∢	DG	BU00027ER	21 3	12.7	1 20e+2
883	180	Pathway	BUX00028ER	02 Sep-93	DRADS	URANIUM 235	4.5	<del>-</del>	æ	0.042	∢	ana	BU00027ER	21 3	127	1 35e+1
883	180	Pathway	BU00028ER	02 Sep 93	DRADS	URANIUM 238	250	33	B	0 042	∢	ā	BU00027ER	21 3	12.7	7 494+7

Table 6-8
Radionuclides Detected in Hot Water Rinsate Samples
IHSS 180

Budding	SSHI	Location	Sample Number	Sample Date	Test Group	Chemical	Result (pCVL)	Error	Qualifier	Detection Limit (pCVL)	Validation Code	QC QC P.	Russate Volume (L)	_	Rusale C Area (m^2)	Concentration in Dust* (pCVg)
883	180	Pathway	BUO0030ER	02 Sep-93	DRADS	AMERICIUM 241	900 0	0 004	J	0 002	>	REAL	1287		39	9 92e-3
883	180	Pathway	BU00030ER	02 Sep-93	DRADS	GROSS ALPHA	100	31		0 59	>	REAL	12.87		13.9	1 65e+2
883	180	Pathway	BU00030ER	02 Sep-93	DRADS	GROSS BETA	140	9 8		27	>	REAL	1287		3.9	2316+2
883	180	Pathway	BU00030ER	02 Sep 93	DRADS	PLUTONIUM 239/240	0000	0 00	-	0000	>	REAL	1287		3.9	66le 3
883	180	Pathway	BU00030ER	02 Sep 93	DRADS	RADIUM 226	88	0 0 0 0	BJ	010	<	REAL	1287		39	463e 1
883	180	Pathway	BU00030ER	02 Sep-93	DRADS	URANIUM 233 -234	21	31	В	0 034	∢	REAL	1287		39	3 47e+1
883	180	Pathway	BU00030ER	02 Sep-93	DRADS	URANIUM-235	13	0 48	В	0 034	∢	REAL	1287		3.9	215e+0
883	180	Pathway	BU00030ER	02 Sep 93	DRADS	URANIUM 238	110	7	В	0900	∢	REAL	1287		3.9	1 82e+2
				***************************************	-											

\* Calculated assuming 560 mg of dust per square meter

Page 1 of 2

Table 6-9 Smear Sample Results IHSS 180

						rre-Kinsale Dust	ate Dust			LOST-VINSMIC DASI	mic Dust
				Pre-Rinsate Smear Sample	mear Sample	Concentration*	ration*	Post-Rinsate S	Post-Rinsate Smear Sample	Concentration*	tration*
				Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Building	Room	SSHI	Area	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCvg)	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCvg)
883	104	180	-	9	0	4 8c+2	0 0c+0	٥	0	7 2c+2	0 0e+0
883	104	180	2	6	81	7 2e+2	1 4e+3	9	0	4 8c+2	0 00+0
883	104	180	3	15	0	1 2c+3	0 000+0	12	0	976+2	0 00+0
883	104	180	4	9	0	4 8c+2	0 0c+0	9	6	4 8c+2	7 20+2
883	104	180	~	12	0	9 7 <del>c+</del> 2	0 0c+0	21	30	1 7c+3	2 4c+3
883	104	180	9	15	15	120+3	1 2e+3	9	24	4 8c+2	1 96+3
883	104	180	7	15	0	1 2c+3	0 000+0	18	21	1 4c+3	1 7c+3
883	104	180	∞	6	24	7 2e+2	1 9e+3	9	24	4 8c+2	1 96+3
883	104	180	6	6	21	7 2e+2	1 7e+3	12	21	97 <del>c+</del> 2	1 7e+3
883	104	180	10	9	27	4 8c+2	2.2e+3	6	69	7 2c+2	5 6c+3
883	104	180	=	9	0	4 8c+2	0 0e+0	9	0	4 8c+2	0 000+0
883	104	180	12	15	30	1 2e+3	2 4c+3	9	36	4 8c+2	2 9e+3
883	104	180	13	15	45	1 2e+3	3 6c+3	30	9	2 4c+3	4 8c+2
883	104	180	7	12	21	9 7e+2	1 7e+3	3	24	2 4c+2	1 96+3
883	104	180	15	15	8	1 2e+3	1 4c+3	6	12	7 2c+2	9 7c+2
883	104	180	16	9	0	4 8e+2	0 0c+0	9	18	2 4c+2	1 4c+3
883	104	180	11	6	12	7 2e+2	9 7e+2	<b>8</b> 2	12	1 4c+3	9 7 <del>c+</del> 2
883	104	180	18	6	0	7 2e+2	0 0e+0	6	15	7 2c+2	1 26+3
883	104	180	61	15	6	1 2e+3	72c+2	18	6	1 4c+3	7 2c+2
883	104	081	70	9	6	4 8c+2	7 2e+2	3	30	24c+2	2 4c+3
883	104	180	21	9	<b>8</b> -	4 8c+2	1 4c+3	6	0	72e+2	0 0c+0
883	104	180	22	3	57	2 4e+2	4 6e+3	12	24	9.7 <del>c+</del> 2	1 9e+3
883	104	180	23	0	0	0 0c+0	0 0c+0	6	48	7 2e+2	3 9c+3
883	104	180	24	3	0	2 4c+2	0 0c+0	18	0	1 4e+3	0 0c+0
883	104	180	25	6	12	7 2e+2	97e+2	12	0	9 7e+2	0 0c+0
883	104	180	56	9	0	4 8c+2	0 0e+0	45	3	3 6c+3	2 4c+2
883	104	180	77	18	12	1 4c+3	976+2	21	33	1 7e+3	2 7c+3
883	104	180	<b>58</b>	6	<b>8</b> 2	7 2e+2	1 4e+3	21	9	1 7c+3	4 8c+2
883	104	180	53	3	27	2 4c+2	2 2e+3	6	36	72c+2	2.96+3
883	104	180	30	9	39	4 8c+2	3 16+3	15	39	1 2c+3	3 le+3
883	104	180	3	9	0	4 8c+2	0 0e+0	21	54	1 7e+3	4 3c+3
883	104	180	12	21	0	1 7e+3	0 0e+0	21	42	1 7e+3	3 4c+3
883	104	180	33	9	0	4 8c+2	0 0c+0	9	57	4 8c+2	4 6c+3
883	104	180	콨	9	30	4 8c+2	2 4e+3	21	45	1 7e+3	3 66+3
883	104	180	35	6	6	7 2e+2	7 2c+2	3	21	2 4c+2	1 7e+3
883	104	180	36	6	ю	7 2e+2	2 4 <del>c+</del> 2	6	9	72c+2	4 8c+2
883	104	180	37	0	36	0.00	2 9e+3	0	٣	0 000+0	2 4c+2
003	701	90.	9.0		•						

Table 6-9 Smear Sample Results IHSS 180

						Pre-Rinsale Dust	ate Dust			Post-Rin.	Post-Rinsate Dust
				Pre-Rinsate Smear	Smear Sample	Concentration*	'ration*	Post-Rinsate Smear Sample	mear Sample	Concen	Concentration*
				Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Building	Room	SSHI	Area	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(bCvg)	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCv/g)
883	104	180	39	8	0	2 4c+2	0 00+0	12	21	976+2	1 7e+3
883	104	180	40	21	0	1 7e+3	0 0c+0	3	45	246+2	3 66+3
883	104	180	4	0	21	0 00+0	1 7c+3	12	0	9 7c+2	0 0 <del>c+</del> 0
883	104	180	42	12	0	97c+2	0 000+0	•	0	4 8c+2	0 0e+0
883	104	180	43	0	12	0 00-+0	9.7c+2	12	0	9 7c+2	0 0c+0
883	104	180	44	0	0	0 00+0	0 000+0	3	٣	24c+2	2 4c+2
883	104	180	45	0	0	0 00+0	0.00+0	9	0	4 8c+2	0 000
883	104	180	46	0	0	0 00+0	0 00+0	6	0	7 2c+2	0 000
883	104	180	47	81	<del>8</del> 1	1 4c+3	1 4c+3	3	12	240+2	9.7c+2
883	104	180	48	12	12	9 7c+2	97e+2	3	0	24c+2	0 0c+0
883	104	180	49	9	9	4 8c+2	4 8e+2	9	0	4 8c+2	0 000

\* Calculated assuming 560 mg of dust per square meter

Table 6-10

Beta and Gamma Dose-Rate Survey Data

IHSS 180

883 883	Room	<i>IHSS</i>			
		11133	Area	(mrem/hr)	(mrem/hr)
883	104	180	1	0 1	0
	104	180	2	0	0 4
883	104	180	3	0	0 4
883	104	180	4	0	0
883	104	180	5	0 1	1 2
883	104	180	6	0	0 4
883	104	180	7	0 1	0
883	104	180	8	o	0
883	104	180	9	0	0 4
883	104	180	10	0	0 4
883	104	180	11	o	0 4
883	104	180	12	0	0
883	104	180	13	0	0
883	104	180	14	0	0.4
883	104	180	15	0	0 4
883	104	180	16	Ö	0 4
883	104	180	17	Ö	04
883	104	180	18	0 1	2
883	104	180	19	0	08
883	104	180	20	0 1	2
883	104		21	0	08
		180			
883	104	180	22	0 1	0
883	104	180	23	0.5	11 2
883	104	180	24	0	0
883	104	180	25	0	0 8
883	104	180	26	0	0 8
883	104	180	27	0 4	0 4
883	104	180	28	0	0 1
883	104	180	29	0 1	4 4
883	104	180	30	03	56
883	104	180	31	0 2	3 6
883	104	180	32	0	0 2
883	104	180	33	03	2 4
883	104	180	34	0 1	0 8
883	104	180	35	0 1	0 4
883	104	180	36	0	0 4
883	104	180	37	0	0
883	104	180	38	0	0
883	104	180	39	0	0 4
883	104	180	40	0	0
883	104	180	41	03	4 4
883	104	180	42	0 1	3 2
883	104	180	43	0 1	2 8
883	104	180	44	0	0 4
883	104	180	45	0	0 4
883	104	180	46	0	0 4
883	104	180	47	0 1	0 4
883	104	180	48	0	1 2
883	104	180	49	0	0 4

Table 6-11 Beryllium Smear Data IHSS 180

Building	Room	IHSS	Area	Pre-Rinsate Smear Sample Beryllium (ug/100cm^2)	Post-Rinsate Smear Sample Beryllium (ug/100cm^2)	Pre-Rinsate Dust Concentration Beryllium* (mg/kg)	Post-Rinsate Dus Concentration Beryllium* (mg/kg)
883	104	180	1	0	1		1 79e+2
883	104	180	2	0	0		
883	104	180	3	0	0		
883	104	180	4	1	0	1 79e+2	
883	104	180	5	3	0	5 36e+2	
883	104	180	6	0	0		
883	104	180	7	0	2		3 57e+2
883	104	180	8	0	0		
883	104	180	9	0	0		
883	104	180	10	1	0	1 79e+2	
883	104	180	11	0	0		
883	104	180	12	0	0		
883	104	180	13	0	o		
883	104	180	14	0	0		
883	104	180	15	0	0		
883	104	180	16	0	0		
883	104	180	17	0	0		
883	104	180	18	0	0		
883	104	180	19	3	0	5 36e+2	
883	104	180	20	1	0	1 79e+2	
883	104	180	21	0	0		
883	104	180	22	0	3		5 36e+2
883	104	180	23	0	0		
883	104	180	24	0	0		
883	104	180	25	4	0	7 14c+2	
883	104	180	26	1	0	1 79e+2	
883	104	180	27	0	0		
883	104	180	28	0	0		
883	104	180	29	0	0		
883	104	180	30	0	0		
883	104	180	31	0	3		5 36e+2
883	104	180	32	0	0		
883	104	180	33	0	23		4 11e+3
883	104	180	34	1	2	1 79e+2	3 57e+2
883	104	180	35	4	8	7 14e+2	1 43e+3
883	104	180	36	0	6		1 07e+3
883	104	180	37	0	0		
883	104	180	38	0	6		1 07e+3
883	104	180	39	0	0		
883	104	180	40	0	0		
883	104	180	41	0	2		3 57e+2
883	104	180	42	0	0		
883	104	180	43	0	0		
883	104	180	44	14	0	2 50e+3	
883	104	180	45	0	0		
883	104	180	46	0	27		4 82e+3
883	104	180	47	0	33		5 89e+3
883	104	180	48	1	14	1 79e+2	2 50e+3
883	104	180	49	o	1	<del>-</del>	1 79e+2

<sup>•</sup> Values calculated assuming 560 mg dust per square meter

Table 6-12 Radionuclides Defected in Hot Water Rinsate Samples IHSS 204

Budding	SSHI	Location	Sample Number	Sample Date	Test Group	Radionuclide	Result (pCvL)	Error	Qualifier	Detection Limit (pCVL)	Validation Code	QC Code	QC Partner	Rinsate Volume	Rinsate	Concentration in Dust*
447	204	Wash Rack	BU000040ER	11-Oct 93	DRADS	GDOSC AT DUA	3.	١							(* m)	(Brok)
447	204	Wash Rack	BI MONOANER	11-0-103	DAAD	GBOSS PETA	2 5	» :		_	>	REAL		239	8 2	781642
447	204	Wash Rack	BI MONAOFD	11 004 03	2000		12	36		2	<	REAL		23.9	8.2	375047
447	2	Warh Deat	11000010	66 30	200	UKANIUM 233 234	24	29		0.5	>	REAL		210	, ,	1000
: :	5	V 43ft KACK	DUMM40EK	11 Oct 93	DRADS		3.5	0 77		00	>	1		3	7 0	7+967
44/	204	Wash Rack	BU00040ER	11 Oct 93	DRADS	URANITIM 238	96			70	> ;	KEA		23 9	8 2	1 82e+1
							2	2		60	>	REAL		23 9	8 2	937e+2
447	204	Wash Rack	BU00041ER	11-Oct 93	DRADS	GBOSS AT BHA	9	ţ								
447	204	Wash Rack	BLOOMIED	11 04 05	200	ONCOS ALCHA	140	1.1		_	>	<b>5</b> 0	BU00040ER	23.9	8.7	7 200.17
447	2	Mark Day	Discontinua di Contra di C	66 30	DKAUS	GROSS BETA	78	38		7	4	910	RIMONAORIB	330		73047
;	5 5	wash Kack	B000041 EK	11 Oct 93	DRADS	URANIUM 233 234	56	31		90	: >		Priocotorn	600	7 8	4 (bet 2
44/	204	Wash Rack	BU00041 ER	11 Oct 93	DRADS	URANIUM 235	5.3	8		9 6	> ;	2	BUCCOCADER	23 9	8 2	1 35e+2
447	504	Wash Rack	BU00041ER	11 Oct 93	DRADS	URANIUM 238	200	2 5		7 0	> :	d i	BU00040ER	23 9	8 2	2 76e+1
!								}		3	>	Ì	воссочовк	23 9	8 2	1 04e+3
447	204	Room 501	BU00043ER	11 Oct 93	DRADS	GROSS ALPHA	χ	9			;					
447	204	Room 501	BU00043ER	11 Oct 93	DRADS	GROSS BETA	2	,		-	>	REAL		11 27	9	1 216+2
447	204	Room 501	BI MON43FR	11 0et 93	Dove	PI I TOME A 230 M	S S	7.6		7	<	<b>REAL</b>		11 27	9	117042
447	204	Room 501	BLIOOMAED		2000	TEOTONIOM 239/240	0.013	0011	æ	100	<	REAL		11 27	4	436.2
447	200	Domination of	Autocotona Trioggraphic	56 150-1	DKADS	UKANIUM 233 234	49	12		90	>	REAL		: :		7-900
;	3 8	Koom 501	BUU0043EK	11 Oct 93	DRADS	URANIUM 235	88 0	0 49		0.5	> >	DEAT		7 ::	۰ ،	1 04e+
44/	504	Koom 501	BU00043ER	11 Oct 93	DRADS	URANIUM 238	34	2.6		, ,	. :	2 :		17 11	9	2 95e+0
								,		5	>	KEA.		11 27	9	1146+2
447	204	Room 502	BU00044ER	11 Oct 93	DRADS	GROSS ALPHA	\$20	1.1		,	;					
447	204	Room 502	BU00044ER	11 Oct 93	DRADS	GROSS BETA	089	2 5		7 (	>	REAL		12 03	23 5	475e+2
447	204	Room 502	BU00044ER	11 Oct 93	DPADS	PI I ITOMI NA 230/240	000	2 5		2	<	REAL		12 03	23 5	6 22e+2
447	204	Room 502	BI KOOO44ED	11 00 02	200	1 EO 1 ON 1 ON 2 59/240	9100	000	œ	0 002	<	REAL		12 03	215	1 464.2
447	204	Boom \$00	DI DOOG 4 ED		S CONTROL	UKANIUM 233 234	110	10		90	~	REAL		12.03	22.5	
447		Post 602	DI Joog 14 FB	11 001 93	DKAUS	UKANIUM 235	<b>8</b>	3.2		7	~	REAL		2 2 2	2 2 2	7.010
Ì	5	ZOC WOON	BUMM4EK	11 Oct 93	DRADS	URANIUM 238	840	11		90	۵ :	DEAT		12.03	667	) 98e+0
;	,	;								•	4	2		12.03	23 5	7 68e+2
44/	504	Koom 31	BU00047ER	09 Nov 93	DRADS	GROSS ALPHA	091	86		,	>					
44/	204	Room 31	BU00047ER	09 Nov 93	DRADS	GROSS BETA	45	-		٠,	- ;	EA.		1675	5.7	8 40e+2
447	201	Room 31	BU00047ER	09 Nov 93	DRADS	URANIUM 233 234	2			, ;	- ;	KEAL		16 75	5.7	2 36e+2
447	204	Room 31	BU00047ER	09 Nov 93	DRADS		, ,	, ,		C O	¥	REAL		1675	5.7	1 52e+2
447	204	Room 31	BI 100047FR	00 Nov 03	DDADe	(TO ANTH DAY 230	7	6/0		0.5	<b>&gt;</b>	REAL		1675	5.7	2 31641
						OKANIOM 238	210	20		0.5	٨	REAL		16.75	5.7	10043
447	204	Room 31	BI MON48FB	00 Now 03	DOADS	*174.1* 850.00	:									
447	204	Room 31	BI MONARED	00 Mon 63	20,400	OROSS ALFITA	081	=		٣	>	ΔĎΩ	BU00047ER	16.75	2.3	0.45-47
447	204	Room 31	DI 100046EB	60 100	SPA PO		63	3 5		7	>	DOL	BU00047FR	16.75		237.5
447	204	Poom 31	DIMONGEN	09 Nov 93	DRADS	UKANIUM 233 234	72	32		0.5	>	DUP	BI KNOWATER	16.75		2 31642
		rooll 31	DUMU48ER	09 Nov 93	DRADS	URANIUM 235	43	080		0.2	>	2	DI 100047EB	50.0	, ,	7 47e+7
<del>,</del>	<b>507</b>	Koom 31	BU00048ER	09 Nov 93	DRADS	URANIUM 238	210	21	В	0.5	۰ >	2 2	BI POOL TER	26.7	27	2 26e+1
447	204	Room 32	BUOOOSOER	09 Nov 93	DRADS	GBOSS AT BHA	7	;			•	i	NT LONG	6/9/	, ,	1 0e+3
447		Room 32	BUDOOSOER	00 Nov 03	DAAG	PI (TOWN PA 2200 to	9450	19		2	>	REAL.		12.51	27.7	5.16043
447	204	Room 32	BLOOOSOED	O No.	2000	FEOTONIOM 239/240	0 014	900		9000	>	REAL		12.51	, ,,	
	١		Macaoaa	62 1001 23	DRADS	UKANIUM 238	1600	2000		006	<b>&gt;</b>	REAL		12.51	27.7	6 13 24.3

Table 6-13 Smear Sample Results IHSS 204

						THE COMPOSITION TO					
				Pre-Rinsale S	Pre-Rinsate Smear Sample	Concentration*	ration	Post-Rinsate	Post-Rinsate Smear Sample	Concen	Concentration*
				Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Building	Room	SSHI	Area	udp)	(dpm/100 cm^2)	(pCvg)	(pCi/g)	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCvg)
447	31	204	_	24	0	1 96+3	0 0c+0	Post-Rinsate Smear	Post-Rinsate Smear Samples not collected for IHSS 204	for IHSS 20	4
447	31	204	7	12	9	9 7e+2	4 8c+2		•		
447	31	204	٣	9	0	4 8c+2	0 0e+0				
447	33	204	4	30	0	2 4e+3	0 06+0				
447	31	204	8	15	33	1 26+3	2.7e+3				
447	31	204	9	12	6	9 7e+2	720+2				
447	32	204	7	2600	13252	2 16+5	1 let6				
447	32	704	00	2000	11363	1 6e+5	9 let5				
447	32	204	0	2400	18939	1 9e+5	1 Se+6				
447	32	204	01	2000	14204	1 6e+5	1 1646				
447	32	204	Ξ	3200	28409	2 6c+5	2 3e+6				
447	32	204	12	2000	37878	4 0c+5	3 0c+6				
447	32	204	13	2200	12310	1 8c+5	99645				
447	32	204	7	3000	16098	2 4c+5	13046				
447	32	204	15	2600	12310	2 le+5	99645				
447	32	204	91	4000	28409	3 2c+5	23e+6				
447	32	204	11	4000	23674	3 2e+5	1 9e+6				
447	32	204	<b>8</b> 2	14000	132575	1 10+6	110+7				
447	32	204	61	0009	57878	4 8c+5	4 7c+6				
447	32	204	70	11000	71522	8 8c+5	S 8e+6				
447	32	204	21	0009	81895	4 8c+5	4 6c+6				
447	32	204	77	0009	28409	4 8c+5	23c+6				
447	32	204	23	8000	47348	6 4c+5	3 8c+6				
447	32	204	24	12000	151515	9.76+5	1 2c+7				
447	32	204	22	1600	12310	1 36+5	9 96+5				
447	32	204	92	4000	18939	3 2c+5	1 Se+6				
447	32	204	27	3000	12310	2 4c+5	9 9e+S				
447	32	704	28	1400	9469	1 10+5	7 6e+5				
447	32	204	53	12000	104166	9.7c+5	8 4c+6				
447	32	204	30	3000	16099	2 4c+5	1 36+6				
447	32	704	31	0009	96299	4 8c+5	5 3eH6				
447	32	204	32	2000	96299	4 0c+5	5 3e+6				
447	32	204	33	8000	47350	6 4c+5	3 8c+6				
447	32	204	34	10000	66290	8 0c+5	5 3e+6				
447	501	204	-	0	0	0.00	0 0e+0				
447	501	204	7	12	m	9 7c+2	2 4c+2				
447	501	204	٣	15	0	12c+3	0 06+0				
447	201	204	4	30	0	2 4c+3	0 0c+0				
447	501	204	\$	9	09	4 8c+2	4 8c+3				

Table 6-13 Smear Sample Results IHSS 204

						Pre-Rinsate Dust	ate Dust			Post-Rin	Post-Rineate Duct
				Pre-Rinsate S	Pre-Rinsate Smear Sample	Concentration*	ration*	Doet Disease	Doct Duente Camer		Switc Lydon
;				Alpha	Beta	Alpha	Beta	Alpha	smeur sumpte Beta	Concen	Concentration" Unha Reta
Building	Room	SSHI	Area	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCVg)	$(dpm/100 cm^2)$	$(dpm/100 cm^{2})$	$(pCV_R)$	(pCv <sub>P</sub> )
447	502	204	7	102	114	8 2c+3	9.26+3				
447	202	204	<b>∞</b>	132	891	1 1c+4	1 4c+4				
447	202	204	6	83	162	8 0c+3	1 3c+4				
447	<b>2</b> 05	204	2	222	243	1 8c+4	2.0c+4				
447	202	204	11	129	219	1 0c+4	1 8c+4				
447	202	204	12	153	222	1 2c+4	1 8c+4				
447	202	204	13	174	279	1 4c+4	2 2e+4				
447	202	204	4	123	156	9 9e+3	1 36+4				
447	205	204	15	198	213	1 6c+4	1 7c+4				
447	202	204	91	1359	3834	1 lets	3 16+5				
447	202	204	11	336	588	2 7c+4	4 7c+4				
447	202	204	28	294	426	2 4c+4	3 46+4				
447	<b>2</b> 02	204	61	342	576	2 8c+4	4 6c+4				
447	205	204	20	324	594	2 6c+4	4 8c+4				
447	202	204	21	135	285	1 16+4	2 3e+4				
447	502	204	22	279	372	2 2c+4	3 0c+4				
447	205	204	23	273	504	2 2c+4	4 1c+4				
447	205	204	<b>54</b>	699	1551	5 4c+4	1 2c+5				
447	205	204	52	417	1029	3 4c+4	8 3c+4				
447	205	204	56	243	303	2 0c+4	2 4c+4				
447	205	204	21	208	2331	5 7c+4	1 9e+5				
447	<b>2</b> 05	504	<b>58</b>	447	<i>472</i>	3 6c+4	7 Sc+4				
44/	202	704	<b>R</b> :	408	636	3 3e+4	5 le+4				
44/	205	204	္က ;	486	711	3 9e14	5 7c+4				
44/	707	707	<del>-</del> 5	£ :	768	3 0€+4	6 2c+4				
744	202	707	75	114.	288	3 3e+4	4 7c+4				
447	207 201 W.P.	<b>7</b> 07	ç -	189	339	1 Sc+4	2 Jc+4				
447	501WR	50.5	۰ ،	671	967	1 0c+4	6 0c+4				
777	601105	707	7 6	917	194	1 7c+4	9 6e+4				
, ;	SA TOC	504	<b>.</b>	<b>3</b>	132	8 0c+3	1 1c+4				
447	301 W.K	707	4 ,	228	807	1 8c+4	6 Sc+4				
44/	301WK	204	so .	42	81	3 4c+3	1 4c+3				
447	301WK	504	9	12	0	9 7c+2	0 0e+0				
44/	301WK	704	7	m	0	2 4c+2	0.00				
447	501WR	504	<b>∞</b>	3	9	2 4c+2	4 8c+2				
447	501WR	204	6	12	9	9 7c+2	4 8c+2				
447	SOI WR	204	02	6	not counted	7 2c+2					

\* Calculated assuming 560 mg of dust per square meter

Table 6-14
Radionuclides Detected in Hot Water Rinsate Samples
IHSS 211

Building	SSIII	Location	Sample Number	Sample Date	Test Group	Radionuclide	Result (pCvL)	Error	Error Qualifier	Detection Limit (pCVL)	Validation Code	Code	QC Partner*	Rinsale Volume (L)	Rinsale Area (m^2)	Concentration in Dust** (pCvg)
881	211	IHSS	BU0000ZER	09 Aug 93	DRADS	AMERICIUM-241	000	9000	Bí	0 004	>	REAL		107	17.8	7 51e 3
881	211	IHSS	BU00002ER	09-Aug 93	DRADS	GROSS ALPHA	1.1	0 93		190	>	REAL		107	178	7 62e+0
188	211	IHSS	BU00002ER	09 Aug 93	DRADS	GROSS BETA	19	2.5		26	>	REAL		107	17.8	2 046+1
881	211	IHSS	BU00002ER	09 Aug 93	DRADS	PLUTONIUM 239/240	15	0 024	æ	0 003	∢	REAL		107	17.8	16161
188	211	IHSS	BU00002ER	09 Aug 93	DRADS	RADIUM 226	65	019	æ	0 24	∢	REAL		107	178	6 98e-1
881	2112	IHSS	BU00003ER	09 Aug 93	DRADS	GROSS ALPHA	7.4	0 -		0 65	>	DO	BU00002ER	107	17.8	7 94e+0
188	211	IHSS	BU00003ER	09 Aug 93	DRADS	GROSS BETA	91	2.4		26	>	DO	BU00002ER	107	17.8	1 726+1
881	211	IHSS	BU00003ER	09 Aug 93	DRADS	RADIUM 226	14	0 0 0 0	-	010	<	DOP	BU00002ER	107	17.8	1 50e 1
881	211	IHSS	BU00003ER	09 Aug 93	DRADS	URANIUM 233 234	62	1.7	æ	690 0	<	DO	BU00002ER	107	17.8	6 666+0
881	211	IHSS	BU00003ER	09 Aug-93	DRADS	URANIUM 235	25	0 29	-	690 0	∢	DUP	BU00002ER	107	17.8	2 68e 1
1881	211	IHSS	BU00003ER	09 Aug 93	DRADS	URANTUM 238	99	0 48		0 12	∢	DO	BU00002ER	107	17.8	6 98e 1
188	211	Permeter	BU00006ER	11 Aug 93	DRADS	GROSS ALPHA	1 6	0 41	-	037	>	REAL		9 47	6	9 026+0
881	211	Peruneter	BU00006ER	11 Aug 93	DRADS	GROSS BETA	. 65	2.1		29	>	REAL		9 47	3	3 336+1
881	211	Perimeter	BU00006ER	11 Aug 93	DRADS	PLUTONIUM 239/240	810	0 008	æ	0 002	<	REAL		9 47	60	1 01e 1
881	211	Peruneter	BU00006ER	11 Aug 93	DRADS	URANIUM 233 234	1.4	95 0	æ	011	∢	REAL		947	3	7 89e+0
88	21.1	Peruneter	BU00006ER	11 Aug 93	DRADS	URANIUM 235	13	017	•	011	∢	REAL		947	6	7 33e 1
881	211	Peruneter	BU00006ER	11 Aug 93	DRADS	URANIUM 238	13	017	-	011	∢	REAL		947	ED.	7 33e 1
881	211	Pathway	BU00008ER	11 Aug 93	DRADS	GROSS ALPHA	47 90	-		4	>	REAL		15.32	Ξ	1 196+1
881	211	Pathway	BU00008ER	11 Aug 93	DRADS	GROSS BETA	61	2.2		3.0	>	REAL		15 32	=	1 67e+1
881	211	Pathway	BU00008ER	11 Aug 93	DRADS	PLUTONIUM 239/240	03	0 008	æ	0000	∢	REAL		15 32	=	497e2
881	211	Pathway	BU00008ER	11 Aug 93	DRADS	URANIUM 233 234	1.5	990		014	∢	REAL		15 32	=	3 73e+0
881	112	Pathway	BU00008ER	11 Aug 93	DRADS	URANIUM 235	61	0 22	ſ	0 053	∢	REAL		15 32	Ξ	4 730-1
188	<u>.</u>	Pathway	BU00008ER	11 Aug 93	DRADS	URANIUM 238	33	0 29	-	0 053	∢	REAL		15 32	=	7 96e 1
881	211	Pathway	BU00009ER	11 Aug 93	DRADS	GROSS ALPHA	4	0 54		0 54	>	DO	BU00008ER	1532	=	5 97e+0
881	211	Pathway	BU00009ER	11 Aug 93	DRADS	GROSS BETA	8	2.1		26	>	DOP	BU00008ER	1532	=	2216+1
188	211	Pathway	BU00009ER	11 Aug 93	DRADS	PLUTONIUM 239/240	013	9000	æ	0 003	∢	DOP	BU00008ER	15 32	=	3 236 2
881	211	Pathway	BU00009ER	11 Aug 93	DRADS	URANIUM 233 234	13	95 0		0 14	∢	DOP	BU00008ER	15 32	=	3 23e+0
88	211	Pathway	BU00009ER	11 Aug 93	DRADS	URANIUM 238	2	0.03	-	0 074	<	9	BU00008ER	15.32	=	4 07.0

• The date for IHSS 211 QC Partner samples was not unput into RFEDS but has been manually entered here •• Calculated assuming 560 mg dust per square meter

Table 6-15 Smear Sample Results IHSS 211

						Pre-Rinsate Dust	tte Dust			Post-Rin	Post-Rinsate Dust
				Pre-Rinsate S.	Pre-Rinsate Smear Sample	Concentration*	ration*	Post-Rinsate &	Post-Rinsate Smear Sample	Concentration*	tration*
				Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Building	Room	SSHI	Area	(dpm/100 cm^2)	(dpm/100 cm^2)	(bCvg)	(bCvg)	(dpm/100 cm^2)	(dpm/100 cm^2)	(pCvg)	(pCi/g)
881	266B	211	-	9	0	4 8c+2	0 0c+0	0	0	0 0e+0	0 0c+0
881	266B	211	7	0	0	0 000	0 0c+0	0	0	0 0c+0	0 0c+0
881	266B	211	ю	0	81	0 000+0	1 4c+3	0	24	0 0c+0	196+3
881	266B	211	4	3	51	2 4c+2	4 le+3	0	0	0 0e+0	0 0c+0
881	266B	211	S	0	0	0 00+0	0 0 <del>c+</del> 0	0	24	0 0e+0	1 96+3
881	266B	211	9	3	0	2 4c+2	0 0 <del>c+</del> 0	0	0	0 0 <del>c+</del> 0	0 0c+0
881	266B	211	7	ю	0	2 4c+2	0 000+0	0	3	0 00+0	2 4c+2
188	266B	211	99	3	36	2 4c+2	2.9e+3	9	12	4 8c+2	9 7c+2
881	266B	211	6	0	0	0 0c+0	0 0 0 0 0	9	27	4 8c+2	2 2c+3
188	266B	211	01	3	0	2 4c+2	0 000	0	0	0 0c+0	0.00+0
881	266B	211	Ξ	0	0	0 0e+0	0 0 <del>c+</del> 0	0	٣	0 00+0	2 4c+2
881	266B	211	12	0	0	0 0c+0	0 0e+0	æ	0	2 4e+2	0 0c+0
881	266B	211	13	0	0	0 0c+0	0 0e+0	0	0	0 0c+0	0 0c+0
881	266B	211	14	3	9	2 4e+2	4 8c+2	0	0	0 0c+0	0 0c+0
881	266B	211	15	9	33	4 8c+2	2 7e+3	æ	24	2 4e+2	1 9e+3
881	266B	211	16	9	m	4 8c+2	2 4e+2	6	0	7 2c+2	0 0c+0
881	266B	211	17	0	36	0 0e+0	2 9e+3	3	27	2 4c+2	2 2e+3
881	266B	211	81	0	6	0 00+0	7 2e+2	0	3	0 0e+0	24c+2
881	26 <b>6B</b>	211	61	3	0	2 4e+2	0 0c+0	0	0	0 0000	0 0e+0
188	266B	211	20	3	0	2 4e+2	0 0c+0	0	9	0.000	4 8c+2
188	266B	211	21	3	0	2 4 <del>c+</del> 2	0 0e+0	0	0	0 0 <del>c+</del> 0	0 0c+0
881	266B	211	22	0	0	0 00+0	0 0c+0	3	0	2 4c+2	0 00-
881	266B	211	23	0	0	0 0c+0	0 0c+0	0	27	0 000+0	2 2c+3
881	266B	211	24	0	0	0 0c+0	0 0e+0	3	e,	2 4c+2	2 4c+2
188	266B	211	22	0	0	0.000	0 0e+0	æ	15	2 4 <del>c+</del> 2	1 2e+3
881	266B	211	56	3	0	2 4c+2	0 0c+0	0	18	0 000+0	1 4c+3
881	266B	211	27	0	0	0 0e+0	0 0c+0	3	0	2 4c+2	0.00
188	266B	211	28	9	0	4 8c+2	0 0e+0	3	15	2 4c+2	1 26+3
188	266B	211	52	0	0	0 0e+0	0 0c+0	3	0	2 4c+2	0 0c+0
881	266B	211	30	0	0	0.000	0.000	0	e	0 0c+0	2 4c+2
881	266B	211	31	æ	0	2 4e+2	0 0 <del>c+</del> 0	0	0	0.000	0 0c+0
100	dy		ç	•	اد	01-00	1 3.13	•	•	•	

Calculated assuming 560 mg of dust per square meter

Table 6-16
Beta and Gamma Dose-Rate Survey Data
IHSS 211

				Gamma Dose-Rate	Beta Dose-Rate
Building	Room	IHSS	Area	(mrem/hr)	(mrem/hr)
881	266B	211	1	0	0
881	266B	211	2	0	0
881	266B	211	3	0	0
881	266B	211	4	0	0
881	266B	211	5	0	0
881	266B	211	6	0	0
881	266B	211	7	0	0
881	266B	211	8	0	0
881	266B	211	9	0	0
881	266B	211	10	0	0
881	266B	211	11	0	0
881	266B	211	12	0	0
881	266B	211	13	0	0
881	266B	211	14	0	0
881	266B	211	15	0	0
881	266B	211	16	0	0 4
881	266B	211	17	0	0 4
881	266B	211	18	0	0
881	266B	211	19	0	0
881	266B	211	20	0	0
881	266B	211	21	0	0
881	266B	211	22	0	0
881	266B	211	23	0	0
881	266B	211	24	0	0
881	266B	211	25	0	0
881	266B	211	26	0	0
881	266B	211	27	0	0
881	266B	211	28	0	0
881	266B	211	29	0	0
881	266B	211	30	0	0
881	266B	211	31	0	0
881	266B	211	32	0	0

Page 1 of 1

Table 6-17 Radionuclides Detected in Hot Water Rinsate Samples IHSS 217

881 217 881 217 881 217 881 217 881 217	IHSS IHSS IHSS	Number	Date	Group	Radionuclide	(pCVL)	Error	Error Qualifier	Lımıt (pCVL)	Validation Code	QC Code	QC Partner	Volume (L)	Area (m^2)	Concentration in Dust* (pCVg)
	IHSS IHSS	BU00017ER	17 Aug 93	DRADS	AMERICTUM 241	0.21	0 032		0 004	>	REAL		22 97	61	1 41e+0
	IHSS	BU00017ER	17 Aug 93	DRADS	GROSS ALPHA	8	11		0 40	>	REAL		22 97	61	2 02e+2
		BU00017ER	17-Aug 93	DRADS	GROSS BETA	8	56		26	>	REAL		22 97	61	1 346+2
	IHSS	BU00017ER	17 Aug 93	DRADS	PLUTONIUM 239/240	0 037	0 014		0 002	>	REAL		22 97	61	2 496-1
	IHSS	BU00017ER	17 Aug 93	DRADS	RADIUM 226	<b>8</b> 2	0 040	В	0900	∢	REAL		22 97	61	1 21 6+0
	IHSS	BU00017ER	17 Aug 93	DRADS	URANIUM 233 234	22	33		013	>	REAL		22 97	61	1 48e+2
881 217	IHSS	BU00017ER	17-Aug 93	DRADS	URANIUM 235	160	0 43		0 064	>	REAL		22 97	61	6 12e+0
881 217	IHSS	BU00017ER	17 Aug 93	DRADS	URANIUM 238	15	2.5		0 064	>	REAL		22 97	61	1 01 0+2
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	AMERICTUM 241	0 22	0 038		0 002	>	DUP	BU00017ER	22 97	19	1 48e+0
881 217	IHSS	BU00018ER	17-Aug 93	DRADS	GROSS ALPHA	4	23		190	>	DOP	BU00017ER	22 97	61	2.76e+2
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	GROSS BETA	92	28		2.7	>	DOP	BU00017ER	22 97	61	1 75e+2
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	PLUTONIUM 239/240	0 042	0 012		0 005	>	DCI	BU00017ER	22 97	61	2 82e 1
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	RADIUM 226	77	0 030	B	0 040	∢	DOP	BU00017ER	22 97	61	1 41e+0
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	URANIUM 233 234	27	39		0 091	>	DOP	BU00017ER	22 97	61	1 82e+2
881 217	IHSS	BU00018ER	17 Aug 93	DRADS	URANIUM 235	080	0 40		160 0	>	DO	BU00017ER	22 97	19	6 05e+0
881 217	HISS	BU00018ER	17 Aug 93	DRADS	URANTUM 238	13	27		0 001	>	DUP	BU00017ER	22 97	61	1 14e+2
881 217	Peruneter	BU00020ER	17 Aug 93	DRADS	AMERICIUM 241	0 017	800 0		0 004	>	REAL		14 34	46	9 46e 2
881 217	Peruneter	BU00020ER	17 Aug 93	DRADS	GROSS ALPHA	69	0 78		0 40	>	REAL		1434	46	3 84c+1
881 217	Perimeter	BU00020ER	17 Aug 93	DRADS	GROSS BETA	15	24		2.7	>	REAL		1434	46	8 35e+1
881 217	Permeter	BU00020ER	17 Aug 93	DRADS	PLUTONIUM 239/240	9100	9000		0 002	>	REAL		14 34	46	8 91e 2
881 217	Peruneter	BU00020ER	17 Aug 93	DRADS	RADIUM 226	23	0 040	B	0900	∢	REAL		14 34	46	1 39e+0
881 217	Peruneter	BU00020ER	17 Aug 93	DRADS	URANIUM 233 234	9 9	13		011	>	REAL		14 34	46	3 12e+1
881 217	Perimeter	BU00020ER	17 Aug 93	DRADS	URANIUM 235	0 20	0 20	-	0 042	>	REAL		14 34	46	- 11 <del>6+</del> 0
881 217	Peruneter	BU00020ER	17 Aug 93	DRADS	URANIUM 238	2.3	0 74		0 042	>	REAL		14 34	46	1 28e+1

Calculated assuming 560 mg of dust per square meter

						Pre-Rinsate Dust	ate Dust			Post-Rin.	Post-Rinsate Dust
				Pre-Rinsate S	Pre-Rinsate Smear Sample	Concentration*	tration*	Post-Rinsate	Post-Rinsate Smear Sample	Concentration*	tration*
				Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta
Building	Room	SSHI		Area (dpm/100 cm^2) (dpm	(dpm/100 cm^2)	(pCvg)	(pCvg)	(dpm/100 cm^2)	(dpm/100 cm^2)	(bCvg)	(pCvg)
881	131C	217	-	m	0	2 4c+2	0 0c+0	0	ĸ	0 0c+0	2 46+2
881	1310	217	2	0	12	0 0000	9 7c+2	9	0	4 8c+2	0 0c+0
881	131C	217	3	0	18	0 000	1 4c+3	0	12	0 00-10	9 7c+2
881	1310	217	4	0	30	0 0000	2 4c+3	3	0	2 4c+2	0 0c+0
881	131C	217	×	3	18	24c+2	1 4c+3	3	6	2 4c+2	7 2e+2
188	131C	217	9	9	0	4 8c+2	0 0c+0	0	30	0 0c+0	2 4c+3
881	131C	217	7	9	39	4 8c+2	3 1c+3	0	6	0 0c+0	7 2e+2
881	131C	217	<b>∞</b>	9	3	4 8c+2	24c+2	3	30	2 4c+2	2 4e+3
188	131C	217	6	0	0	0.000	0 0c+0	0	6	0 0c+0	7 2e+2
881	131C	217	10	က	27	2 4c+2	2 2e+3	3	33	2 4c+2	2.7e+3
881	131C	217	=	0	24	0 000	1 9e+3	0	9	0 0c+0	4 8c+2
881	131C	217	12	e	36	2 4c+2	2 9c+3	9	24	4 8c+2	196+3
881	131C	217	13	9	24	4 8c+2	1 %+3	6	m	726+2	2 4c+2

\* Calculated assuming 560 mg of dust per square meter

Table 6-19
Beta and Gamma Dose-Rate Survey Data
IHSS 217

Building	Room	IHSS	Area	Gamma Dose-Rate (mrem/hr)	Beta Dose-Rate (mrem/hr)
881	131C	217	1	0	0 4
881	131C	217	2	0	0 4
881	131C	217	3	0	0 4
881	131C	217	4	0	0 4
881	131C	217	5	0	0 4
881	131C	217	6	0	0 4
881	131C	217	7	0	0 4
881	131C	217	8	0	0 4
188	131C	217	9	0 1	0
881	131C	217	10	0 1	0
881	131C	217	11	0 1	0
881	131C	217	12	0	0
881	131C	217	13	0	0

Section 7.0

29 \_\_\_\_\_\_\_\_

\_\_\_\_\_\_

.

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	70, Final
Inside Building Closures	Page	1 of 2

#### 7.0 SUMMARY AND CONCLUSIONS

TM#1 presents an evaluation of the data collected during the OU15 Stage I and II field investigations with three specific objectives

- To determine if Stage III field work would be necessary for any IHSS,
- To determine if verification sampling would be required to show compliance with the established RCRA closure performance standards for each IHSS, and
- To determine if any additional CERCLA evaluation would be required with regard to radionuclides and beryllium at any IHSS

This section summarizes the findings of the evaluation of the OU15 IHSSs, and presents specific recommendations for further action

## 7.1 Summary of Findings

The analyses presented in Sections 2 0, 5 0, and 6 0 included specific determinations for each IHSS of

- whether indoor organic and inorganic compound contamination within each IHSS is at levels low enough to allow for clean closure of the unit under RCRA,
- whether the levels of radiological contamination within each IHSS require additional consideration, and
- whether additional Stage III field work is required to delineate any potential outdoor releases from any of the IHSSs

A summary of the recommendations for each IHSS is provided in Table 7-1

The evaluations of historical information and the visual inspections presented in Section 2 0 indicated that no evidence of releases migrating to outdoor locations existed. Therefore, no Stage III field work is anticipated at this time. The evaluations of RCRA-

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	70, Final
Inside Building Closures	Page	2 of 2

regulated constituents of regulatory concern provided in Section 5 0 showed the presence of detectable levels of cyanide at IHSS 217 Therefore, verification sampling is proposed for IHSS 217 for cyanide All other IHSSs did not show detectable levels of constituents of regulatory concern

The CERCLA evaluations in Section 6.0 indicated that the radionuclide levels detected at all IHSSs were below levels of concern for workers, therefore, no additional action is proposed for radionuclides. Two IHSSs, 179 and 180, showed levels of removable beryllium in excess of the RFP beryllium smear control level. Sampling data did not indicate the IHSSs as the source of the beryllium, and showed beryllium levels as high or higher outside the IHSS than within it. Beryllium decontamination will need to be addressed under the D&D and economic redevelopment programs according to RFP procedures. No additional action is proposed as part of the Phase I RFI/RI for OU15 with regard to beryllium.

#### 7.2 Recommendations

Verification sampling for cyanide at IHSS 217 is recommended. Existing data is sufficient to characterize all other IHSSs, and to complete the Draft Phase I RFI/RI report for OU15. Verification sampling using hot water rinsate collection equipment should proceed immediately using identical equipment and procedures as described in Section 2.0 of this document, and as described in the Work Plan. Upon completion of the verification sampling and receipt of the results, the Draft Phase I RFI/RI report should be completed and submitted. If verification sampling shows the presence of detectable levels of cyanide at IHSS 217, then a recommendation for decontamination procedures will be required. If the verification sampling does not show the presence of cyanide at IHSS 217, then a No Further Action recommendation can be made for all IHSSs.

Table 7-1 Decision Summary Matrix

	Indoor E	valuation	
IHSS	RCRA (Verification Sampling)	CERCLA (Further Investigation)	Stage III Field Work
178	NFA	NFA	NFA
179	NFA	NFA	NFA
180	NFA	NFA	NFA
204	NFA	NFA	NFA
211	NFA	NFA	NFA
217	Cyanıde	NFA	NFA

NFA = No Further Action

Section 8.0

Technical Memorandum Number 1	Manual	RFP/ER-OU15 01-TM 01-93
for Operable Unit 15 Phase I RFI/RI	Section	8 0, Final
Inside Building Closures	Page	1 of 1

#### 8.0 SCHEDULE

This section presents the proposed schedule for OU15 activities leading up to the submittal of the Draft Phase I RFI/RI Report. At this time, no Stage III field work has been proposed. In addition, no further action has been proposed with regard to RCRA clean closure of the indoor units, with the exception of verification sampling for cyanide in IHSS 217. No further investigatory action has been proposed for the six OU15 IHSSs with respect to CERCLA. The proposed schedule for concurrence on TM#1, verification sampling of IHSS 217 and the submittal of the Draft Phase I RFI/RI Report is as follows.

Submittal of Final Technical Memorandum Number 1

TM#1 Review Period

Comment Resolution

Concurrence on TM#1

Verification Sampling

Submittal of Draft Phase I RFI/RI Report

10 May 1994

11 May 1994 - 24 May 1994

25 May 1994 - 2 June 1994

3 June 1994

10 May 1994 - 24 June 1994

1 August 1994